



GERLAX®

BLUETOOTH SPEAKER

ADD:New Asia International Digital City No, 55 Xiti Erma Rosd, Guangzhou

Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

型号	产品图	产品图	卖点	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Product Picture	SELLING POINTS	Price rmb	OUTER CTN/ INNER BOX (PCS)	Carton size (CM)			CBM/CTN (m³)	KG/CTN	SPECIFICATIONS
GS-33			Wireless With dual microphone (Black)	¥ 149.00	12	56.1	37.4	41.3	0.0867		Bluetooth version: 5.4 Functions: TF, USB, BT,AUX, KTV Transmission distance: 10 meters Output power: 14W Running time: 2-4 hours Frequency effect: 80HZ-16KHZ Speaker: 105MM 3 euro 14W Input power: 5V 1A Charging time: 3.5 hours Battery model: 18650 Li-ion 3000 MA

GERLAX®

FM CAR KIT

ADD:New Asia International Digital City No, 55 Xiti Erma Rosd, Guangzhou

Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

型号	产品图	产品图	卖点	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Product Picture	SELLING POINTS	Price rmb	OUTER CTN/ INNER BOX (PCS)	Carton size (CM)			CBM/CTN (m³)	KG/CTN	SPECIFICATIONS
C-M9			good price	¥ 14.50	100	55.0	31.5	42.0	0.0792	6.9	1.material: ABS 2.surface process: fine lines, highlights 3.Features: Appearance patent/white large screen, voltage separate display 4. Enter 12-24 5. Output: 5V-1.5A or 5V-3.1A C port: 9V-2A 6. Total power: 7.5-15W 7. Output type: USB, Type-C 8. Protocol: Bluetooth 5.0 9. Hardware functions: FM transmission, Bluetooth, USB charging, reading U disk, TF/ color light
GC-M1			ambient lighting	¥ 18.80	100	55.0	31.5	42.0	0.0728	7.5	1.material: ABS 2.surface process: fine lines, highlights 3.Features: Appearance patent/white large screen, voltage separate display 4. Enter 12-24 5. Output: 5V-1.5A or 5V-3.1A C port: 9V-2A 6. Total power: 7.5-15W 7. Output type: USB, Type-C 8. Protocol: Bluetooth 5.0 9. Hardware functions: FM transmission, Bluetooth, USB charging, reading U disk, TF/ color light, EQ function
GC-M2			ambient lighting	¥ 18.80	100	55.0	31.5	42.0	0.0728	7.7	1.material: ABS 2.surface process: fine lines, highlights 3.Features: Appearance patent/white large screen, voltage separate display 4. Enter 12-24 5. Output: 5V-1.5A or 5V-3.1A C port: 9V-2A 6. Total power: 7.5-15W 7. Output type: USB, Type-C 8. Protocol: Bluetooth 5.0 9. Hardware functions: FM transmission, Bluetooth, USB charging, reading U disk, TF/ color light, EQ function
GC-M3			ambient lighting	¥ 20.20	100	55.0	31.5	42.0	0.0728	7.7	1.material: ABS 2.surface process: fine lines, highlights 3.Features: Appearance patent/white large screen, voltage separate display 4. Enter 12-24 5. Output: 5V-1.5A or 5V-3.1A C port: 9V-2A 6. Total power: 7.5-15W 7. Output type: USB, Type-C 8. Protocol: Bluetooth 5.0 9. Hardware functions: FM transmission, Bluetooth, USB charging, reading U disk, TF/ color light, EQ function
GC-M4			ambient lighting	¥ 18.80	100	55.0	31.5	42.0	0.0728	7.7	1.material: ABS 2.surface process: fine lines, highlights 3.Features: Appearance patent/white large screen, voltage separate display 4. Enter 12-24 5. Output: 5V-1.5A or 5V-3.1A C port: 9V-2A 6. Total power: 7.5-15W 7. Output type: USB, Type-C 8. Protocol: Bluetooth 5.0 9. Hardware functions: FM transmission, Bluetooth, USB charging, reading U disk, TF/ color light, EQ function
GC-M5			LED ambient lighting	¥ 18.80	100	55.0	31.5	42.0	0.0728	7.3	1.material: ABS 2.surface process: fine lines, highlights 3.Features: Appearance patent/white large screen, voltage separate display 4. Enter 12-24 5. Output: 5V-1.5A or 5V-3.1A C port: 9V-2A 6. Total power: 7.5-15W 7. Output type: USB, Type-C 8. Protocol: Bluetooth 5.0 9. Hardware functions: FM transmission, Bluetooth, USB charging, reading U disk, TF/ color light, EQ function
GC-M6			multiport	¥ 26.50	100	55.0	31.5	42.0	0.0728	9.8	1.material: ABS 2.surface process: fine lines, highlights 3.Features: Appearance patent/white large screen, voltage separate display 4. Enter 12-24 5. Output: 5V-1.5A or 5V-3.1A C port: 9V-2A 6. Total power: 7.5-15W 7. Output type: USB, Type-C 3IN1 CABLE (IP,MICRO,TC) 8. Protocol: Bluetooth 5.0 9. Hardware functions: FM transmission, Bluetooth, USB charging, reading U disk, TF/ color light, EQ function
GC-M7			quick charge	¥ 24.50	100	55.0	31.5	42.0	0.0728	7.5	1.material: ABS 2.surface process: fine lines, highlights 3.Features: Appearance patent/white large screen, voltage separate display 4. Enter 12-24 5. Output: 5V-1.5A or 5V-3.1A C port: 9V-2A 6. Total power: 25-35W 7. Output type: USB, Type-C SUPPORT FAST CHARGING 8. Protocol: Bluetooth 5.3 9. Hardware functions: FM transmission, Bluetooth, USB charging, reading U disk, color light
GC-M8			quick charge	¥ 30.40	100	55.0	31.5	42.0	0.0728	8.17	1.material: ABS 2.surface process: fine lines, highlights 3.Features: Appearance patent/white large screen, voltage separate display 4. Enter 12-24 5. Output: 5V-2.4A or 5V-3.1A C port: 9V-3A 6. Total power: 25-38W 7. Output type: USB SUPPORT FAST CHARGING, Type-C SUPPORT FAST CHARGING 8. Protocol: Bluetooth 5.3 9. Hardware functions: FM transmission, Bluetooth, USB charging, reading U disk, TF/ color light, EQ function

GERLAX[®]

TEMPERED GLASS

ADD:New Asia International Digital City No, 55 Xiti Erma Road, Guangzhou

Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

型号	产品图	产品图	型号表	数量	价格	数量/箱	箱规	立方数	重量/箱	详情
Model	Product Picture	Product Picture	Model List	QTY	Price rmb	QTY CTN	Carton size (CM)	CBM/CTN (m³)	KG/CTN	Standard
GG-101			IP 11,11 Pro, 11 ProMax, IP 12/12 Pro, 12ProMax, IP 13/14,13Pro,13ProMax, IP 14 Pro,14 Pro Max,14 Plus, IP 15,15 Pro ,15 ProMax,15Plus IP 16,16 PLUS,16 PRO,16 PRO MAX	/	¥4.30	200	43.0 39.0 48.0	0.0805	14.5KG	GERLAX High Definition Glass Function : ①Phones Screen Protector ②99% Highly Clear ③2.5D Anti-explosion ④add anti-static function(ESD) ⑤Electroplating oil(AF)
GG-102			IP 11,11 Pro, 11 ProMax, IP 12/12 Pro, 12ProMax, IP 13/14,13Pro,13ProMax, IP 14 Pro,14 Pro Max,14 Plus, IP 15,15 Pro ,15 ProMax,15Plus IP 16,16 Plus,16 Pro,16 Pro MAX	/	¥5.50	200	43.0 39.0 48.0	0.0805	14.5KG	GERLAX Privacy Glass Function : ①Phones Screen Protector ②Protect the privacy ③Original hole position design ④Full screen coverage ⑤Electroplating oil(AF) ⑥add anti-static function(ESD)
GG-103			IP 11,11 Pro, 11 ProMax, IP 12/12 Pro, 12ProMax, IP 13/14,13Pro,13ProMax, IP 14 Pro,14 Pro Max,14 Plus, IP 15,15 Pro ,15ProMax,15Plus IP 16,16 Pro ,16ProMax,16Plus Other models 1000pcs can make	≤20000	¥1.40	500	47.0 25.5 20.0	0.0240	10.8	GERLAX High Definition 10 IN 1 Glass Function : ①Phones Screen Protector ②99% Highly Clear ③2.5D Anti-explosion ④add anti-static function(ESD)
				≥20001-100000	¥1.20					
				≥100001	¥1.15					
GG-104			For iPhone, For Samsung, OPPO,VIVO,Realme, XIAOMI,HUAWEI,Motorola, The number of different phone types of the same model can be combined	≤50000	¥2.20	500	47.0 25.5 20.0	0.0240	11	GERLAX Privacy Glass 10 IN 1 Function : ①Phones Screen Protector ②Protect the privacy ③2.5D Anti-explosion ④add anti-static function(ESD) ⑤The bottom plate of the tempered glass is 0.3mm
				≥50001-100000	¥1.90					
				≥100001	¥1.70					
GG-105			IP 11,11 Pro, 11 Pro Max, IP 12/12 Pro, 12 Pro Max, IP 13/14,13 Pro,13 Pro Max, IP 14 Pro,14 Pro Max,14 Plus, IP 15,15 Pro ,15 ProMax,15Plus IP 16,16 Pro ,16ProMax,16Plus	≤20000	¥1.90	500	47.0 25.5 20.0	0.0240	15	GERLAX High Definition 10 IN 1 (with small packing) Glass Function : ①Phones Screen Protector ②99% Highly Clear ③2.5D Anti-explosion ④add anti-static function(ESD) ⑤The bottom plate of the tempered glass is 0.3mm ⑥Alcohol Packets
				≥20001-100000	¥1.70					
				≥100001	¥1.60					
GG-106			For iPhone For Samsung, OPPO,VIVO,Realme, XIAOMI,HUAWEI,Motorola, The number of different phone types of the same model can be combined	≤10000	¥2.50	500	47.0 25.5 20.0	0.0240	15.2	GERLAX Privacy 10 IN 1 (with small packing) Glass Function : ①Phones Screen Protector ②Protect the privacy ③2.5D Anti-explosion ④add anti-static function(ESD) ⑤The bottom plate of the tempered glass is 0.3mm ⑥Alcohol Packets
				≥10001-50000	¥2.40					
				≥50001	¥2.30					
GG-107			For iPhone, For Samsung, OPPO,VIVO,Realme,XIAOMI	≤20000	¥2.00	500	47.0 25.5 20.0	0.0240	10.8	GERLAX 18D Airbag Glass Function : ①Phones Screen Protector ②99% Highly Clear ③2.5D Anti-explosion ④add anti-static function(ESD) ⑤The bottom plate of the tempered glass is 0.3mm
				≥20001-50000	¥1.90					
				≥50001	¥1.70					
GG-108			For iPhone, For Samsung, OPPO,VIVO,Realme,XIAOMI	≤10000	¥3.00	500	47.0 25.5 20.0	0.0240	11	GERLAX 18D Airbag Privacy Glass Function : ①Phones Screen Protector ②Protect the privacy ③2.5D Anti-explosion ④add anti-static function(ESD) ⑤The bottom plate of the tempered glass is 0.3mm
				≥10001-30000	¥2.80					
				≥30001	¥2.60					
GG-109			IP X/XS/11 PRO,XR/11, XS MAX/11 PRO MAX, 12/12 PRO,12 PRO MAX, 13/13 PRO/14, 13 PRO MAX/14 PLUS,14 PRO,14 PRO MAX, 15,15 PLUS,15 PRO,15 PRO MAX IP 16,16 Pro ,16ProMax,16Plus GG-109 and GG-110 can be mixed.	≤20000	¥3.50	200	47.0 25.5 20.0	0.0240	13	GERLAX Magic Glass Box Function : ①Phones Screen Protector ②99% Highly Clear ③2.5D Anti-explosion ④add anti-static function(ESD) ⑤Easier to fit
				≥20001-100000	¥3.30					
				≥100001	¥2.90					
GG-110			IP X/XS/11 PRO,XR/11, XS MAX/11 PRO MAX, 12/12 PRO,12 PRO MAX, 13/13 PRO/14, 13 PRO MAX/14 PLUS,14 PRO,14 PRO MAX, 15,15 PLUS,15 PRO,15 PRO MAX IP 16,16 Pro ,16ProMax,16Plus GG-109 and GG-110 can be mixed.	≤20000	¥4.70	200	48.0 39.0 20.5	0.0384	13.2	GERLAX Magic Glass Box Privacy Function : ①Phones Screen Protector ②Protect the privacy ③2.5D Anti-explosion ④add anti-static function(ESD) ⑤Easier to fit
				≥20001-100000	¥4.50					
				≥100001	¥4.10					
GG-111			IP X/XS/11 PRO,XR/11,11 PRO MAX IP 12/12 PRO, 12 PRO MAX IP 13/13 PRO/14, 13 PRO MAX/14 PLUS IP 14 PRO,14 PRO MAX IP 15/15 PRO,15 PRO MAX IP 16,16 Pro ,16ProMax,16Plus	≤20000	¥1.60	500	47.0 25.5 20.0	0.0240	10.6	GERLAX Frosted Glass 10 IN 1 Function : ①Phones Screen Protector ②90% Highly Clear ③No fingerprints left ④add anti-static function(ESD)
				≥20001-50000	¥1.40					
				≥50001	¥1.35					
GG-112			IP X/XS/11 PRO,XR/11,11 PRO MAX IP 12/12 PRO, 12 PRO MAX IP 13/13 PRO/14, 13 PRO MAX/14 PLUS IP 14 PRO,14 PRO MAX IP 15/15 PRO,15 PRO MAX IP 16,16 Pro ,16ProMax,16Plus	≤10000	¥2.30	500	48.0 39.0 20.5	0.0384	10.8	GERLAX Frosted Privacy Glass 10 IN 1 Function : ①Phones Screen Protector ②Protect the privacy ③No fingerprints left ④add anti-static function(ESD)
				≥10001-30000	¥2.10					
				≥30001	¥2.00					


GG-113			SAM S21 SAM S21+ SAM S22/S23 SAM S22+/S23+ SAM S24 SAM S24+ SAM S24 ULTRA	/	¥ 4.3	200	43.0	39.0	48.0	0.0805	14	GERLAX Fingerprint Second Unlocking Glass Function: ①Phones Screen Protector ②99% Highly Clear ③2.5D Anti-explosion ④360 Folding glass ⑤The bottom plate of the tempered glass is 0.5mm
GG-114			SAM S21 SAM S21+ SAM S22/S23 SAM S22+/S23+ SAM S24 SAM S24+ SAM S24 ULTRA	/	¥ 6.5	200	43.0	39.0	48.0	0.0805	14.2	GERLAX Fingerprint Second Unlocking Glass Function: ①Phones Screen Protector ②99% Highly Clear ③2.5D Anti-explosion ④360 Folding glass ⑤The bottom plate of the tempered glass is 0.5mm
GG-201			IP 11/12 IP 13/13 MINI, IP 14/14 PLUS, IP 15/15 PLUS, IP 16/16 PLUS, (two camera lens)	≤2000	¥ 4.0	500	48.0	39.0	20.5	0.0384	12	GERLAX Lens Glass Function : ①Phones Lens 360° Protector ②95% Transparency ③AF oil ④Same color as the phone ⑤Alcohol Packets
				≥2001-5000	¥ 3.7							
				≥5001	¥ 3.4							
GG-201			IP 11 PRO/11 PRO MAX , IP 12 PRO,12 PRO MAX, IP 13 PRO/13 PRO MAX, IP 14 PRO/14 PRO MAX, IP 15 PRO/15 PRO MAX, IP 16 PRO/16 PROMAX, (three camera lens)	≤2000	¥ 5.0	500	48.0	39.0	20.5	0.0384	12	GERLAX Lens Glass Function : ①Phones Lens 360° Protector ②95% Transparency ③AF oil ④Same color as the phone ⑤Alcohol Packets
				≥2001-5000	¥ 4.7							
				≥5001	¥ 4.4							
GG-201			SAM S23/S23+ SAM S24/S24+ (three camera lens)	≤2000	¥ 6.5	500	48.0	39.0	20.5	0.0384	12	GERLAX Lens Glass Function : ①Phones Lens 360° Protector ②95% Transparency ③AF oil ④Same color as the phone ⑤Alcohol Packets
				≥2001-5000	¥ 6.2							
				≥5001	¥ 5.9							
GG-201			SAM S23 Ultra , SAM S24 Ultra (five camera lens)	≤2000	¥ 8.5	500	48.0	39.0	20.5	0.0384	12	GERLAX Lens Glass Function : ①Phones Lens 360° Protector ②95% Transparency ③AF oil ④Same color as the phone ⑤Alcohol Packets
				≥2001-5000	¥ 8.2							
				≥5001	¥ 7.9							
GG-M1			White	≥20	¥ 1,790	1	62.5	30.0	25.0	0.0469	7KG	GERLAX Film Cutting Machine Function : ①Can cut most phone models ②The accurate data ③Easy to operate ④One model have many size to select
GG-301			The models are in the machine	≤999	¥ 1.60	2000	52.5	26.5	20.5	0.0285	25	GERLAX Clear TPU Film Function : ①Phones screen protector ②99% Highly Clear ③Not easy to break
				≥1000	¥ 1.50							
GG-302			The models are in the machine	≤999	¥ 1.80	2000	52.5	26.5	20.5	0.0285	25	GERLAX Matte TPU Film Function : ①Phones screen protector ②90% Highly Clear ③No fingerprints left ④Not easy to break
				≥1000	¥ 1.70							
GG-303			The models are in the machine	≤999	¥ 6.00	2000	52.5	26.5	20.5	0.0285	25	GERLAX Matte&Privacy TPU Film Function : ①Phones screen protector ②Protect the privacy ③No fingerprints left ④Not easy to break
				≥1000	¥ 5.50							
GG-304			The models are in the machine	≤999	¥ 6.50	2000	52.5	26.5	20.5	0.0285	25	GERLAX Privacy TPU Film Function : ①Phones screen protector ②Protect the privacy ③Not easy to break
				≥1000	¥ 6.00							

GERLAX[®]

SMART WATCH

ADD:New Asia International Digital City No. 55 Xiti Erma Rosd, Guangzhou

Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

型号	产品图	产品图	卖点	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Product Picture	SELLING POINTS	Price rmb	OUTER CTN/ INNER BOX (PCS)	Carton size (CM)			CBM/CTN (m ³)	KG/CTN	SPECIFICATIONS
GW-01			amoled screen	¥146.00	100	57.0	43.0	24.0	0.0588	20.1	1, Main screen: 2.02inch AMOLED; resolution: 360*360; IP67 waterproof 2, CPU:SF32BL551 RAM: 256MB 3, Bluetooth: 5.0; support call 4, Battery capacity: 280mAh; Battery life: 5-7 days for single Bluetooth, 3 days for dual Bluetooth 5, languages:Simplified Chinese, Traditional Chinese, English, Russian, German, Italian, French, Polish, Portuguese, Spanish, Korean, Japanese, Thai, Indonesian, Vietnamese, Turkish, Persian, Hebrew, Arabic
GW-02			amoled screen	¥156.00	100	57.0	43.0	24.0	0.0588	21.3	1, Main screen: 2.02inch AMOLED; resolution: 360*360; IP67 waterproof 2, CPU:SF32BL551 RAM: 256MB 3, Bluetooth: 5.0; support call 4, Battery capacity: 280mAh; Battery life: 5-7 days for single Bluetooth, 3 days for dual Bluetooth 5, languages:Simplified Chinese, Traditional Chinese, English, Russian, German, Italian, French, Polish, Portuguese, Spanish, Korean, Japanese, Thai, Indonesian, Vietnamese, Turkish, Persian, Hebrew, Arabic
GW-03			powerful functions	¥108.00	100	57.0	34.0	46.5	0.0901	21.59	> CPU:ZK8959 > Memory: 128MB > 1.46 inch screen, 360*360 resolution, full fit process > Case: Zinc alloy case + aluminum button, single button > Bluetooth 5.0, compatible with Android and iPhone > Charging method: wireless charging > Battery: 300mAh > Use time: >3 days > Standby time: >15 days > Charging time: 2-3H > Motor: Support > Functions: Sleep monitoring, exhibition 1688 heart rate, blood oxygen, movement and activity records; bluetooth phone, bluetooth music, speech message alerts (WeChat, QQ, SMS, WhatsApp, Facebook, Tittver, etc.), weather, breathing, blood pressure, may take off, tools (calendar, calculator, timer, stopwatch, alarm, remote control, NFC, SOS, drainage, find mobile phone, business card QR code), application center time and him, blood sugar, respiratory rate, short video remote control), payment (Alipay offline payment, wallet collection QR code) Settings (notification, general/about the machine, language Settings, connect the phone, restore factory, restart, shutdown, do not disturb mode, power saving mode, Display and light screen (brightness adjustment, wrist light up, off screen dial, steady on mode, Pause screen time, Steady on time, Wake screen), APP view, sound and vibration, password switch, key definition, time setting, health alert, battery, bedside clock) Slider menu (customizable) : Bluetooth switch, Settings, Alipay, Do not disturb mode, connect mobile phone, drain function, flashlight, dial lock > IP67 waterproof > Wrist strap size: Total length 226mm, width 22mm:
GW-03			powerful functions	¥108.00	100	57.0	34.0	46.5	0.0901	21.59	> CPU:ZK8959 > Memory: 128MB > 1.46 inch screen, 360*360 resolution, full fit process > Case: Zinc alloy case + aluminum button, single button > Bluetooth 5.0, compatible with Android and iPhone > Charging method: wireless charging > Battery: 300mAh > Use time: >3 days > Standby time: >15 days > Charging time: 2-3H > Motor: Support > Functions: Sleep monitoring, exhibition 1688 heart rate, blood oxygen, movement and activity records; bluetooth phone, bluetooth music, speech message alerts (WeChat, QQ, SMS, WhatsApp, Facebook, Tittver, etc.), weather, breathing, blood pressure, may take off, tools (calendar, calculator, timer, stopwatch, alarm, remote control, NFC, SOS, drainage, find mobile phone, business card QR code), application center time and him, blood sugar, respiratory rate, short video remote control), payment (Alipay offline payment, wallet collection QR code) Settings (notification, general/about the machine, language Settings, connect the phone, restore factory, restart, shutdown, do not disturb mode, power saving mode, Display and light screen (brightness adjustment, wrist light up, off screen dial, steady on mode, Pause screen time, Steady on time, Wake screen), APP view, sound and vibration, password switch, key definition, time setting, health alert, battery, bedside clock) Slider menu (customizable) : Bluetooth switch, Settings, Alipay, Do not disturb mode, connect mobile phone, drain function, flashlight, dial lock > IP67 waterproof > Wrist strap size: Total length 226mm, width 22mm:
GW-04			fashion	¥56.70	100	61.0	31.0	39.0	0.0737	16.3	1, Bluetooth version: V5.3 (Blue 5635B) 2, transmission power: Class2 3, wireless frequency: 2.4-2.48GHz 4, transmission distance: 10 meters 5, charging time: 1 hour (charging voltage 5V) 6, talk/listen to music time: 5-6 hours 7, Support high quality music stereo playback 8, Horn: 10MM 9, suitable model suitable for all mobile phones with Bluetooth function 10, battery capacity 55ma*2 11, charging cable DC
GF-04			Fast Cool	¥26.40	100	48.0	23.0	34.0	0.0375	11.8	Mobile phone back clip semiconductor radiator, digital display, 10W high power, product material: ABS+ aluminum alloy Input parameters: 5V-2A with RGB light effect Fan speed: 5500 RPM Type-C interface

GERLAX®

MOBILE PHONE CAR HOLDER

ADD: New Asia International Digital City No. 55 Xiti Erma Road, Guangzhou

Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

型号	产品图	产品图	卖点	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Product Picture	SELLING POINTS	Price rmb	OUTER CTN/ INNER BOX (PCS)	Carton size (CM)			CBM/CTN (m³)	KG/CTN	SPECIFICATIONS
T01			good price	¥7.70	100	60.0	45.0	43.5	0.1175	18.99	车载伸缩支架 ABS
T02			good price	¥6.10	100	58.0	39.0	39.5	0.0893	13.2	车载出风口支架 ABS
T03			good price	¥5.80	100	57.5	49.0	33.0	0.0930	12.55	车载出风口支架 ABS
T04			good price	¥7.70	100	59.0	41.0	37.0	0.0895	15.2	车载伸缩支架 ABS
T05			good price	¥5.40	200	60.0	52.0	43.0	0.1342	12.4	车载仪表支架 ABS
T06			good price	¥5.40	200	66.0	39.0	30.0	0.0772	13.15	车载仪表支架 ABS
T07			good price	¥7.40	100	60.0	52.0	43.0	0.1342	20.3	车载伸缩支架 ABS
T08			good price	¥4.30	200	65.0	37.5	34.0	0.0829	26.65	桌面平板手机支架 ABS
T09			good price	¥4.60	300	48.0	36.0	45.0	0.0778	13.55	车载L款塑料出风口支架 ABS
T10			good price	¥6.50	100	65.5	30.0	28.0	0.0550	14.55	平板电脑支架 ABS
T11			good price	¥2.90	200	46.0	28.0	52.0	0.0670	21	1.Material: metal 2.Process: Oxidation, Applicable to all mobile phones from 4.5-7inch 3.Applicable scenarios: online classes, work meetings, watching dramas and watching videos, live broadcasting;

GT-1			steadiness	¥11.80	80	64.0	54.0	40.5	0.1400	20.45	Material:ABS+silicone Weight:168G Grip:4-6.7寸,5.7-9CM
GT-2			steadiness	¥9.50	80	64.0	54.0	40.5	0.1400	18.95	Material:ABS+silicone Weight:156G Grip:4-6.7寸, 5.7-9CM
GT-3			steadiness	¥9.90	80	64.0	54.0	40.5	0.1400	18.35	Material:ABS+silicone Weight:150.6G Grip:4-6.7寸, 5.7-9CM
GT-4			steadiness	¥11.50	80	64.0	54.0	40.5	0.1400	19.7	Material:ABS+silicone Weight:162G Grip:4-6.7寸, 5.7-9CM
GT-5			steadiness	¥10.50	80	64.0	54.0	40.5	0.1400	20.25	Material:ABS+silicone Weight:195G Grip:4-6.7寸, 5.7-9CM
GT-6			steadiness	¥11.50	80	64.0	54.0	40.5	0.1400	19.85	Material:ABS+silicone Weight:214G Grip:4-6.7寸, 5.7-9CM
GT-7			magnet	¥10.70	100	49.0	32.0	47.0	0.0737	10.3	Material:ABS+PC Magnetic: Built-in 4X N42 powerful magnets Weight: 52G
GT-8			light and handy	¥10.80	100	49.0	32.0	47.0	0.0737	10.75	Material:ABS+Aluminum alloy+silicone Weight: 62G Grip:4-6.7寸, 5.7-9CM
GT-14			steadiness	¥7.60	100	48.0	38.5	49.5	0.0915	11.95	Product color: black Product material: ABS+silicone Product weight: 70g Suitable for 4.5-7 inch mobile phones (Chuck width range: 55-85mm) Applicable scene: car air outlet
GT-15			steadiness	¥9.10	80	64.0	54.0	40.5	0.1400	19.1	color: silver white material: ABS+silicone+alloy size: 128*77*20mm (folded state) 128*77*159mm (expanded state) weight: 151.5g Height and angle adjustable and foldable, stable and non-slip Support mobile phones, tablets and other devices
GT-16			good quality	¥9.20	100	49.0	32.0	47.0	0.0737	10.8	Product color: grey Product material: zinc alloy + soft rubber magnet + foam rubber Product size: 125*19*9 mm Product weight: 56.3g Scope of application: suitable for any car Magnetic hidden switch, oversized fluorescent number keys
GT-17			good quality	¥12.10	100	49.0	32.0	47.0	0.0737	11.58	Product color: grey Product material: zinc alloy + EVA + nano removable glue Product size: 150*50mm Product weight: 72.8g Scope of application: full-size tablet/laptop 0.3CM slim and portable, can be folded in one second
GT-18			steadiness	¥12.60	80	64.0	54.0	40.5	0.1400	18.1	Product color: black Product material: ABS+silicone Product weight: 138g Suitable for 4.5-7 inch mobile phones (Chuck width range: 60-85mm)

			steadiness	¥11.20	80	64.0	54.0	40.5	0.1400	12.15	Product color: black Product material: ABS+silicone Product weight: 75g Suitable for 4.5-7 inch mobile phones (Chuck width range: 60-85mm) Applicable scene: car air outlet
NEW			convenience	¥12.60	80	64.0	54.0	40.5	0.1400	17.9	Product material: ABS+silicone+APET Product weight: 145g Suitable for 4.5-7 inch mobile phones (Chuck width range: 55-95mm) 1. Automatic lock, mobile phone does not drop; 2. One-hand operation, easy to take and put; 3. 360 degrees free rotation, without blocking the line of sight;
NEW			convenience	¥11.20	80	64.0	54.0	40.5	0.1400	12.1	Product material: ABS+silicone+APET Product weight: 73g Suitable for 4.5-7 inch mobile phones (Chuck width range: 55-95mm) 1. Automatic lock, mobile phone does not drop; 2. One-hand operation, easy to take and put; 3. 360 degrees free rotation, without blocking the line of sight;
NEW			magnet	¥13.60	80	64.0	54.0	40.5	0.1400	18.9	Material:ABS+PC Magnetic: Built-in 4X N42 powerful magnets suitable for 4.7-6.7 inch mobile phone
NEW			good price	¥7.50	100	50.0	47.0	37.0	0.0870	11.9	Material:ABS+PCMagnetic: Built-in4X N42 powerfulmagnets suitablefor 4.7-6.7 inchmobile phone
WIRELESS CHARGE			wireless charging	¥20.00	100	57.0	26.0	58.0	0.0860	13.8	Product color: black Product material: ABS+metalaccessories+lenses wireless charging stand: 15W max input interface: type-c Product weight: 140g Suitable for 4.5-7 inch mobile phones
WIRELESS CHARGE			wireless charging	¥22.00	100	57.5	55.5	40.0	0.1277	22.6	Product color: black Product material: ABS+metal accessories+lenses wireless charging stand: 15W max input interface: type-c Product weight: 210g Suitable for 4.5-7 inch mobile phones
			magnet	¥12.00	100	-1.0	-1.0	-1.5	0.0000		1. Material: ABS+silicone 2. Surface process: texturing 3. Size: 80*62*69mm; Weight: 67g 4. Suitable for 4.5-7.0 inch mobile phones (mainly iPhone 12/13/14/15 series) 5. Mount type: car air outlet
WIRELESS CHARGE			magnet wireless charging	¥28.50	100	-1.0	-1.0	-1.5	0.0000		1. Material: ABS+silicone+metal accessories+lenses 2.wireless charging output: 15W(Max) 3. Size: 200*57*40mm; Weight: 120g 4. Suitable for 4.5-7.0 inch mobile phones (mainly iPhone 12/13/14/15 series) 5.maximum load: 1500G
NEW			steadiness	¥11.00	100	48.0	38.5	49.5	0.0915	15.47	Material: PC + ABS+Silicone, metal Arm Weight: 122 g Clamp: 4-6.7 inches Product size: 103*14*162MM Fixed: rear view mirror seat
NEW			steadiness	¥11.00	100	48.0	38.5	49.5	0.0915	18.25	Material: PC+ABS+ Silicone Weight: 152 g Clamp: 4-6.7 inches Product size: 103*14*162MM Fixed: aperture ≤ 2.8cm handlebar

GERLAX®

HDMI

ADD:New Asia International Digital City No, 55 Xiti Erma Road, Guangzhou

Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

型号	产品图	产品图	卖点	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Product Picture	SELLING POINTS	Price rmb	OUTER CTN/ INNER BOX (PCS)	Carton size (CM)			CBM/CTN (m³)	KG/CTN	SPECIFICATIONS
Hot GV-01			convenient and swift	¥38.0	100	32.0	27.0	44.5	0.0384	5.7	Lightning to HDMI adapter With charging port Applicable to the mobile phone and pad with lightning port Line length:200MM 2-in-1
GV-02			convenient and swift	¥35.2	100	32.0	27.0	44.5	0.0384	7.35	TYPE-C to HDMI adapter HDMI OUTPUT(4K30HZ) USB3.0 SMART PD(3.0) Applicable to the mobile phone with USB-C 3.1 full-function ports Line length:200MM 3-in-1
GV-03			powerful functions	¥61.8	100	32.0	27.0	44.5	0.0384	7.5	USB-C Multi-function expansion dock HDMI output (4K30HZ) +SD+TF card reader +USB3.0+USB2.0+DATA+ intelligent PD (3.0) Applicable to the mobile phone with USB-C 3.1 full-function ports Line length:200MM 7-in-1
GV-04			powerful functions	¥77.2	100	32.0	27.0	44.5	0.0384	7.75	USB-C Multi-function expansion dock HDMI output (4K30HZ) +RJ45 (100 MB) +USB2.0*2+ intelligent PD (3.0) Applicable to the mobile phone with USB-C 3.1 full-function ports Line length:200MM 5-in-1
GV-05			powerful functions	¥59.0	100	32.0	27.0	44.5	0.0384	6.8	5-in-1 TYPE-C multifunctional docking port,HDMI output (4K30HZ)+USB3.0+USB2.0+DATA+ Intelligent PD (3.0) length 0.2M black, space gray hardware enclosure Applicable to the mobile phone with USB-C 3.1 full-function ports
GV-06			Convenient for multiple bites	¥15.5	100	32.0	27.0	44.5	0.0384	5.35	USB3.0 4-in-1 Multi Function Expansion Dock USB3.0 TO HUB3.0+USB2.0+USB2.0+USB2.0 length 0.2M black, space gray hardware enclosure
GV-07			Convenient for multiple bites	¥15.5	100	32.0	27.0	44.5	0.0384	5.15	TYPE-C 4-in-1 Multi Function Expansion Dock TYPE-C TO HUB3.0+USB2.0+USB2.0+USB2.0 length 0.2M black, space gray hardware enclosure
GV-08			Convenient for multiple bites	¥23.5	100	32.0	27.0	44.5	0.0384	6.55	USB3.2 Gen1 4-in-2 Multi Function Expansion Dock USB3.0 & TYPE-C TO HUB3.0+USB2.0+USB2.0+USB2.0 length 0.5M black, space gray hardware enclosure
NEW GV-09			powerful functions	¥177.0	50	56.0	34.0	33.8	0.0644	24	GV-09 (USBC dual purpose multi-purpose docking station) 1, support dual 4KHDMI output, Gigabit network interface, PD3.0 protocol charging, call microphone (can support calls). 2, USBC data interface, compatible with the USBC interface of the device data transmission, such as USB disk. 3, provides four USB3.0 ports, as well as card reader functions with SD and TF card slots 4, shell material: all aluminum alloy peripheral highlight, ventilation and heat dissipation design
NEW GV-10			Convenient for multiple bites	¥25.6	200	47.5	37.5	47.5	0.0846	13.4	5 in 2 Multi Function Expansion Dock typec/USB3.0(2in1) USB3.0+USB2.0+USB2.0+SD+ length 0.5M pine green hardware enclosure



























GERLAX®



























EARPHONE



























ADD:New Asia International Digital City No, 55 Xiti Erma Road, Guangzhou



























Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

























型号	产品图	产品图	卖点	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Product Picture	SELLING POINTS	Price rmb	OUTER CTN/ INNER BOX (PCS)	Carton size (CM)			CBM/CTN (m³)	KG/CTN	SPECIFICATIONS
H12W			good price	¥19.9	100	53.5	24.0	43.0	0.0552	9.50	Wireless version: V5.3 Communication range: 10m Frequency response sensitivity: 20Hz-20KHz Sensitivity: 103dB SPL+/- 3dB Distortion: $\leq 5\%$ Voltage: 3.3-4.2V Power: 5mw Charging box battery capacity: 250mAh Headset battery capacity: 25mAh
H13W			good price	¥22.0	100	53.5	24.0	43.0	0.0552	11.00	Chip :JL6983 Battery capacity :25mAh* 2.7V Charging capacity :200mAh,3.7V Product color: White Features: 1. Touch control and support for waking Siri 2. Allow renaming and positioning 3. Charge the charging bucket first, then charge the earphones
H14W			good price	¥21.0	100	53.5	24.0	43.0	0.0552	9.45	Chip :JL6983 Battery capacity :25mAh* 2.7V Charging capacity :200mAh,3.7V Product color: White Features: 1. Touch control and support for waking Siri 2. Allow renaming and positioning 3. Charge the charging bucket first, then charge the earphones
H15W			good price	¥24.0	100	53.5	24.0	43.0	0.0552	11.00	Chip :JL6983 Battery capacity :25mAh* 2.7V Charging capacity :200mAh,3.7V Product color: White Features: 1. Touch control and support for waking Siri 2. Allow renaming and positioning 3. Charge the charging bucket first, then charge the earphones
H16W			good price	¥18.9	100	53.5	24.0	43.0	0.0552	8.50	Chip :JL6983 Battery capacity :25mAh* 2.7V Charging capacity :200mAh,3.7V Product color: White Features: 1. Touch control and support for waking Siri 2. Allow renaming and positioning 3. Charge the charging bucket first, then charge the earphones
H10			good price	¥11.0	100	53.0	32.0	25.5	0.0432	4.90	1. Bluetooth chip: JL Bluetooth version: 5.0 2. Battery capacity: 60mAh, charging time 2hours 3. Call/ music time: 4 hours, standby time 200hours, 4. Weight: 21g 5. Support protocol Headset Hands-free A2DP, AVRCP, HSP, HFP 6. Function: calling, listen to music, voice function, phone redial, volume addition and subtraction 7. Product color: black 8. Pack color: orange
H1B			good price	¥11.0	100	53.0	32.0	25.5	0.0432	4.90	1. Bluetooth chip: JL Bluetooth version: 5.0 2. Battery capacity: 60mAh, charging time 2hours 3. Call/ music time: 4 hours, standby time 200hours, 4. Weight: 21g 5. Support protocol Headset Hands-free A2DP, AVRCP, HSP, HFP 6. Function: calling, listen to music, voice function, phone redial, volume addition and subtraction 7. Product color: black 8. Pack color: blue
H5W			regret	¥32.5	100	55.5	46.5	27.5	0.0710	16.45	Chip: JL6973 Earphones Battery Capacity: 25mAh*2, 3.7V Charging Bin Charging Capacity: 300mAh, 3.7V Product color: white Pack color: white Functions: 1. True capacity display 2. Touch control and the pop-up window connection function 3. Support wake up Siri 4. Allow to rename and position 5. Support Charging bin and earphones charge at one time Touch key functions: 1. Play / pause: double Clicks the right earphone 2. Answer calls: double Clicks one earphone 3. Next / last songs: Three clicks the right / left earphone WARRANTY PERIOD 12 MONTHS
H6W			regret	¥39.5	100	55.5	46.5	27.5	0.0710	19.95	Chip: JL6973 Earphones Battery Capacity: 25mAh*2, 3.7V Charging Bin Charging Capacity: 300mAh, 3.7V Product color: white Pack color: white Functions: 1. True capacity display 2. Support wake up Siri 3. Touch control and the pop-up window connection function 4. Allow to rename and position 5. Support Charging bin and earphones charge at one time Charging time: 2 hours Calling time: 3-3.5 hours Standby time: 60 hours Material: PC+ABS WARRANTY PERIOD 12 MONTHS
H7W			regret	¥38.5	100	55.5	46.5	27.5	0.0710	16.70	Chip: JL6973 Earphones Battery Capacity: 30mAh*2, 3.7V Charging Bin Charging Capacity: 300mAh, 3.7V Product color: white Pack color: white Functions: 1. True capacity display 2. Support wake up Siri 3. Touch control and the pop-up window connection function 4. Allow to rename and position 5. Support Charging bin and earphones charge at one time Charging time: 2 hours Calling time: 3.5-4 hours Standby time: 150 hours Material: PC+ABS WARRANTY PERIOD 12 MONTHS

E1B			good price	¥1.8	500	47.5	39.8	27.0	0.0510	7.80	1.Hom diameter:Φ10MM 2.Frequency range:20-20000Hz 3.Sensitivity:98dB ±/3dB(1 KHZ) 4.Impedance:32 Ω±15% 5.Material:TPE 6.Line length:1200MM 7.Product color: black 8.Pack color: orange
E1W			good price	¥1.8	500	47.5	39.8	27.0	0.0510	7.80	1.Hom diameter:Φ10MM 2.Frequency range:20-20000Hz 3.Sensitivity:98dB ±/3dB(1 KHZ) 4.Impedance:32 Ω±15% 5.Material:TPE 6.Line length:1200MM 7.Product color: white 8.Pack color: green
E1			metal case	¥3.6	500/10	64.0	37.0	44.0	0.1042	12.8	Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 Ω±15% Material:TPE Line length:1200MM Hom diameter:10MM Plug:3.5MM Color: Red/Green/Golden/Silver/Tarnish
E2			metal case	¥3.6	500/10	64.0	37.0	44.0	0.1042	12.8	Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 Ω±15% Material:TPE Line length:1200MM Hom diameter:10MM Plug:3.5MM Color: Red/Green/Golden/Silver/Tarnish
Hot E6			metal case	¥4.6	400/20	52.5	42.5	32.0	0.0714	7.8	Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 Ω±15% Material:TPE Line length:1200MM Hom diameter:Φ10MM Plug:3.5MM Color: Red/Green/Golden/Tarnish
Hot E7			metal case	¥3.6	400/20	52.5	42.5	32.0	0.0714	8.06	Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 Ω±15% Material:TPE Line length:1200MM Plug:3.5MM Color: Red/Green/Golden/Black
GE-03			metal case	¥6.3	200/5	52.0	39.0	42.0	0.0852	8.95	Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 Ω±15% Material:TPE Line length:1200MM Hom diameter:10MM Plug:3.5MM
Hot GE-04			High-grade process housing	¥8.7	200/5	44.0	37.5	37.0	0.0611	11.6	Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 Ω±15% Material:TPE Line length:1200MM Hom diameter:14MM Plug:3.5MM
Hot GE-04			Digital chip, common more models of mobile phones	¥11.7	200/5	44.0	37.5	37.0	0.0611	11.6	Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 Ω±15% Material:TPE Line length:1200MM Hom diameter:14MM Plug:3.5MM
Hot GE-04			Bluetooth connection, available for calls	¥13.7	200/5	44.0	37.5	37.0	0.0611	11.6	Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 Ω±15% Material:TPE Line length:1200MM Hom diameter:14MM Plug:3.5MM
Hot GE-05			metal case Tensile wire	¥6.7	200/5	44.0	37.5	37.0	0.0611	11.6	Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 Ω±15% Material:TPE Line length:1200MM Hom diameter:10MM Plug:3.5MM
Hot GE-06			metal case with magnetic	¥7.0	200/5	44.0	37.5	37.0	0.0611	11.1	Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 Ω±15% Material:TPE Line length:1200MM Hom diameter:10MM Plug:3.5MM
GE-15			Wear comfortably	¥8.2	200	52.0	39.0	42.0	0.0852	8.5	Hom diameter:Φ15MM Frequency range:20-20000Hz Sensitivity:98dB ±/3dB(1 KHZ) Impedance:32 Ω±15% Material:TPE Line length:1200MM Plug: 3.5MM









			Cool look	¥9.5	200/5	52.0	39.0	42.0	0.0852	8.65	<ul style="list-style-type: none"> 1. Speaker: 10mm Copper ring horn 2. Audio plug: Ø3.5mm 3. Earphones cable:high elastic TPE with enameled wire; wire length: 1.2M , The metal head 4. Microphone: controller with mic 5. Wire control: Functional one-button operation controls music playback + answering calls, up and down music functions, volume level adjustment
			New high-grade material	¥9.9	200/5	52.0	39.0	42.0	0.0852	8.75	<ul style="list-style-type: none"> 1. Speaker: 10mm Copper ring horn 2. Audio plug: Ø3.5mm 3. Earphones cable:high elastic TPE with enameled wire; wire length: 1.2M ,Metal tuning control and metal head 4. Microphone: controller with mic 5. Wire control: Functional one-button operation controls music playback + answering calls, up and down music functions, volume level adjustment
			digital chip	¥10.7	200/5	52.0	39.0	42.0	0.0852	8.9	<ul style="list-style-type: none"> 1, material: aluminum alloy + TPE 2. Speaker: 14mm 3. Cable length: 1.2m; 4. Audio plug: Type-C digital plug 5. Support wire control, volume increase and decrease, support call 6. Support most models of Huawei, Xiaomi, and other brands, and some models of Samsung mobile phones, and support iPad Pro/iPad Air with Type-C interface.
			digital chip	¥10.1	200/5	52.0	39.0	42.0	0.0852	8.9	<ul style="list-style-type: none"> 1, material: aluminum alloy + TPE 2. Speaker: 10mm 3. Cable length: 1.2m; 4. Audio plug: Type-C digital plug 5. Support wire control, volume increase and decrease, support call 6. Support most models of Huawei, Xiaomi, and other brands, and some models of Samsung mobile phones, and support iPad Pro/iPad Air with Type-C interface.
NEW			digital chip	¥11.8	200	47.5	37.5	47.5	0.0846	9.65	<ul style="list-style-type: none"> 1, material: aluminum alloy + TPE 2. Speaker: 10mm 3. Cable length: 1.2m; 4. Audio plug: Type-C digital plug 5. Support wire control, volume increase and decrease, support call 6. Support most models of Huawei, Xiaomi, and other brands, and some models of Samsung mobile phones, and support iPad Pro/iPad Air with Type-C interface.
NEW			digital chip	¥10.1	200/5	52.0	39.0	42.0	0.0852	9.22	<ul style="list-style-type: none"> 1, material: aluminum alloy + TPE 2. Speaker: 10mm 3. Cable length: 1.2m; 4. Audio plug: Type-C digital plug 5. Support wire control, volume increase and decrease, support call 6. Support most models of Huawei, Xiaomi, and other brands, and some models of Samsung mobile phones, and support iPad Pro/iPad Air with Type-C interface.
NEW			digital chip	¥9.3	200/5	52.0	39.0	42.0	0.0852	8.9	<ul style="list-style-type: none"> 1, material: ABS + TPE 2. Speaker: 10mm 3. Cable length: 1.2m; 4. Audio plug: Type-C digital plug 5. Support wire control, volume increase and decrease, support call 6. Support most models of Huawei, Xiaomi, and other brands, and some models of Samsung mobile phones, and support iPad Pro/iPad Air with Type-C interface.
NEW			digital chip	¥15.6	200/20	37.5	22.5	31.0	0.0262	5.94	<ul style="list-style-type: none"> Speaker: φ14mm Dynamic Type Impedance:32Ohms ±20% Frequency:20-20KHZ Sensitivity:100 ±3dB(at 1KHZ) Max. Input Power:5mW Mic Sensitivity : -42 ±3dB(at 1KHZ) Input Connection: TYPE-C Cable Length:1.20 ±0.03M TPE
NEW			In-line chip for phone calls	¥20.7	200/20	37.5	22.5	31.0	0.0262	5.94	<ul style="list-style-type: none"> Speaker: φ14.2mm Dynamic Type Frequency: 20-20000HZ Sensitivity:90 ±3dB Max Power: 1 - 3MW Mic Sensitivity: -29DBFS. Material: φ2.2*4c(8*0.06+250D)TPE
			Wear comfortably	¥5.6	200/5	52.0	39.0	42.0	0.0852	7.90	<ul style="list-style-type: none"> Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 Ω±15% Material:TPE Line length:1200MM Hom diameter:10MM Plug:3.5MM
HOT			hifi audio with tuning	¥8.9	200	47.5	37.5	47.5	0.0846	12.45	<ul style="list-style-type: none"> Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 ±15% Material:TPE Line length:1200MM Hom diameter:φ14MM Plug:3.5MM
HOT			digital chip hifi audio with tuning	¥11.4	200	47.5	37.5	47.5	0.0846	12.45	<ul style="list-style-type: none"> Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 ±15% Material:TPE Line length:1200MM Hom diameter:φ14MM
HOT			Bluetooth connection chip hifi audio with tuning	¥12.1	200	47.5	37.5	47.5	0.0846	12.45	<ul style="list-style-type: none"> Frequency range:20Hz-20000Hz Sensitivity:98dB ±/3dB(1KHZ) Impedance:16 ±15% Material:TPE Line length:1200MM Hom diameter:φ14MM

HOT			fashion	¥7.3	200/5	52.0	39.0	42.0	0.0852	8.05	<p>Hom diameter:Ø14MM</p> <p>Frequency range:20-20000Hz</p> <p>Sensitivity:98dB ±3dB(1 KHZ)</p> <p>Impedance:32Ω±15%</p> <p>Material:TPE</p> <p>Line length:1200MM</p>
			Tape tuning	¥6.3	200/5	52.0	39.0	42.0	0.0852	8.2	<p>1. Speaker: 10mm</p> <p>2. Audio plug: Ø3.5mm</p> <p>3. Earphones cable:high elastic TPE with enameled wire; wire length: 1.2M , The metal head</p> <p>4. Microphone: controller with mic</p> <p>5. Wire control: Functional one-button operation controls music playback + answering calls, up and down music functions, volume level adjustment</p>
			good price	¥2.9	500/10	64.0	37.0	44.0	0.1042	13.2	<p>Frequency range:20Hz-20000Hz</p> <p>Sensitivity:98dB ±3dB(1KHZ)</p> <p>Impedance:16Ω±15%</p> <p>Material:TPE</p> <p>Line length:1200MM</p> <p>Hom diameter:10MM</p> <p>Plug:3.5MM</p> <p>Color: White</p>
			good price	¥2.8	500/10	64.0	37.0	44.0	0.1042	13.2	<p>Frequency range:20Hz-20000Hz</p> <p>Sensitivity:98dB ±3dB(1KHZ)</p> <p>Impedance:16Ω±15%</p> <p>Material:TPE</p> <p>Line length:1200MM</p> <p>Hom diameter:10MM</p> <p>Plug:3.5MM</p> <p>Color: White</p>
			fashion	¥4.7	500/10	64.0	37.0	44.0	0.1042	13.3	<p>1. Speaker: 10mm</p> <p>2. Audio plug: Ø3.5mm</p> <p>3. Earphones cable:high elastic TPE with enameled wire; wire length: 1.2M</p> <p>4. Microphone: controller with mic</p> <p>5. Wire control: Functional one-button operation controls music playback + answering calls, up and down music functions, volume level adjustment</p>
			metal case Elbow joint	¥5.4	200/5	52.0	39.0	42.0	0.0852	9.30	<p>1. Material: Aluminum alloy, TPE enameled wire;</p> <p>2. Length: 1.2m;</p> <p>3. Weight: 13 g;</p> <p>4. Speaker: 10mm Copper ring horn</p> <p>5. Sensitivity: 110dB±3dB;</p> <p>6. Impedance: 32Ω</p> <p>7. Frequency response: 20-20000Hz;</p> <p>8. Jack: 3.5mm;</p> <p>9. Mic: Controller with Mic;</p> <p>10. Line control: Single key for control</p>
NEW			metal case Elbow joint	¥5.4	200/5	52.0	39.0	42.0	0.0852	9.10	<p>1. Material: Aluminum alloy, TPE enameled wire;</p> <p>2. Length: 1.2m;</p> <p>3. Weight: 13g;</p> <p>4. Speaker: 10mm Copper ring horn</p> <p>5. Sensitivity: 110dB±3dB;</p> <p>6. Impedance: 32Ω</p> <p>7. Frequency response: 20-20000Hz;</p> <p>8. Jack: 3.5mm;</p> <p>9. Mic: Controller with Mic;</p> <p>10. Line control: Single key for control</p>
NEW			metal case Elbow joint	¥5.4	200/5	52.0	39.0	42.0	0.0852	9.10	<p>1. Material: Aluminum alloy, TPE enameled wire;</p> <p>2. Length: 1.2m;</p> <p>3. Weight: 13 g;</p> <p>4. Speaker: 10mm Copper ring horn</p> <p>5. Sensitivity: 110dB±3dB;</p> <p>6. Impedance: 32Ω</p> <p>7. Frequency response: 20-20000Hz;</p> <p>8. Jack: 3.5mm;</p> <p>9. Mic: Controller with Mic;</p> <p>10. Line control: Single key for control</p>
NEW			metal case Elbow joint	¥5.4	200/5	52.0	39.0	42.0	0.0852	9.10	<p>1. Material: Aluminum alloy, TPE enameled wire;</p> <p>2. Length: 1.2m;</p> <p>3. Weight: 13 g;</p> <p>4. Speaker: 10mm Copper ring horn</p> <p>5. Sensitivity: 110dB±3dB;</p> <p>6. Impedance: 32Ω</p> <p>7. Frequency response: 20-20000Hz;</p> <p>8. Jack: 3.5mm;</p> <p>9. Mic: Controller with Mic;</p> <p>10. Line control: Single key for control</p>
NEW			metal case Elbow joint	¥5.4	200/5	52.0	39.0	42.0	0.0852	9.20	<p>1. Material: Aluminum alloy, TPE enameled wire;</p> <p>2. Length: 1.2m;</p> <p>3. Weight: 14 g;</p> <p>4. Speaker: 10mm Copper ring horn</p> <p>5. Sensitivity: 110dB±3dB;</p> <p>6. Impedance: 32Ω</p> <p>7. Frequency response: 20-20000Hz;</p> <p>8. Jack: 3.5mm;</p> <p>9. Mic: Controller with Mic;</p> <p>10. Line control: Single key for control</p>
NEW			metal case Elbow joint	¥5.4	200/5	52.0	39.0	42.0	0.0852	9.00	<p>1. Material: Aluminum alloy, TPE enameled wire;</p> <p>2. Length: 1.2m;</p> <p>3. Weight: 13 g;</p> <p>4. Speaker: 10mm Copper ring horn</p> <p>5. Sensitivity: 110dB±3dB;</p> <p>6. Impedance: 32Ω</p> <p>7. Frequency response: 20-20000Hz;</p> <p>8. Jack: 3.5mm;</p> <p>9. Mic: Controller with Mic;</p> <p>10. Line control: Single key for control</p>
NEW			good price	¥3.4	500/10	64.0	37.0	44.0	0.1042	13.20	<p>1, Material: ABS+TPE</p> <p>2. Speaker: 14mm</p> <p>3. Cable length: 1.2m;</p> <p>4. Audio plug: Ø3.5mm</p> <p>5. Microphone: support</p> <p>6. wire control: functional one-button control</p>
NEW			good price	¥3.4	500/10	64.0	37.0	44.0	0.1042	13.20	<p>1, Material: ABS+TPE</p> <p>2. Speaker: 14mm</p> <p>3. Cable length: 1.2m;</p> <p>4. Audio plug: Ø3.5mm</p> <p>5. Microphone: support</p> <p>6. wire control: functional one-button control</p>

NEW			good price	¥3.2	500/10	64.0	37.0	44.0	0.1042	12.80	1, Material: ABS+TPE 2. Speaker: 10mm 3. Cable length: 1.2m; 4. Audio plug: Ø3.5mm 5. Microphone: support 6. wire control: functional one-button control
NEW			good price	¥3.2	500/10	64.0	37.0	44.0	0.1042	12.80	1, Material: ABS+TPE 2. Speaker: 10mm 3. Cable length: 1.2m; 4. Audio plug: Ø3.5mm 5. Microphone: support 6. wire control: functional one-button control
			Half in the ear, comfortable to wear	¥3.3	500/10	64.0	37.0	44.0	0.1042		1.Material: ABS+TPE 2. Speaker: 14mm 3. Cable length: 1.2m; 4. Audio plug: Ø3.5mm 5. Microphone: support 6. wire control: functional one-button control
			good price	¥3.2	500/10	64.0	37.0	44.0	0.1042		1.Material: ABS+TPE 2. Speaker: 14mm 3. Cable length: 1.2m; 4. Audio plug: Ø3.5mm 5. Microphone: support 6. wire control: functional one-button control
			Electroplated case, digital chip	¥5.7	500/10	64.0	37.0	44.0	0.1042		1.Material: ABS+TPE 2. Speaker: 10mm 3. Cable length: 1.2m; 4. Audio plug: TYPE-C 5. Microphone: support 6. wire control: functional one-button control
			Electroplated case, digital chip	¥5.7	500/10	64.0	37.0	44.0	0.1042		1.Material: ABS+TPE 2. Speaker: 10mm 3. Cable length: 1.2m; 4. Audio plug: TYPE-C 5. Microphone: support 6. wire control: functional one-button control
			oil injection process ear shell decoration	¥3.3	500/10	64.0	37.0	44.0	0.1042		1.Material: ABS+TPE 2. Speaker: 10mm 3. Cable length: 1.2m; 4. Audio plug: Ø3.5mm 5. Microphone: support 6. wire control: functional one-button control
			Electroplated decorative parts, digital chips	¥5.4	500/10	64.0	37.0	44.0	0.1042		1.Material: ABS+TPE 2. Speaker: 14mm 3. Cable length: 1.2m; 4. Audio plug: TYPE-C 5. Microphone: support 6. wire control: functional one-button control
NOT			Comfortable hanging neck	¥18.4	50	66.0	31.5	19.0	0.0395	4.7	Headset battery:Polymer lithium battery 130mAh Wireless version: 5.0 Wireless distance: 10m Headset music time: About 6Hours DC charging current:100mA DC charging voltage:5V
NEW			Long standby, HiFi sound quality	¥38.0	100	76.0	41.5	32.5	0.1025	12.76	Bluetooth 5.3; Chip: JL AC7006 Battery capacity: 800mAh; charging about 3.5 hours Use time: 160 hours; Standby time: 1200 hours Support Bluetooth, TF card (≤32G) playback 800mAh large battery, 160 hours of super battery life 6.Metal semi-in-ear ear shell, ear shell with magnetic function, 14.2mm copper ring horn
NEW			Long standby, HiFi sound quality	¥38.0	100	76.0	41.5	32.5	0.1025	12.26	Bluetooth 5.3; Chip: JL AC7006 Battery capacity: 800mAh; charging about 3.5 hours Use time: 160 hours; Standby time: 1200 hours Support Bluetooth, TF card (≤32G) playback 800mAh large battery, 160 hours of super battery life 6.Metal full in-ear ear shell, ear shell with magnetic function, 14.2mm copper ring horn
NEW			Light and comfortable wear	¥22.5	100	67.0	63.0	26.0	0.1097	8.45	Bluetooth:5.3 Connect distance:10m Speaker size:Ø14.2mm Battery:100mAh S/N:90dB Charging time:≤1.5H Playing time:6H Stand by:30days Weight:14g
NEW			Business convenience	¥42.0	100/5	34.5	31.0	47.0	0.0503	7.40	1, Bluetooth 5.2, chip: AC6976D 2. Battery capacity: 95mAh, charging for about 1 hour 3. Talk/music time: 9 hours 4. Standby time 200 hours 5. Double-mark ENC noise reduction, clearer call 6.Intelligent voice reminder function , Can rotate 180 degrees, suitable for the left and right ears

		HiFi sound quality	¥66.0	50	52.0	24.0	21.0	0.0262	7.20	<p>Chip: JL6973 Earphones Battery Capacity: 30mAh*2, 3.7V Charging Bin Charging Capacity: 300mAh,3.7V Functions: 1.Ture capacity display 2.Support wireless charging and automatic ear detection 3.Support wake up Siri 4.Touch control and the pop-up window connection function 5.Allow to rename and position 6.Support Charging bin and earphones charge at one time Charging time: 2 hours Calling time: 3.5-4 hours Standby time: 150 hours Materials:Hinges of metal +ABS WARRANTY PERIOD: 12 MONTHS</p>
		Aesthetic classic	¥43.3	100	50.5	37.0	21.5	0.0402	12.55	<p>1. Bluetooth 5.1, chip: JL AC6973 2. Battery capacity: charging compartment 300mAh, earphone 25mAh 3. Talk/music time: 3.5 hours, 120 hours standby 4. Size: 53.8*44.3*21.5mm; Net weight: 47g 5. Support master-slave switching, call Siri, modify pairing name, touch operation, do not support pop-up window 6. with charging cable WARRANTY PERIOD: 12 MONTHS</p>
		full function with HiFi sound quality	¥58.7	100	55.5	51.0	24.0	0.0679	20.85	<p>Bluetooth V5.3,Chip: JL6973 Support Bluetooth profileA2DP, AVRCP, HSP, HFP Earphones Battery Capacity: 30mAh*2, 3.7V Charging case Capacity: 300mAh,3.7V Functions: 1.Ture capacity display 2.Support wireless charging and automatic ear detection 3.Support wake up Siri 4.Touch control and the pop-up window connection function Charging time: 2 hours Calling time: 4 hours Standby time: 60 hours Materials:PC+ABS</p>
		High capacity button battery	¥40.8	100	54.5	37.0	34.5	0.0696	18.40	<p>1. Bluetooth 5.3; Chip :JLAC6973 2. Battery capacity: charging box 300mAh; Headphones 35mah 3. Use time :7 hours (button battery); Standby time :200 hours 4. Support for iPhone popover connection with window, customization, and three real battery displays in the charging case/left and right earphones 5. Full function support wireless charging, in-ear detection function</p>
		High capacity button battery	¥48.8	100	54.5	37.0	34.5	0.0696	19.35	<p>1. Bluetooth 5.3; Chip :JLAC6973 2. Battery capacity: charging box 300mAh; Headphones 35mah 3. Use time :7 hours (button battery); Standby time :200 hours 4. Support for iPhone popover connection with window, customization, and three real battery displays in the charging case/left and right earphones 5. Full function support wireless charging, in-ear detection function</p>
		High capacity button battery	¥46.8	100	54.5	37.0	34.5	0.0696	18.80	<p>1. Bluetooth 5.3; Chip :JLAC6973 2. Battery capacity: charging box 300mAh; Headphones 35mah 3. Use time :7 hours (button battery); Standby time :200 hours 4. Support for iPhone popover connection with window, customization, and three real battery displays in the charging case/left and right earphones 5. Full function support wireless charging, in-ear detection function</p>
		full function with ANC	¥52.8	100	54.5	37.0	34.5	0.0696	19.90	<p>1. Bluetooth 5.3; Chip :JLAC6973 2. Battery capacity: charging box 300mAh; Headphones 35mah 3. Use time :7 hours (button battery); Standby time :200 hours 4. Support for iPhone popover connection with window, customization, and three real battery displays in the charging case/left and right earphones 5. Full function support wireless charging, in-ear detection function</p>
		HiFi sound quality	¥51.0	100	54.5	37.0	34.5	0.0696	8.55	<p>Chip: JL6973 Bluetooth version: V5.3 Working range: about 10 meters Charging time: 2 hours Talk time: 4 hours Standby time: 60 hours Headphone battery: 25mAh Charging case battery: 250mAh</p>
		HiFi sound quality	¥49.0	100	54.5	37.0	34.5	0.0696	9.25	<p>Chip: JL6973 Bluetooth version: V5.3 Working range: about 10 meters Charging time: 2 hours Talk time: 4 hours Standby time: 60 hours Headphone battery: 25mAh Charging case battery: 250mAh</p>
		HiFi sound quality	¥50.0	100	54.5	37.0	34.5	0.0696	8.8	<p>Chip: JL6973 Bluetooth version: V5.3 Working range: about 10 meters Charging time: 2 hours Talk time: 4 hours Standby time: 60 hours Headphone battery: 25mAh Charging case battery: 250mAh</p>
		Comfortable wear	¥38.0	100	54.5	37.0	34.5	0.0696	9.9	<p>Chip: JL6973 Bluetooth version: V5.3 Working range: about 10 meters Charging time: 2 hours Talk time: 4 hours Standby time: 60 hours Headphone battery: 30mAh Charging case battery: 250mAh</p>
		Super function, LCD screen, ANC,ENC	¥46.5	100	53.5	24.0	43.0	0.0552	10.9	<p>Bluetooth version: V5.4 Dual chip: AB5636+LP7812C. Large screen high resolution color screen intelligent control, with active noise reduction ANC and passive noise reduction ENC Transmission distance: 10m Charging jack: TYPE-C Bluetooth frequency: 2.402-2.480GHZ Rated input: 5V--300mA Charging time :1H Music time: 4H Talk time: 4H Headset battery capacity: 30mAh Charging bay battery capacity: 300mAh</p>
		Comfortable wear	¥37.0	60	84.0	43.0	59.0	0.2131	19.6	<p>1. Bluetooth Chip/Version: JL/5.3 2. Battery capacity: 250mAh; Charging time: about 2 hours 3. Speaker impedance: 32Ω/Φ40mm 4. Use time: 7 hours; Standby time: 120 hours 5. Working distance: 10m 6. Support Bluetooth, TF card and AUX mode</p>

		Classic look, rotary multi-function control key	¥39.0	60	65.0	57.0	46.0	0.1704	18.77	Chip: JL AC6955F Wireless Version: 5.3 Support Profiles: A2DP, AVCTP, AVDTP, AVRCP, HFP, SPP, Operation Distance: 10m Frequency Range: 2.402 -2.480 GHz Speaker: Ø40mm Impedance: 32Ω Radio Frequency Response: 87.5-108MHz Rechargeable Lithium Battery: 4000mAh Music Playing Time: 9h
		Classic look, rotary multi-function control key	¥39.0	60	65.0	57.0	46.0	0.1704	18.77	Chip: JL AC6955F Wireless Version: 5.3 Support Profiles: A2DP, AVCTP, AVDTP, AVRCP, HFP, SPP, Operation Distance: 10m Frequency Range: 2.402 -2.480 GHz Speaker: Ø40mm Impedance: 32Ω Radio Frequency Response: 87.5-108MHz Rechargeable Lithium Battery: 4000mAh Music Playing Time: 9h
		High grade CD ornamentation	¥46.8	60	84.0	43.0	59.0	0.2131	26.9	1. Bluetooth Chip/Version: JL/5.3 2. Battery capacity: 250mAh 3. Speaker impedance: 32Ω/Ø40mm 4. Working distance: 10m 5. Working time: 7 hours 6.Support Bluetooth, TF card and AUX mode
		Cute and unique appearance	¥39.8	60	84.0	43.0	59.0	0.2131	30	1. Bluetooth 5.3, JL AC6925F chip 2. 400mAh battery capacity, charging time 2 hours 3. Use time: 10 hours (8 hours with lights on); standby time 120 hours 4. Speaker diameter: 40mm 5.Working distance: 10m 6. Support Bluetooth,TF card,AUX playback modes 7. Glowing cat ear shape design, very cuty 8.with RGB Flash light
		Full package comfortable to wear	¥39.5	60	84.0	43.0	59.0	0.2131	29.2	1. Bluetooth Chip/Version: JL/5.3 2. Battery: 350mAh 3.7V 3. Speaker impedance: 32Ω/Ø40mm 4. Working distance: 10m 5. Material: ABS+PU Leather 6. Frequency Response:20-20KHz 7. TF card memory:128M-32GB 8. Support: TF card, FM, wireless
		Metal trims	¥39.1	60	84.0	43.0	59.0	0.2131	25.5	1. Bluetooth Chip/Version: JL/5.3 2. Battery: 350mAh 3.7V 3. Speaker impedance: 32Ω/Ø40mm 4. Working distance: 10m 5. Material: ABS+Aluminium alloy decorative sheet 6. Frequency Response:20-20KHz 7. TF card memory:128M-32GB 8. Support: TF card, FM, wireless
		RGB ambient lighting	¥41.2	60	84.0	43.0	59.0	0.2131	26.4	Chip: JL AC6925F Wireless Version: 5.0 Support Profiles: A2DP, AVCTP, AVDTP, AVRCP, HFP, SPP Operation Distance: 10m Frequency Range: 2.402 -2.480 GHz Speaker: Ø40mm Impedance: 32Ω TF card Supported:128M-32G Radio Frequency Response: 87.5-108MHz Rechargeable Lithium Battery: 400mAh Music Playing Time: 7h Talking Time: 7h Charging Time: 2h
		Unique square ear muffs RGB ambient lighting	¥40.5	60	84.0	43.0	59.0	0.2131	25.9	Chip: JL AC6955F Wireless Version: 5.3 Support Profiles: A2DP, AVCTP, AVDTP, AVRCP, HFP, SPP, Operation Distance: 10m Frequency Range: 2.402 -2.480 GHz Speaker: Ø40mm Impedance: 32Ω Radio Frequency Response: 87.5-108MHz Rechargeable Lithium Battery: 400mAh Music Playing Time: 9h Talking Time: 9h Charging Time: 2.5h
		Unique square ear muffs RGB ambient lighting	¥40.5	60	84.0	43.0	59.0	0.2131	25.9	Chip: JL AC6955F Wireless Version: 5.3 Support Profiles: A2DP, AVCTP, AVDTP, AVRCP, HFP, SPP, Operation Distance: 10m Frequency Range: 2.402 -2.480 GHz Speaker: Ø40mm Impedance: 32Ω Radio Frequency Response: 87.5-108MHz Rechargeable Lithium Battery: 400mAh Music Playing Time: 9h Talking Time: 9h Charging Time: 2.5h
		Fully enclosed comfortable earmuffs with ANC	¥76.2	60	86.0	43.0	59.5	0.2200	30.68	Bluetooth 5.3 JL 6965A solution with ANC function, head bow, shell bowl rubber process, 40mm steel magnetic horn, 350MAH lithium battery with protection plate, TYPE-C charging port
		Light and beautiful	¥38.4	60	86.0	43.0	59.5	0.2200	25.3	Bluetooth:5.3 Connect distance:10m Speaker size:Ø14.2mm Battery:100mAh S/N:90dB Charging time:≤1.5H Playing time:6H Stand by:30days Weight:14g
		Comfortable wear ultra-long standby time	¥45.0	60	64.0	45.5	57.0	0.1660	20.15	Function: BT+TF Chip: JL 7006 Bluetooth Version: 5.3 Battery: 400 mah Playing time: 50H (100% volume) Talk time: 50H Standby time: 300H Charging time: 3H Type C Port Product size: 20.2X4X20.5 Net weight: 190g
		Comfortable wear ultra-long standby time	¥45.0	60	64.0	45.5	57.0	0.1660	20.15	Function: BT+TF Chip: JL 7006 Bluetooth Version: 5.3 Battery: 400 mah Playing time: 50H (100% volume) Talk time: 50H Standby time: 300H Charging time: 3H Type C Port Product size: 20.2X4X20.5 Net weight: 190g























<p>GH-39</p>			<p>Comfortable wear ultra-long standby time</p>	<p>¥45.0</p>	<p>60</p>	<p>64.0</p>	<p>45.5</p>	<p>57.0</p>	<p>0.1660</p>	<p>20.15</p> <p>Function: BT+TF Chip: JL 7006 Bluetooth Version: 5.3 Battery: 400 mah Playing time: 50H (100% volume) Talk time: 50H Standby time: 300H Charging time: 3H Type C Port Product size: 20.2X4X20.5 Material: ABS</p>
<p>GH-41</p>			<p>ultra-long standby time with ANC</p>	<p>¥56.3</p>	<p>40</p>	<p>89.0</p>	<p>40.5</p>	<p>47.5</p>	<p>0.1712</p>	<p>16.6</p> <p>Chipset:JL7006F8 Wireless distance range:10M bluetooth version: 5.3 * Main Features: Active Noise Cancelling * Bluetooth profile:A2DP/AVRCP/HSP/HFP * Battery capacity:3.7V/400 mAh * Bluetooth + noise canceling: 44 hours *Bluetooth: 50 hours *ANC: 50 hours * Charging time :about 3 hours *Material: PU,ABS</p>
<p>GH-43</p>			<p>ultra-long standby time with ANC</p>	<p>¥58.8</p>	<p>40</p>	<p>89.0</p>	<p>40.5</p>	<p>47.5</p>	<p>0.1712</p>	<p>15.8</p> <p>Chipset:JL7006F8 Wireless distance range:10M bluetooth version: 5.3 * Main Features: Active Noise Cancelling * Bluetooth profile:A2DP/AVRCP/HSP/HFP * Battery capacity:3.7V/400 mAh * Bluetooth + noise canceling: 44 hours *Bluetooth: 50 hours *ANC: 50 hours * Charging time :about 3 hours *Material: PU,ABS</p>
<p>GH-38</p>			<p>Business premium ultra-long standby time</p>	<p>¥47.5</p>	<p>100</p>	<p>34.5</p>	<p>31.0</p>	<p>47.0</p>	<p>0.0503</p>	<p>6.65</p> <p>Bluetooth version:5.2 JL6976D4 10MM copper ring horn, 140MAH battery with protection board, intelligent voice reminder, to telegraph number, one drag two, can be connected to two mobile phones at the same time, power display, call vibration reminder function</p>



























GERLAX®



























EU CHARGER



























ADD:New Asia International Digital City No, 55 Xiti Erma Rosd, Guangzhou



























Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费)

型号	产品图	产品图	卖点	类型	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Product Picture	SELLING POINTS	Type	Price rmb	OUTER CTN/ INNER BOX (PCS)	Carton size (CM)			CBM/CT N (m³)	KG/CTN	SPECIFICATIONS
A300			QC3.0 1USB-A (White)	Without Cable	¥ 5.30	200/10	77.0	33.0	32.5	0.0826	13.1	1. Size: 24.5x40x82mm Weight:38.5g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB DC5V / 2.4A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A3V			QC3.0 with cable 1USB-A (White)	MICRO	¥ 5.90	300	54.0	47.0	37.0	0.0939	22.45	1. Size: 24.5x40x82mm Weight:38.5g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB DC5V / 2.4A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A3T			QC3.0 with cable 1USB-A (White)	TYPE-C	¥ 6.20	300	54.0	47.0	37.0	0.0939	22.45	1. Size: 24.5x40x82mm Weight:38.5g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB DC5V / 2.4A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A3L			QC3.0 with cable 1USB-A (White)	5G	¥ 6.40	300	54.0	47.0	37.0	0.0939	22.45	1. Size: 24.5x40x82mm Weight:38.5g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB DC5V / 2.4A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A4S			PD20W Single port (1C) (White)	Without Cable	¥ 6.90	300	54.0	47.0	37.0	0.0939	18.9	1. Size: 26.3x42.8x82mm Weight:44g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYP-C 5V / 3A,9V/2.22A,12V/1.67A up to 20W 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A4G			PD20W Single port (1C) (White)	Without Cable	¥ 6.90	300	54.0	47.0	37.0	0.0939	19.05	1. Size: 26.3x42.8x82mm Weight:44g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYP-C 5V / 3A,9V/2.22A,12V/1.67A up to 20W 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A4T			PD20W with cable Single port (1C) (White)	C-C	¥ 9.50	100	35.5	32.5	43.0	0.0496	8.8	1. Size: 26.3x42.8x82mm Weight:44g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYP-C 5V / 3A,9V/2.22A,12V/1.67A up to 20W 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A4L			PD20W with cable Single port (1C) (White)	C-IP	¥ 11.00	100	35.5	32.5	43.0	0.0496	8.8	1. Size: 26.3x42.8x82mm Weight:44g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYP-C 5V / 3A,9V/2.22A,12V/1.67A up to 20W 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A5S			PD20W USB-C+USB-A (White)	Without Cable	¥ 7.90	300	54.0	47.0	37.0	0.0939	19	1. Size:26.3 x 42.8 x 82mm Weight:45 g 2. Input:AC100 - 240 V 50-60Hz 0.6 3. Output:USB-A DC5V/3A,9V/2.22A,12V/1.67A TYP-C DC5V/3A,9V/2.22A,12V/1.67A up to 20W 4. plug: nickel-plated EU plug, 24 hours salt spray test 5. Material: ABS 6. circuit over-current, over-voltage protection; short circuit protection, explosion-proof, intelligent identification IC
A5G			PD20W USB-C+USB-A (White)	Without Cable	¥ 7.90	300	54.0	47.0	37.0	0.0939	19	1. Size:26.3 x 42.8 x 82mm Weight:45 g 2. Input:AC100 - 240 V 50-60Hz 0.6 3. Output:USB-A DC5V/3A,9V/2.22A,12V/1.67A TYP-C DC5V/3A,9V/2.22A,12V/1.67A up to 20W 4. plug: nickel-plated EU plug, 24 hours salt spray test 5. Material: ABS 6. circuit over-current, over-voltage protection; short circuit protection, explosion-proof, intelligent identification IC
A5T			PD20W with cable USB-C+USB-A (White)	C-C	¥ 10.90	100	35.5	32.5	43.0	0.0496	9.1	1. Size: 26.5x43x61.2mm Weight:40g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYP-C 5V / 3A,9V/2.22A,12V/1.67A up to 20W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC

A5L			PD20W with cable USB-C+USB-A (White)	C-IP	¥12.90	100	35.5	32.5	43.0	0.0496	9.1	<ul style="list-style-type: none"> 1. Size: 26.5x43x61.2mm Weight:40g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYP-C 5V / 3A,9V/2.22A,12V/1.67Aup to 20W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A700			QC3.0/3A 1USB-A (White)	Without Cable	¥5.50	200/10	67.0	33.0	32.5	0.0719	22.1	<ul style="list-style-type: none"> 1. Size: 24x42x82mm Weight:37.2g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: single USB DCSV/3A,9V/2A,12V/1.5Aup to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A7V			QC3.0/3A with cable 1USB-A (White)	MICRO	¥6.00	300	54.0	47.0	37.0	0.0939	22.1	<ul style="list-style-type: none"> 1. Size: 24x42x82mm Weight:37.2g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: single USB DCSV/3A,9V/2A,12V/1.5Aup to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A7T			QC3.0/3A with cable 1USB-A (White)	TYPE-C	¥6.30	300	54.0	47.0	37.0	0.0939	22.1	<ul style="list-style-type: none"> 1. Size: 24x42x82mm Weight:37.2g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: single USB DCSV/3A,9V/2A,12V/1.5Aup to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A7L			QC3.0/3A with cable 1USB-A (White)	5G	¥6.50	300	54.0	47.0	37.0	0.0939	22.1	<ul style="list-style-type: none"> 1. Size: 24x42x82mm Weight:37.2g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: single USB DCSV/3A,9V/2A,12V/1.5Aup to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A71V			QC3.0/3A with cable 1USB-A (White)	MICRO	¥6.50	300	74.0	40.5	53.5	0.1603	26	<ul style="list-style-type: none"> 1.Input: AC 100-240V 50-60Hz 0.35A 2. Ouput: DC 5V=3A 9V=2.22A 12V=1.67A 3. Material: ABS 4. Overcurrent and overvoltage protection of the circuit; Short circuit protection 5. Product color: White 6.Line leng: 1M
A71T			QC3.0/3A with cable 1USB-A (White)	TYPE-C	¥6.80	300	74.0	40.5	53.5	0.1603	26	<ul style="list-style-type: none"> 1.Input: AC 100-240V 50-60Hz 0.35A 2. Ouput: DC 5V=3A 9V=2.22A 12V=1.67A 3. Material: ABS 4. Overcurrent and overvoltage protection of the circuit; Short circuit protection 5. Product color: White 6.Line leng: 1M
A71L			QC3.0/3A with cable 1USB-A (White)	5G	¥7.00	300	74.0	40.5	53.5	0.1603	26	<ul style="list-style-type: none"> 1.Input: AC 100-240V 50-60Hz 0.35A 2. Ouput: DC 5V=3A 9V=2.22A 12V=1.67A 3. Material: ABS 4. Overcurrent and overvoltage protection of the circuit; Short circuit protection 5. Product color: White 6.Line leng: 1M
A8			PD20W Single port (1C) (White)	Without Cable	¥8.50	400	62.0	35.0	37.0	0.0803	27.5	<ul style="list-style-type: none"> 1. Size: 75.5x45.7x24.35mm Weight:50g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB-C DCSV/3A,9V/2.22A,12V/1.67A 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A8T			PD20W with cable Single port (1C) (White)	C-C	¥10.50	200/10	63.0	32.0	43.5	0.0877	20.5	<ul style="list-style-type: none"> 1. Size: 75.5x45.7x24.35mm Weight:50g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB-C DCSV/3A,9V/2.22A,12V/1.67A 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A8L			PD20W with cable Single port (1C) (White)	C-IP	¥12.50	200/10	63.0	32.0	43.5	0.0877	20.5	<ul style="list-style-type: none"> 1. Size: 75.5x45.7x24.35mm Weight:50g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB-C DCSV/3A,9V/2.22A,12V/1.67A 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A9S			3A 2USB-A (White)	Without Cable	¥2.80	500	45.5	37.8	23.2	0.0399	17.15	<ul style="list-style-type: none"> 1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 3. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A9V			3A with cable 2USB-A (White)	MICRO	¥4.80	300	73.0	40.0	51.5	0.1504	25.3	<ul style="list-style-type: none"> 1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 3. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC

A9T			3A with cable 2USB-A (White)	TYPE-C	¥ 5.50	300	73.0	40.0	51.5	0.1504	25.3	1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 3. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A9L			3A with cable 2USB-A (White)	5G	¥ 5.60	300	73.0	40.0	51.5	0.1504	25.3	1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 3. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A11S			PD20W Single port (1C) (Black)	Without Cable	¥ 11.00	200/10	72.0	38.5	25.5	0.0707	14.1	Input: AC 100V-240V 50HZ Output: (PDO)5.0V DC 3.0Aor 9.0V DC 2.77A (PPS)3.3-5.9V DC 3.0Aor 3.3-10.0V DC 2.25A
A11			PD20W with cable Single port (1C) (Black)	C-C	¥ 13.50	200/10	89.0	44.0	28.5	0.1116	22.2	Input: AC 100V-240V 50HZ Output: (PDO)5.0V DC 3.0Aor 9.0V DC 2.77A (PPS)3.3-5.9V DC 3.0Aor 3.3-10.0V DC 2.25A Line length: 1M
A12S			PD45W Single port (1C) (Black)	Without Cable	¥ 21.00	200/10	72.0	38.5	25.5	0.0707	23.8	Input:AC 100V-240V 50HZ Output: (POD)5V DC 3A.15W or 9V DC 3A 27W or 15C DC 3A 45W or20V DC 2.25A 45W(PPS)3.0-20V DC 2.25A(7.5-45W)
A12			PD45W with cable Single port (1C) (Black)	C-C	¥ 23.50	200/10	89.0	44.0	28.5	0.1116	31.85	Input:AC 100V-240V 50HZ Output: (POD)5V DC 3A.15W or 9V DC 3A 27W or 15C DC 3A 45W or20V DC 2.25A 45W(PPS)3.0-20V DC 2.25A(7.5-45W) Line length: 1M
A15S			PD20W Single port (1C) (White)	Without Cable	¥ 6.00	500				0.0000		1. Input:AC100-240V 50-60Hz 0.6A 2. Output: single USB-C DC5V/3A,9V/2.22A,12V/1.67A 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A15T			PD20W Single port (1C) (White)	C-C	¥ 8.90	300/50	73.0	40.0	51.5	0.1504		1. Input:AC100-240V 50-60Hz 0.6A 2. Output: single USB-C DC5V/3A,9V/2.22A,12V/1.67A 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 5.Product color: white 6.Line length: 1m
A15L			PD20W Single port (1C) (White)	C-IP	¥ 9.90	300/50	73.0	40.0	51.5	0.1504		1. Input:AC100-240V 50-60Hz 0.6A 2. Output: single USB-C DC5V/3A,9V/2.22A,12V/1.67A 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 5.Product color: white 6.Line length: 1m
A19T			PD25W USB-C+USB-A (White)	C-C	¥ 10.50	300/50	73.0	40.0	51.5	0.1504		1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC5V/3A,9V/2.22A,12V/1.67A(MAX) 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 5.Product color: white 6.Line length: 1m
A19L			PD25W USB-C+USB-A (White)	C-IP	¥ 12.00	300/50	73.0	40.0	51.5	0.1504		1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC5V/3A,9V/2.22A,12V/1.67A(MAX) 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 5.Product color: white 6.Line length: 1m
A13S			3A 1USB-A (White)	Without Cable	¥ 2.40	500	47.0	41.5	26.5	0.0517	17.75	Input:AC 100V-240V 50HZ Output: (POD)5V DC 3A.15W or 9V DC 3A 27W or 15C DC 3A 45W or20V DC 2.25A 45W(PPS)3.0-20V DC 2.25A(7.5-45W)
A13V			3A with cable 1USB-A (White)	MICRO	¥ 3.70	300	54.0	47.0	37.0	0.0939	20.05	Input:AC 100V-240V 50HZ Output: (POD)5V DC 3A.15W or 9V DC 3A 27W or 15C DC 3A 45W or20V DC 2.25A 45W(PPS)3.0-20V DC 2.25A(7.5-45W) Line length: 1M

			3A with cable 1USB-A (White)	TYPE-C	¥ 4.00	300	54.0	47.0	37.0	0.0939	20.05	Input:AC 100V-240V 50HZ Output:(POD)5V DC 3A.15W or 9V DC 3A 27W or 15C DC 3A 45W or20V DC 2.25A 45W(PPS)3.0-20V DC 2.25A(7.5-45W) Line length: 1M
			3A with cable 1USB-A (White)	5G	¥ 4.20	300	54.0	47.0	37.0	0.0939	20.05	Input:AC 100V-240V 50HZ Output:(POD)5V DC 3A.15W or 9V DC 3A 27W or 15C DC 3A 45W or20V DC 2.25A 45W(PPS)3.0-20V DC 2.25A(7.5-45W) Line length: 1M
NEW			33W with cable 1USB-A (White)	TYPE-C	¥ 8.60	200	53.5	42.0	33.0	0.0742		1.Input: AC 100V-240V 50/60HZ 0.7A 2.Output: DC 5V/3A 9V/3A 12V/2.25A 20V/1.35A 11V/3A maximum 3.Material: ABS 4.Overcurrent and overvoltage protection of the circuit; Short circuit protection, explosion-proof, intelligent recognition IC, Xiaomi top speed charging, Redmi top charge, Samsung QC3.0 fast charging
			20W with cable 1USB-A (White)	MICRO	¥ 5.90	240/40	73.0	40.0	51.5	0.1504		1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC5V/3A,9V/2.22A,12V/1.67A(MAX) 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof 5.Product color: white 6.Line length: 1m
			20W with cable 1USB-A (White)	TYPE-C	¥ 6.20	240/40	73.0	40.0	51.5	0.1504		1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC5V/3A,9V/2.22A,12V/1.67A(MAX) 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof 5.Product color: white 6.Line length: 1m
			20W with cable 1USB-A (White)	5G	¥ 6.40	240/40	73.0	40.0	51.5	0.1504		1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC5V/3A,9V/2.22A,12V/1.67A(MAX) 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof 5.Product color: white 6.Line length: 1m
			PD20W+QC3.0 USB-C+USB-A (White)	Without Cable	¥ 14.00	200	59.5	28.0	38.0	0.0633	17.92	Input:AC 100-240V,50/60Hz 0.35A Output:DC 5V=3A 9V=2.2A 12V=1.67A Working temperature:-10°C-50°C
			PD20W+QC3.0 USB-C+USB-A Green light (White)	Without Cable	¥ 16.50	200	55.0	54.0	37.0	0.1099	10.85	Input:AC 100-240V,50-60Hz 0.6A Output:USB-C: 5V=3A 9V=2.22A 12V=1.67A USB-A: 5V=3A 9V=2A 12V=1.5A USB-A+USB-C: 5V=3A (total) Working temperature:-10°C-50°C
			PD18W Single port (1C) (White)	Without Cable	¥ 14.50	200	59.5	28.0	38.0	0.0633	15.2	Input:AC 100-240V,50/60Hz 0.6A Output:DC 5V=3A 9V=2A 12V=1.5A Working temperature:-10°C-50°C
NEW			PD20W Single port (1C) (White)	Without Cable	¥ 8.90	200	59.5	28.0	38.0	0.0633	17	Input:AC 100-240V,50/60Hz 0.5A Output:DC 5V=3A 9V=2.2A Working temperature:-10°C-50°C
			PD27W Single port (1C) (White)	Without Cable	¥ 9.00	100	37.5	34.5	46.5	0.0602	10.65	Input:AC 100-240V,50-60Hz 0.7A Output:5V=3Aor9V=3Aor12V=2.25 (PPS) 3.3-5.9V=3Aor3.3-11.0V=2.45A
			PD25W/3A USB-C+USB-A Green light (White)	Without Cable	¥ 14.50	100	37.0	34.5	46.5	0.0594	8.9	Input:AC 100-240V,50-60Hz 0.7A Output:USB-C: 5V=3A 9V=2.77A (PPS) 3.3-5.9V=3Aor3.3-11.0V=2.75A USB-A: 5V=3A 9V=2.77A USB-A+USB-C: 5V=3A (total)
			PD20W/3A USB-C+USB-A (White)	Without Cable	¥ 15.50	100	37.0	34.5	46.5	0.0594	8.45	Input:AC 100-240V,50-60Hz 0.6A Output:USB-C: 5V=3A 9V=2.22A 12V=1.67A USB-A: 5V=3A 9V=2A 12V=1.5A USB-A+USB-C: 5V=3A (total)

GA-32P/C-C			PD27W with cable Single port (1C) (White)	C-C	¥12.00	100	34.5	31.0	47.0	0.0503	11.5	Input:AC 100-240V,50-60Hz 0.7A Output:5V=3Aor9V=3Aor12V=2.25 (PPS) 3.3-5.9V=3Aor3.3-11.0V=2.45A Line length: 1M
GA-32P/C-IO5				C-IP	¥14.00							
GA-35/C-IO5			PD20W with cable Single port (1C) (White)	C-IP	¥18.00	100	37.5	35.0	42.5	0.0558	12.2	Input:AC 100-240V,50-60Hz 0.6A Output:5V=3Aor9V=2.22Aor12V=1.67A Line length: 1M
GA-36/C-C			PD25W+QC3.0 with cable USB-C+USB-A (White)	C-C	¥18.00	100	37.0	34.5	46.5	0.0594	11	Input:AC 100-240V,50-60Hz 0.7A Output:USB-C: 5V=3A 9V=2.77A (PPS) 3.3-5.9V=3Aor3.3-11.0V=2.75A USB-A: 5V=3A 9V=2.77A USB-A+USB-C: 5V=3A (total)
GA-36/C-IO5												
GA-37/C-C			PD20W+QC3.0 with cable USB-C+USB-A (White)	C-C	¥18.70	100	37.0	34.5	46.5	0.0594	10.55	Input:AC 100-240V,50-60Hz 0.6A Output:USB-C: 5V=3A 9V=2.22A 12V=1.67A USB-A: 5V=3A 9V=2.2A 12V=1.5A USB-A+USB-C: 5V=3A (total)
GA-37/C-IO5												
GA-38/C-C			PD20W+QC3.0 with cable USB-C+USB-A Green/Red light (White)	C-C	¥18.50	200	37.0	34.5	46.5	0.0594	10.8	USB+PD 20W fast charger At the same time, charging shows that the red light is 5V=3A. USB 18W fast charging shows Green light or PD 20W fast charging shows Green light
GA-38/C-IO5												
GA-40/C-C			PD45W+QC3.0 with cable 2USB-C Green light (White)	C-C	¥40.00	100	50.0	34.5	49.0	0.0845	19.05	PD 45W fast charger Input:AC 100V-240V,50Hz 1.0A Output:C1 or C2: 20V=2.25A or 12V=3A or 5V=3A or 3.3V-11V=3A Output:C1+C2: 5V=3A or 12V=3A 3.3V-11V=3A
GA-40/C-IO5												
GA-41/C-C			PD25W+QC3.0 with cable USB-C+USB-A (White)	C-C	¥16.00	100	54.0	31.5	41.5	0.0706	11.7	PD 25W fast charger Input:AC 100-240V,50-60Hz 0.7A Output:Type-C: 5V=3A 9V=2.77A (PPS) 3.3-5.9V=3Aor3.3-11V=2.75V USB-A: 5V=3A 9V=2.77A Type-C+USB-A: 5V=3A (total)
GA-41/C-IO5												
GA-42黑/C-C			PD67W with cable 2USB-C+1USB-A Green light (Black)	C-C	¥54.00	100	54.0	31.5	41.5	0.0706	20.5	PD 65W fast charger ,support Samsung AFC, Huawei FCP, PD3.0, QC3.0 INPUT:AC 100-240V 50/60Hz 1.8A OUTPUT:USB-C1:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W USB-C2:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W USB-A:4.5V=5A 5V=4.5A 9V=2A 12V=1.5A 10V=2.25A 22.5W USB-C1+USB-C2:45W+20W 65W USB-C1+USB-A:45W+20W 65W USB-C2+USB-A:20W MAX USB-C1+(USB-C2+USB-A):45W+20W 65W Line length: 1000MM
GA-43/C-C			GAN 35W with cable Single port (1C) (White)	C-C	¥20.00	100	55.5	47.0	25.5	0.0665	21.7	Input:100-240V,50/60Hz 0.8A Output:5V-3A/9V-3A/12V=2.92A/15V=2.33A/20V=1.75A PPS1:3.3V-11V=3A PPS2:3.3V-16V=2.2A
GA-43/C-IO5												
GA-44黑/C-C			PD45W with cable USB-C+USB-A Green light (Black)	C-C	¥19.90	100	50.0	34.5	49.0	0.0845	17.75	PD 45W fast charger Input:AC 100V-240V,50Hz 1.0A Output:USB-C: 5V=3A 9V=3A 12V=3A 15V=3A 20V=2.25A PPS Output:USB-A: 5V=3A 9V=3A 12V=3A 15V=3A 20V=2.25A Output:USB-C+USB-A: 5V=3A Line length: 1M
GA-01F/V8			18W/QC3.0 with cable 1USB-A (White)	MICRO	¥8.90	100	35.5	32.5	43.0	0.0496	9.95	Input:100-240V,50/60Hz 0.5A Output:5V-3A/9V-2A/12V-1.5A Working temperature:-10°C-50°C QC 3.0 charger Line length: 1M
GA-01F/TC				TYPE-C	¥9.40							
GA-01F/IO5				5G	¥9.60							
GA-02F/V8			18W/QC3.0 with cable 1USB-A (White)	MICRO	¥11.50	100	35.5	32.5	43.0	0.0496	11.16	Input:100-240V,50/60Hz 0.5A Output:5V-3A/9V-2A/12V-1.5A Working temperature:-10°C-50°C QC 3.0 charger Line length: 1M
GA-02F/TC				TYPE-C	¥12.00							
GA-02F/IO5				5G	¥12.30							
GA-19F/V8			18W/QC3.0 with cable 1USB-A (White)	MICRO	¥9.50	100	33.0	32.0	45.0	0.0475	10.6	Input:100-240V,50/60Hz 0.5A Output:5V-3A/9V-2A/12V-1.5A Working temperature:-10°C-50°C QC 3.0 charger Line length: 1M
GA-19F/TC				TYPE-C	¥10.00							
GA-19F/IO5				5G	¥10.20							

GA-01/V8			2.4A with cable 2USB-A (White)	MICRO	¥ 8.20	100	35.5	32.5	43.0	0.0496	9.84	Input:100-240V,50/60Hz Output:5V-2.4A(MAX) Working temperature:-10°C-50°C Line length: 1M
GA-01/TC				TYPE-C	¥ 8.70							
GA-01/IOS				5G	¥ 9.00							
GA-05/TC			2.4A with cable 2USB-A (White)	TYPE-C	¥ 9.00	100	37.5	35.0	42.5	0.0558	10.15	Input:100-240V,50/60Hz Output:5V-2.4A(MAX) Working temperature:-10°C-50°C Line length: 1M
GA-05/IOS				5G	¥ 9.40							
GA-08白/V8			2.4A with cable 2USB-A (White)	MICRO	¥ 7.50	100	35.5	32.5	43.0	0.0496	9.62	Input:100-240V,50/60Hz Output:5V-2.4A(MAX) Working temperature:-10°C-50°C Line length: 1M
GA-08白/TC				TYPE-C	¥ 8.00							
GA-08白/IOS				5G	¥ 8.20							
GA-09/V8			2.4A with cable 2USB-A (White)	MICRO	¥ 9.00	100	35.5	32.5	43.0	0.0496	10.06	Input:100-240V,50/60Hz Output:5V-2.4A(MAX) Working temperature:-10°C-50°C Line length: 1M
GA-09/TC				TYPE-C	¥ 9.40							
GA-09/IOS				5G	¥ 9.80							
GA-19/V8			3A with cable 2USB-A Green light (White)	MICRO	¥ 7.50	100	35.5	32.5	43.0	0.0496	9.75	Input:100-240V,50/60Hz Output:5V-2.4A(MAX) Working temperature:-10°C-50°C Line length: 1M
GA-19/TC				TYPE-C	¥ 8.00							
GA-19/IOS				5G	¥ 8.20							
GA-26/V8			3.4A with cable 3USB-A (White)	MICRO	¥ 8.50	100	55.0	34.0	50.0	0.0935	14.9	Input:AC100-240V,50/60Hz 0.35A Output:DC5V=3.4A(MAX) Working temperature:-10°C-50°C Line length: 1M
GA-26/TC				TYPE-C	¥ 9.00							
GA-26/IOS				5G	¥ 9.20							
GA-27/V8			3A with cable 2USB-A Green light (White)	MICRO	¥ 8.50	100	54.0	31.5	41.5	0.0706	11	Input:AC 100-240V,50-60Hz 0.6A Output:5V=3A Line length: 1M
GA-27/TC				TYPE-C	¥ 8.90							
GA-27/IOS				5G	¥ 9.30							
GA-39/V8			33W/3A with cable 1USB-A (White)	MICRO	¥ 8.40	100	35.5	32.5	43.0	0.0496	9.7	Input:AC 100V-240V 50/60HZ 0.7A Output:DC 5V=3A 9V= 3A 12V=2.25A, 20V=1.35A 11V=3A MAX Line length: 1M
GA-39/TC				TYPE-C	¥ 8.90							
GA-39/IOS				5G	¥ 9.10							



























GERLAX®

























US CHARGER



























ADD:New Asia International Digital City No. 55 Xiti Erma Road, Guangzhou



























Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)



















型号	产品图	产品图	卖点	类型	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Product Picture	SELLING POINTS	Type	Price rmb	OUTER CTN/ INNER BOX	Carton size (CM)			CBM/CTN (m³)	KG/CTN	SPECIFICATIONS
A1MS新			2.4A 1USB-A (White)	Without Cable	¥ 3.40	500	47.0	39.3	25.7	0.0475	18	1. Size: 23x35.5x64mm Weight:30g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB DCSV / 2.4A, up to 12W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof
A2MS新			2.4A 2USB-A (White)	Without Cable	¥ 4.40	500	46.0	27.0	35.5	0.0441	17.9	1. Size: 24x42x65mm Weight:31.5g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: USB-A DCSV / 2.4A USB-B DCSV / 2.4A /AUTO-ID,up to 12W 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A2MV			2.4A with cable 2USB-A (White)	MICRO	¥ 5.40	300	54.0	47.0	37.0	0.0939	20.6	1. Size: 24x42x65mm Weight:31.5g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: USB-A DCSV / 2.4A USB-B DCSV / 2.4A /AUTO-ID,up to 12W 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 7.Pack color: yellow
A2MT			2.4A with cable 2USB-A (White)	TYPE-C	¥ 6.10	300	54.0	47.0	37.0	0.0939	20.6	1. Size: 24x42x65mm Weight:31.5g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: USB-A DCSV / 2.4A USB-B DCSV / 2.4A /AUTO-ID,up to 12W 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 7.Pack color: blue
A2ML			2.4A with cable 2USB-A (White)	5G	¥ 6.20	300	54.0	47.0	37.0	0.0939	20.6	1. Size: 24x42x65mm Weight:31.5g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: USB-A DCSV / 2.4A USB-B DCSV / 2.4A /AUTO-ID,up to 12W 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 8.Pack color: orange
A300M			QC3.0/3A 1USB-A (White)	Without Cable	¥ 5.30	200/10	77.0	33.0	32.5	0.0826	12.05	1. Size: 24.5x40x61mm Weight:35.2g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB DC 5V / 3A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A3MV			QC3.0/3A with cable 1USB-A (White)	MICRO	¥ 5.90	300	54.0	47.0	37.0	0.0939	22.05	1. Size: 24.5x40x61mm Weight:35.2g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB DC 5V / 3A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A3MT			QC3.0/3A with cable 1USB-A (White)	TYPE-C	¥ 6.20	300	54.0	47.0	37.0	0.0939	22.05	1. Size: 24.5x40x61mm Weight:35.2g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB DC 5V / 3A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A3ML			QC3.0/3A with cable 1USB-A (White)	5G	¥ 6.40	300	54.0	47.0	37.0	0.0939	22.05	1. Size: 24.5x40x61mm Weight:35.2g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB DC 5V / 3A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A4MR			PD20W Single port (1C) (White)	Without Cable	¥ 6.90	300	54.0	47.0	37.0	0.0939	18.8	1. Size: 26.5x43x61.2mm Weight:40g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYPC-C 5V / 3A,9V/2.22A,12V/1.67A up to 20W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 7.Pack color: red
A4MS			PD20W Single port (1C) (White)	Without Cable	¥ 6.90	300	54.0	47.0	37.0	0.0939	18.8	1. Size: 26.5x43x61.2mm Weight:40g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYPC-C 5V / 3A,9V/2.22A,12V/1.67A up to 20W. 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC

A4MT			PD20W with cable Single port (1C) (White)	C-C	¥ 9.50	100	35.5	32.5	43.0	0.0496	8.8	1. Size: 26.5x43x61.2mm Weight:40g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYP-C 5V / 3A,9V/2.22A,12V/1.67A up to 20W. 4. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A4ML			PD20W with cable Single port (1C) (White)	C-IP	¥ 11.00	100	35.5	32.5	43.0	0.0496	8.8	1. Size: 26.5x43x61.2mm Weight:40g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYP-C 5V / 3A,9V/2.22A,12V/1.67A up to 20W. 4. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A5MS			PD20W USB-C+USB-A (White)	Without Cable	¥ 7.90	300	54.0	47.0	37.0	0.0939	19.25	Input: AC 100-240V50-60Hz 0.6A Output 1(PD): 5V=3A 9V=2.22A 12V=1.67A Output 2(QC 3.0): 5V=3A 9V=2A 12V=1.5A
A5MT			PD20W with cable USB-C+USB-A (White)	C-C	¥ 10.90	100	35.5	32.5	43.0	0.0496	8.95	1. Size: 26.5x43x61.2mm Weight:40g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYP-C 5V / 3A,9V/2.22A,12V/1.67A up to 20W. 4. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A5ML			PD20W with cable USB-C+USB-A (White)	C-IP	¥ 12.90	100	35.5	32.5	43.0	0.0496	8.95	1. Size: 26.5x43x61.2mm Weight:40g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: TYP-C 5V / 3A,9V/2.22A,12V/1.67A up to 20W. 4. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A700M			QC3.0/3A 1USB-A (White)	Without Cable	¥ 5.50	200/10	67.0	33.0	32.5	0.0719	11.65	1. Size: 24x42x63mm Weight:33.6g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: single USB DCSV/3A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A7MV			QC3.0/3A with cable 1USB-A (White)	MICRO	¥ 6.00	300	54.0	47.0	37.0	0.0939	21.7	1. Size: 24x42x63mm Weight:33.6g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: single USB DCSV/3A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A7MT			QC3.0/3A with cable 1USB-A (White)	TYPE-C	¥ 6.30	300	54.0	47.0	37.0	0.0939	21.7	1. Size: 24x42x63mm Weight:33.6g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: single USB DCSV/3A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A7ML			QC3.0/3A with cable 1USB-A (White)	5G	¥ 6.50	300	54.0	47.0	37.0	0.0939	21.7	1. Size: 24x42x63mm Weight:33.6g 2. Input:AC100-240V 50-60Hz 0.6A 3. Output: single USB DCSV/3A,9V/2A,12V/1.5A up to 18W. 4. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A71MV			QC3.0/3A with cable 1USB-A (White)	MICRO	¥ 6.50	300	73.0	40.0	51.5	0.1504	25.3	1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V/3A 9V/2A 12V/1.5A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A71MT			QC3.0/3A with cable 1USB-A (White)	TYPE-C	¥ 6.80	300	73.0	40.0	51.5	0.1504	25.3	1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V/3A 9V/2A 12V/1.5A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A71ML			QC3.0/3A with cable 1USB-A (White)	5G	¥ 7.00	300	73.0	40.0	51.5	0.1504	25.3	1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V/3A 9V/2A 12V/1.5A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A8M			PD20W Single port (1C) (White)	Without Cable	¥ 8.50	400	62.0	35.0	37.0	0.0803	29.7	1. Size: 57.3x42.8x27.5mm Weight:54.3g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB-C DCSV/3A,9V/2.22A,12V/1.67A 4. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC

A8MT			PD20W with cable Single port (1C) (White)	C-C	¥10.50	200/10	63.0	32.0	43.5	0.0877	27.5	<ul style="list-style-type: none"> 1. Size: 57.3x42.8x27.5mm Weight:54.3g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB-C DC5V/3A,9V/2.22A,12V/1.67A 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A8ML			PD20W with cable Single port (1C) (White)	C-IP	¥12.50	200/10	63.0	32.0	43.5	0.0877	27.5	<ul style="list-style-type: none"> Single USB-C*1 1. Size: 57.3x42.8x27.5mm Weight:54.3g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB-C DC5V/3A,9V/2.22A,12V/1.67A 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A9MS			3A 2USB-A (White)	Without Cable	¥2.80	500	46.5	38.8	24.7	0.0446	/	<ul style="list-style-type: none"> 1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 3. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A9MV			3A with cable 2USB-A (White)	MICRO	¥4.80	300	73.0	40.0	51.5	0.1504	23	<ul style="list-style-type: none"> 1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 3. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A9MT			3A with cable 2USB-A (White)	TYPE-C	¥5.50	300	73.0	40.0	51.5	0.1504	23	<ul style="list-style-type: none"> 1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 3. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A9ML			3A with cable 2USB-A (White)	5G	¥5.60	300	73.0	40.0	51.5	0.1504	23	<ul style="list-style-type: none"> 1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 3. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A10MS			3A 1USB-A (White)	Without Cable	¥2.40	500	45.5	37.8	23.2	0.0399	18	<ul style="list-style-type: none"> 1. Size: 23x35.5x83mm Weight:33.3g 2. Input:AC100-240V 50-60Hz 0.35A 3. Output: single USB DC5V/3A 4. Plug: Nickel plated EU plug, 24 Hours Salt -Fog Test 5. Material:ABS 6. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A11MS			PD25W Single port (1C) (Black)	Without Cable	¥11.00	200/10	72.0	38.5	25.5	0.0707	14.1	<ul style="list-style-type: none"> Input: AC 100V-240V 50HZ Output: (PDO)5.0V DC 3.0A or 9.0V DC 2.77A (PPS)3.3-5.9V DC 3.0A or 3.3-10.0V DC 2.25A
A11M			PD25W with cable Single port (1C) (Black)	C-C	¥13.50	200/10	89.0	44.0	28.5	0.1116	22.2	<ul style="list-style-type: none"> Output: (PDO)5.0V DC 3.0A or 9.0V DC 2.77A(PPS)3.3-5.9VDC 3.0A or 3.3-11.0VDC 2.25A Line length: 1M
A12MS			PD45W Single port (1C) (Black)	Without Cable	¥21.00	200/10	72.0	38.5	25.5	0.0707	23.8	<ul style="list-style-type: none"> Input:AC 100V-240V 50HZ Output: (POD)5V DC 3A,15W or 9V DC 3A 27W or 15C DC 3A 45W or20V DC 225A 45W(PPS)3.0-20V DC 2.25A(7.5-45W)
A12M			PD45W with cable Single port (1C) (Black)	C-C	¥23.50	200/10	89.0	44.0	28.5	0.1116	31.85	<ul style="list-style-type: none"> Input:AC 100V-240V 50HZ Output: (POD)5V DC 3A,15W or 9V DC 3A 27W or 15C DC 3A 45W or20V DC 225A 45W(PPS)3.0-20V DC 2.25A(7.5-45W) Line length: 1M
 A19MT			PD25W USB-C+USB-A (White)	C-C	¥10.50	300/50	74.0	40.5	53.5	0.1603		<ul style="list-style-type: none"> 1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC5V/3A,9V/2.22A,12V/1.67A (MAX) 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 5.Product color: white 6.Line length: 1m
 A19ML			PD25W USB-C+USB-A (White)	C-IP	¥12.00	300/50	74.0	40.5	53.5	0.1603		<ul style="list-style-type: none"> 1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC5V/3A,9V/2.22A,12V/1.67A (MAX) 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 5.Product color: white 6.Line length: 1m

A13MS			15W/3A 1USB-A (White)	Without Cable	¥ 2.40	500	45.5	37.8	23.2	0.0399	/	Input: AC 100-240V 50-60Hz 0.35A Output: DC 5V=3A
A13MV			15W/3A with cable 1USB-A (White)	MICRO	¥ 3.70	300	54.0	47.0	37.0	0.0939	19.3	Input: AC 100-240V 50-60Hz 0.35A Output: DC 5V=3A Line length: 1M
A13MT			15W/3A with cable 1USB-A (White)	TYPE-C	¥ 4.00	300	54.0	47.0	37.0	0.0939	19.3	Input: AC 100-240V 50-60Hz 0.35A Output: DC 5V=3A Line length: 1M
A13ML			15W/3A with cable 1USB-A (White)	5G	¥ 4.20	300	54.0	47.0	37.0	0.0939	19.3	Input: AC 100-240V 50-60Hz 0.35A Output: DC 5V=3A Line length: 1M
NEW A14M			33W with cable 1USB-A (White)	C-C	¥ 8.60	200	53.5	42.0	33.0	0.0742		1.Input: AC 100V-240V 50/60HZ 0.7A 2.Output: DC 5V/3A 9V/3A 12V/2.25A 20V/1.35A 11V/3A maximum 3.Material: ABS 4.Overcurrent and overvoltage protection of the circuit; Short circuit protection, explosion-proof, intelligent recognition IC, Xiaomi top speed charging, Redmi top charge, Samsung QC3.0 fast charging
NOT GA-25MPS			PD20W+QC3.0 USB-C+USB-A (White)	Without Cable	¥ 14.00	200	59.5	28.0	38.0	0.0633	17	Input:AC 100-240V,50/60Hz 0.35A Output:DC 5V=3A 9V=2.2A 12V=1.67A Working temperature:-10°C~50°CUSB Ports: USB-A+USB-C
NOT GA-31MPS			PD20W+QC3.0 USB-C+USB-A (White)	Without Cable	¥ 8.90	200	59.5	28.0	38.0	0.0633	17.1	Input:AC 100-240V,50/60Hz 0.5A Output:DC 5V=3A 9V=2.2A Working temperature:-10°C~50°C
GA-32MPS			PD27W Single port (1C) (White)	Without Cable	¥ 9.00	200	59.5	28.0	38.0	0.0633	18.8	Input:AC 100-240V,50-60Hz 0.7A Output:5V=3Aor9V=3Aor12V=2.25 (PPS) 3.3-5.9V=3Aor3.3-11.0V=2.45A
GA-35MS			PD20W Single port (1C) (White)	Without Cable	¥ 11.00	200	59.5	28.0	38.0	0.0633	13.3	Input:AC 100-240V,50-60Hz 0.6A Output:5V=3Aor9V=2.22Aor12V=1.67A
GA-36MS			PD25W+3A USB-C+USB-A Green light (White)	Without Cable	¥ 14.50	100	37.0	34.5	46.5	0.0594	8.6	Input:AC 100-240V,50-60Hz 0.7A Output:USB-C: 5V=3A 9V=2.77A (PPS) 3.3-5.9V=3Aor3.3-11.0V=2.75A USB-A: 5V=3A 9V=2.77A USB-A+USB-C: 5V=3A (total)
GA-38MS			PD20W+QC3.0 USB-C+USB-A Green/Red light (White)	Without Cable	¥ 15.50	200	59.5	28.0	38.0	0.0633	13.5	USB+PD 20W fast charger At the same time, charging shows that the red light is 5V=3A. USB 18W fast charging shows Green light or PD 20W fast charging shows Green light
GA-40MS			PD45W+QC3.0 2USB-C Green light (White)	Without Cable	¥ 37.00	100	54.0	31.5	41.5	0.0706	16	PD 45W fast charger Input:AC 100V-240V,50Hz 1.0A Output:C1or C2: 20V=2.25A or 12V=3A or 5V=3A or 3.3V-11V=3A Output:C1+ C2: 5V=3A or 12V=3A 3.3V-11V=3A
NEW GA-41MS			PD25W+QC3.0 USB-C+USB-A (White)	Without Cable	¥ 13.00	100	54.0	31.5	41.5	0.0706	9.1	PD 25W fast charger Input:AC 100-240V,50-60Hz 0.7A Output:Type-C: 5V=3A 9V=2.77A (PPS)3.3-5.9V=3Aor3.3-11V=2.75V USB-A: 5V=3A 9V=2.77A Type-C+USB-A: 5V=3A (total)

		PD67W+QC3.0 2USB-C+1USB-A Green light (Black)	Without Cable	¥ 50.00	100	54.0	31.5	41.5	0.0706		PD 65W fast charger ,support Samsung AFC, Huawei FCP , PD3.0 , QC3.0 INPUT:AC 100-240V 50/60HZ 1.8A OUTPUT:USB-C1:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W USB-C2:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W USB-A:4.5V=5A 5V=4.5A 9V=2A 12V=1.5A 10V=2.25A 22.5W USB-C1+USB-C2:45W+20W 65W USB-C1+USB-A:45W+20W 65W USB-C2+USB-A:20W MAX USB-C1+(USB-C2+USB-A):45W+20W 65W
		PD67W+QC3.0 2USB-C+1USB-A Green light (White)	Without Cable	¥ 50.00	100	54.0	31.5	41.5	0.0706		PD 65W fast charger ,support Samsung AFC, Huawei FCP , PD3.0 , QC3.0 INPUT:AC 100-240V 50/60HZ 1.8A OUTPUT:USB-C1:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W USB-C2:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W USB-A:4.5V=5A 5V=4.5A 9V=2A 12V=1.5A 10V=2.25A 22.5W USB-C1+USB-C2:45W+20W 65W USB-C1+USB-A:45W+20W 65W USB-C2+USB-A:20W MAX USB-C1+(USB-C2+USB-A):45W+20W 65W
		PD45W USB-C+USB-A Green light (Black)	Without Cable	¥ 16.50	100	54.0	31.5	41.5	0.0706	14.3	PD 45W fast charger Input:AC 100V-240V,50Hz 1.0A Output:USB-C: 5V=3A 9V=3A 12V=3A 15V=3A 20V=2.25A PPS Output:USB-A: 5V=3A 9V=3A 12V=3A 15V=3A 20V=2.25A Output:USB-C+USB-A: 5V=3A
		18W/3A 1USB-A (White)	Without Cable	¥ 7.00	400/10	82.0	33.0	32.5	0.0879		Input:100-240V,50/60Hz 0.5A Output:5V-3A/9V-2A/12V-1.5A Working temperature:-10°C-50°C QC 3.0 charger
		18W/QC3.0 1USB-A Green light (White)	Without Cable	¥ 7.50	200/10	77.0	33.0	32.0	0.0813	13.4	Input:100-240V,50/60Hz 0.5A Output:5V-3A/9V-2A/12V-1.5A Working temperature:-10°C-50°C QC 3.0 charger
		33W/QC3.0 1USB-A (White)	Without Cable	¥ 6.50	200	67.0	33.0	32.5	0.0719	11.5	Input:AC100-240V,50/60Hz0.35A Output:DC5V=3A 9V=2A 12V=1.5A(MAX) Working temperature:-10°C-50°C QC 3.0 charger
		2.4A 2USB-A (White, Black)	Without Cable	¥ 5.50	400/10	67.0	33.0	32.5	0.0719		Input:100-240V,50/60Hz Output:5V-2.4A(MAX) Working temperature:-10°C-50°C
		PD20W+QC3.0 with cable USB-C+USB-A (White)	C-C C-IP	¥ 17.00 ¥ 19.00	100	35.5	32.5	43.0	0.0496	17.26	Input:AC 100-240V,50/60Hz 0.35A Output:DC 5V=3A 9V=2.2A 12V=1.67A Working temperature:-10°C-50°C USB Ports: USB-A+USB-C Line length: 1M
		PD27W with cable Single port (1C) (White)	C-C C-IP	¥ 12.00 ¥ 14.00	100	34.5	31.0	47.0	0.0503	11.2	Input:AC 100-240V,50-60Hz 0.7A Output:5V=3Aor9V=3Aor12V=2.25 (PPS) 3.3-5.9V=3Aor3.3-11.0V=2.45A Line length: 1M
		PD20W with cable Single port (1C) (White)	C-C C-IP	¥ 15.50 ¥ 18.00	100	37.5	35.0	42.5	0.0558	11.9	Input:AC 100-240V,50-60Hz 0.6A Output:5V=3Aor9V=2.22Aor12V=1.67A Line length: 1M
		PD25W+QC3.0 with cable USB-C+USB-A Green light (White)	C-C C-IP	¥ 18.00 ¥ 20.00	100	37.0	34.5	46.5	0.0594	10.75	Input:AC 100-240V,50-60Hz 0.7A Output:USB-C: 5V=3A 9V=2.77A (PPS) 3.3-5.9V=3Aor3.3-11.0V=2.75A USB-A: 5V=3A 9V=2.77A USB-A+USB-C: 5V=3A (total)
		PD20W+QC3.0 with cable USB-C+USB-A Green/Red light (White)	C-C C-IP	¥ 18.50 ¥ 20.50	100	37.0	34.5	46.5	0.0594	10.4	USB+PD 20W fast charger At the same time, charging shows that the red light is 5V=3A. USB 18W fast charging shows Green light or PD 20W fast charging shows Green light
		PD45W+QC3.0 with cable 2USB-C Green light (White)	C-C C-IP	¥ 40.00 ¥ 42.00	100	50.0	34.5	49.0	0.0845	18.8	PD 45W fast charger Input:AC 100V-240V,50Hz 1.0A Output:C1or C2: 20V=2.25A or 12V=3A or 5V=3A or 3.3V-11V=3A Output:C1+ C2: 5V=3A or 12V=3A 3.3V-11V=3A

NEW	GA-41M			PD25W+QC3.0 with cable USB-C+USB-A (White)	C-C	¥16.00	100	54.0	31.5	41.5	0.0706	11.2	PD 25W fast charger Input:AC 100-240V,50-60Hz 0.7A Output:Type-C: 5V=3A 9V=2.77A (PPS)3.3-5.9V=3AAor3.3-11V=2.75V USB-A: 5V=3A 9V=2.77A Type-C+USB-A: 5V=3A (total)
					C-IP	¥18.00							
NEW	GA-42M			PD67W with cable 2USB-C+1USB-A Green light (Black)	C-C	¥54.00	100	50.0	34.5	49.0	0.0845		PD 65W fast charger ,support Samsung AFC, Huawei FCP, PD3.0, QC3.0 INPUT:AC 100-240V 50/60Hz 1.8A OUTPUT:USB-C1:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W USB-C2:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W USB-A:4.5V=5A 5V=4.5A 9V=2A 12V=1.5A 10V=2.25A 22.5W USB-C1+USB-C2:45W+20W 65W USB-C1+USB-A:45W+20W 65W USB-C2+USB-A:20W MAX USB-C1+(USB-C2+USB-A):45W+20W 65W Line length: 1000MM
NEW	GA-44M			PD45W with cable USB-C+USB-A Green light (Black)	C-C	¥19.90	100	50.0	34.5	49.0	0.0845	17.1	PD 45W fast charger Input:AC 100V-240V,50Hz 1.0A Output:USB-C: 5V=3A 9V=3A 12V=3A 15V=3A 20V=2.25A PPS Output:USB-A: 5V=3A 9V=3A 12V=3A 15V=3A 20V=2.25A Output:USB-C+USB-A: 5V=3A Line length: 1M
HOT	GA-01MF			18W/QC3.0 with cable 1USB-A (White)	MICRO	¥8.90	100	35.5	32.5	43.0	0.0496	9.96	Input:100-240V,50/60Hz 0.5A Output:5V-3A/9V-2A/12V-1.5A Working temperature:-10°C-50°C QC 3.0 charger Line length: 1M
					TYPE-C	¥9.40							
					5G	¥9.60							
HOT	GA-19MF			18W/QC3.0 with cable 1USB-A (White)	MICRO	¥9.50	100	35.5	32.5	43.0	0.0496	10.1	Input:100-240V,50/60Hz 0.5A Output:5V-3A/9V-2A/12V-1.5A Working temperature:-10°C-50°C QC 3.0 charger Line length: 1M
					TYPE-C	¥10.00							
					5G	¥10.20							
	GA-39M			33W/3A with cable 1USB-A (White)	MICRO	¥8.40	100	35.5	32.5	43.0	0.0496	9.35	Input:AC 100V-240V 50/60HZ 0.7A Output:DC 5V=3A 9V= 3A 12V=2.25A, 20V=1.35A 11V=3A MAX Line length: 1M
					TYPE-C	¥8.90							
					5G	¥9.10							
	GA-01M			2.4A with cable 2USB-A (White)	MICRO	¥8.20	100	35.5	32.5	43.0	0.0496	9.98	Input:100-240V,50/60Hz Output:5V-2.4A(MAX) Working temperature:-10°C-50°C Line length: 1M
					TYPE-C	¥8.70							
					5G	¥9.00							
HOT	GA-08M			2.4A with cable 2USB-A (White)	MICRO	¥7.50	100	35.5	32.5	43.0	0.0496	9.6	Input:100-240V,50/60Hz Output:5V-2.4A(MAX) Working temperature:-10°C-50°C Line length: 1M
					TYPE-C	¥8.00							
					5G	¥8.20							
	GA-19M			3A with cable 2USB-A Green light (White)	MICRO	¥7.50	100	35.5	32.5	43.0	0.0496	9.76	Input:100-240V,50/60Hz Output:5V-2.4A(MAX) Working temperature:-10°C-50°C Line length: 1M
					TYPE-C	¥8.00							
					5G	¥8.20							

GERLAX®

























UK CHARGER

























ADD:New Asia International Digital City No, 55 Xiti Erma Rosd, Guangzhou

























Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)




型号	产品图	产品图	卖点	类型	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Product Picture	SELLING POINTS	Type	Price rmb	OUTER CTN/ INNER	Carton size (CM)			CBM/CTN (m³)	KG/CTN	SPECIFICATIONS
A3YS			QC3.0/3A 1USB-A (White)	Without Cable	¥ 6.20	100	54.0	31.5	41.5	0.0706	8.5	1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 9V / 2A 12V / 1.5A (18W) 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A3YV			QC3.0/3A with cable 1USB-A (White)	MICRO	¥ 7.20	100	54.0	31.5	41.5	0.0706	10.5	1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC 5V / 3A 9V / 2A 12V / 1.5A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A3YT			QC3.0/3A with cable 1USB-A (White)	TYPE-C	¥ 7.50	100	54.0	31.5	41.5	0.0706	10.5	1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC 5V / 3A 9V / 2A 12V / 1.5A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A3YL			QC3.0/3A with cable 1USB-A (White)	5G	¥ 7.70	100	54.0	31.5	41.5	0.0706	10.5	1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC 5V / 3A 9V / 2A 12V / 1.5A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A4YS			PD20W Single port (1C) (White)	Without Cable	¥ 7.60	200	55.0	54.0	37.0	0.1099	15.2	1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC 5V / 3A 9V / 1.22A 12V / 1.67A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A4YT			PD20W with cable Single port (1C) (White)	C-C	¥ 9.90	100	54.0	31.5	41.5	0.0706	10	1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC 5V / 3A 9V / 1.22A 12V / 1.67A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A4YL			PD20W with cable Single port (1C) (White)	C-IP	¥ 11.40	100	54.0	31.5	41.5	0.0706	10	1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC 5V / 3A 9V / 1.22A 12V / 1.67A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A5YS			PD20W USB-C+USB-A (White)	Without Cable	¥ 8.90	200	55.0	54.0	37.0	0.1099	15.5	1. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC 5V / 3A 9V / 1.22A 12V / 1.67A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS
A5YT			PD20W with cable USB-C+USB-A (White)	C-C	¥ 11.90	100	54.0	31.5	41.5	0.0706	10.08	1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC 5V / 3A 9V / 1.22A 12V / 1.67A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A5YL			PD20W with cable USB-C+USB-A (White)	C-IP	¥ 13.90	100	54.0	31.5	41.5	0.0706	10.08	1. Input:AC100-240V 50-60Hz 0.6A 2. Output: DC 5V / 3A 9V / 1.22A 12V / 1.67A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC

A8YS			PD20W Single port (1C) (White)	Without Cable	¥ 9.50	400/10	74.0	36.5	34.0	0.0918	37.9	1. Input:AC100-240V 50-60Hz 0.6A 2. Output: single USB-C DC5V/3A,9V/2.22A,12V/1.67A 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A8YT			PD20W Single port (1C) with cable (White)	C-C	¥ 12.50	200/10	63.0	37.0	43.5	0.1014	26.2	1. Input:AC100-240V 50-60Hz 0.6A 2. Output: single USB-C DC5V/3A,9V/2.22A,12V/1.67A 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 5.Line length: 1M
A8YL			PD20W Single port (1C) with cable (White)	C-IP	¥ 13.50	200/10	63.0	37.0	43.5	0.1014	26.2	1. Input:AC100-240V 50-60Hz 0.6A 2. Output: single USB-C DC5V/3A,9V/2.22A,12V/1.67A 3. Material:ABS 4. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 5.Line length: 1M
A9VV			3A with cable 2USB-A (White)	MICRO	¥ 6.90	100	54.0	31.5	41.5	0.0706	10.25	1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A9YT			3A with cable 2USB-A (White)	TYPE-C	¥ 7.60	100	54.0	31.5	41.5	0.0706	10.25	1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A9YL			3A with cable 2USB-A (White)	5G	¥ 7.70	100	54.0	31.5	41.5	0.0706	10.25	1. Input:AC100-240V 50-60Hz 0.35A 2. Output: DC 5V / 3A 3. Plug: Nickle plated EU plug, 24 Hours Salt -Fog Test 4. Material:ABS 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC
A11YS			PD25W Single port (1C) (Black)	Without Cable	¥ 12.00	200/10	72.0	38.5	25.5	0.0707		Input: AC 100V-240V 50HZ Output :(PDO)5V DC 3A or 9V DC 2.77A (PPS)3.3-5.9V DC 3A or 3.3-11V DC 2.25A
A11Y			PD25W with cable Single port (1C) (Black)	C-C	¥ 14.50	200/10	89.0	44.0	28.5	0.1116		Input: AC 100V-240V 50HZ Output :(PDO)5V DC 3A or 9V DC 2.77A (PPS)3.3-5.9V DC 3A or 3.3-11V DC 2.25A Line length: 1M
A12YS			PD45W Single port (1C) (Black)	Without Cable	¥ 22.00	200/10	72.0	38.5	25.5	0.0707		input: AC 100V-240V 50HZ Output: (PDO)5.0V DC 3A 15W or 9V DC 3A 27W or 15V DC 3A 45W or 20V DC 2.25A 45W(PPS)3.0-20V DC 2.25A(7.5-45W)
A12Y			PD45W with cable Single port (1C) (Black)	C-C	¥ 24.50	200/10	89.0	44.0	28.5	0.1116		Input:AC 100V-240V 50HZ Output: (PDO)5V DC 3A, 15W or 9V DC 3A, 27W or 15V DC 3A, 45W or 20V DC 2.25A 45W (PPS)3.0-20V DC 2.25A(7.5-45W) Line: length:1M
A16VV			PD15W with cable 2USB-A (White)	MICRO	¥ 4.90	200	54.0	31.5	41.5	0.0706	15.2	1. Input: AC 100V-240V 50/60HZ 0.35A 2. Output: DC 5V/3A 3. Material: ABS 4. Overcurrent and overvoltage protection of the circuit; Short circuit protection 5. Line leng: 1m
A16YT			PD15W with cable 2USB-A (White)	TYPE-C	¥ 5.20	200	54.0	31.5	41.5	0.0706	15.2	1. Input: AC 100V-240V 50/60HZ 0.35A 2. Output: DC 5V/3A 3. Material: ABS 4. Overcurrent and overvoltage protection of the circuit; Short circuit protection 5. Line leng: 1m

NEW			PD20W+QC3.0 USB-C+USB-A (White)	Without Cable	¥ 15.00	200	55.0	54.0	37.0	0.1099	23.65	Input:AC 100-240V,50-60Hz 0.35A Output:5V=3A 9V=2.2A 12V=1.67A USB Ports: USB-A+USB-C Working temperature:-10°C-50°C
NEW			3.4A 3USB-A (White)	Without Cable	¥ 7.50	100	54.0	31.5	41.5	0.0706	11.45	Input:AC 100-240V,50-60Hz 0.35A Output:DC 5V=3.4A Working temperature:-10°C-50°C
NEW			PD20W+QC3.0 USB-C+USB-A Green light (White)	Without Cable	¥ 17.50	200	55.0	54.0	37.0	0.1099	20.65	Input:AC 100-240V,50-60Hz 0.6A Output:USB-C: 5V=3A 9V=2.22A 12V=1.67A USB-A: 5V=3A 9V=2A 12V=1.5A USB-A+USB-C: 5V=3A (total) Working temperature:-10°C-50°C
NEW			PD27W Single port (1C) (White)	Without Cable	¥ 10.00	200	55.0	54.0	37.0	0.1099	10.9	Input:AC 100-240V,50-60Hz 0.7A Output:5V=3Aor9V=3Aor12V=2.25 (PPS) 3.3-5.9V=3Aor3.3-11.0V=2.45A
NEW			PD30W+QC3.0 USB-C+USB-A (White)	Without Cable	¥ 14.50	100	54.0	31.5	41.5	0.0706	12.65	Input:AC 100-240V,50-60Hz 0.6A Output: Type-c:5V=3A 9V=3A 12V=2.5A 15V=2A 20V=1.5A USB-A:5V=3A 9V=3A 12V=2.5A 20V=1.5A USB-A+Type-c:5V=3A
NEW			PD20W+QC3.0 USB-C+USB-A Green/Red light (White)	Without Cable	¥ 16.50	100	54.0	31.5	41.5	0.0706	10.3	USB+PD 20W fast charger At the same time, charging shows that the red light is 5V=3A. USB 18W fast charging shows Green light or PD 20W fast charging shows Green light
NEW			PD25W+3A USB-C+USB-A Green light (White)	Without Cable	¥ 15.50	100	54.0	31.5	41.5	0.0706	10.6	Input:AC 100-240V,50-60Hz 0.6A Output: Type-c:5V=3A 9V=2.22A 12V=1.67A USB-A:5V=3A 9V=3A 12V=2A 20V=1.5A USB-A+Type-c:5V=3A
NEW			PD67W+QC3.0 2USB-C+1USB-A Green light (Black)	Without Cable	¥ 52.00	100	54.0	31.5	41.5	0.0706		PD 65W fast charger ,support Samsung AFC, Huawei FCP, PD3.0, QC3.0 INPUT:AC 100-240V 50/60Hz 1.8A OUTPUT:USB-C1:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W USB-C2:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W
NEW			PD67W+QC3.0 2USB-C+1USB-A Green light (White)	Without Cable	¥ 52.00	100	54.0	31.5	41.0	0.0697		USB-A:4.5V=5A 5V=4.5A 9V=2A 12V=1.5A 10V=2.25A 22.5W USB-C1+USB-C2:45W+20W 65W USB-C1+USB-A:45W+20W 65W USB-C2+USB-A:20W MAX USB-C1+(USB-C2+USB-A):45W+20W 65W
NEW			18W/QC3.0 1USB-A (White)	Without Cable	¥ 8.00	200	55.0	54.0	37.0	0.1099	17.9	Input:100-240V,50/60Hz 0.5A Output:5V-3A/9V-2A/12V-1.5A Working temperature:-10°C-50°C QC 3.0 charger
NEW			18W/QC3.0 1USB-A Green light (White)	Without Cable	¥ 8.50	100	54.0	31.5	41.5	0.0706	10.1	Input:100-240V,50/60Hz 0.5A Output:5V-3A/9V-2A/12V-1.5A Working temperature:-10°C-50°C QC 3.0 charger
NEW			12W/2.4A 2USB-A (White)	Without Cable	¥ 8.00	100	40.5	30.0	44.0	0.0535	9.1	Input:100-240V,50/60Hz Output:5V-2.4A(MAX) Working temperature:-10°C-50°C

GA-19YS			QC3.0 2USB-A Green light (White)	Without Cable	¥ 7.00	100	54.0	31.5	41.5	0.0706	9.4	Input:AC100-240V,50/60Hz 0.35A Output:DC5V=3A
GA-33YS			12W/2.4A 2USB-A (White)	Without Cable	¥ 6.50	200	55.0	35.0	39.0	0.0751	13.7	Input:AC 100-240V,50-60Hz Output:DC 5V=2.4A Working temperature:-10°C-50°C
GA-37YS			PD20W/3A USB-C+USB-A (White)	Without Cable	¥ 17.00	100	55.0	34.0	50.0	0.0935	9.85	Input:AC 100-240V,50-60Hz 0.6A Output:USB-C: 5V=3A 9V=2.22A 12V=1.67A USB-A: 5V=3A 9V=2.0A 12V=1.5A USB-A+USB-C: 5V=3A (total)
GA-40YS			PD45W+QC3.0 2USB-C Green light (White)	Without Cable	¥ 38.00	100	54.0	31.5	41.5	0.0706	17.6	PD 45W fast charger Input:AC 100V-240V,50Hz 1.0A Output:C1or C2: 20V=2.25A or 12V=3A or 5V=3A or 3.3V-11V=3A Output:C1+ C2: 5V=3A or 12V=3A 3.3V-11V=3A
GA-41YS			PD25W+QC3.0 USB-C+USB-A (White)	Without Cable	¥ 14.00	100	54.0	31.5	41.5	0.0706	9.55	PD 25W fast charger Input:AC 100-240V,50-60Hz 0.7A Output:Type-C: 5V=3A 9V=2.77A (PPS)3.3-5.9V=3AAor3.3-11V=2.75V USB-A: 5V=3A 9V=2.77A Type-C+USB-A: 5V=3A (total)
GA-44YS			PD45W+QC3.0 2USB-C+1USB-A Green light (Black)	Without Cable	¥ 17.50	100	54.0	31.5	41.5	0.0706	16.4	PD 45W fast charger Input:AC 100V-240V,50Hz 1.0A Output:USB-C: 5V=3A 9V=3A 12V=3A 15V=3A 20V=2.25A PPS Output:USB-A: 5V=3A 9V=3A 12V=3A 15V=3A 20V=2.25A Output:USB-C+USB-A: 5V=3A
GA-25YP			PD20W+QC3.0 with cable USB-C+USB-A (White)	C-C C-IP	¥ 18.00 ¥ 20.00	100	55.0	34.0	50.0	0.0935	15.32	Input:AC 100-240V,50-60Hz 0.35A Output:5V=3A 9V=2.2A 12V=1.67A USB Ports: USB-A+USB-C Working temperature:-10°C-50°C
GA-27YP			PD20W+QC3.0 with cable USB-C+USB-A Green light (White)	C-C C-IP	¥ 21.00 ¥ 23.00	100	54.0	31.5	41.5	0.0706	13.75	Input:AC 100-240V,50/60Hz 0.35A Output:DC 5V=3A 9V=2.2A 12V=1.67A Working temperature:-10°C-50°C USB Ports: USB-A+USB-C Line length: 1M
GA-32YP			PD27W with cable Single port (1C) (White)	C-C C-IP	¥ 13.00 ¥ 15.00	100	55.0	34.0	50.0	0.0935	14.7	Input:AC 100-240V,50-60Hz 0.7A Output:5V=3Aor9V=3Aor12V=2.25 (PPS) 3.3- 5.9V=3AAor3.3-11.0V=2.45A Line length: 1M
GA-34YP			PD30W+QC3.0 with cable USB-C+USB-A (White)	C-C C-IP	¥ 18.00 ¥ 20.00	100	55.0	34.0	50.0	0.0935	15.3	Input:AC 100-240V,50-60Hz 0.6A Output: Type-c:5V=3A 9V=3A 12V=2.5A 15V=2A 20V=1.5A USB-A:5V=3A 9V=3A 12V=2.5A 20V=1.5A USB-A+Type-c:5V=3A
GA-36Y			PD25W+QC3.0 with cable USB-C+USB-A Green light (White)	C-C C-IP	¥ 19.00 ¥ 21.00	100	55.0	34.0	50.0	0.0935	13.55	Input:AC 100-240V,50-60Hz 0.6A Output: Type-c:5V=3A 9V=2.22A 12V=1.67A USB-A:5V=3A 9V=3A 12V=2A 20V=1.5A USB-A+Type-c:5V=3A
GA-37Y			PD20W+3A with cable USB-C+USB-A (White)	C-C C-IP	¥ 20.00 ¥ 22.00	100	55.0	34.0	50.0	0.0935	13.2	Input:AC 100-240V,50-60Hz 0.6A Output:USB-C: 5V=3A 9V=2.22A 12V=1.67A USB-A: 5V=3A 9V=2A 12V=1.5A USB-A+USB-C: 5V=3A (total)

NEW	GA-38Y			PD20W+QC3.0 with cable USB-C+USB-A Green/Red light (White)	C-C	¥ 19.50	100	55.0	34.0	50.0	0.0935	13.15	USB+PD 20W fast charger At the same time, charging shows that the red light is 5V=3A. USB 18W fast charging shows Green light or PD 20W fast charging shows Green light
					C-IP	¥ 21.50							
NEW	GA-40Y			PD45W+QC3.0 with cable 2USB-C Green light (White)	C-C	¥ 41.00	100	55.0	34.0	50.0	0.0935	20.45	PD 45W fast charger Input:AC 100V-240V,50Hz 1.0A Output:C1or C2: 20V=2.25A or 12V=3A or 5V=3A or 3.3V-11V=3A Output:C1+ C2: 5V=3A or 12V=3A 3.3V-11V=3A
					C-IP	¥ 43.00							
NEW	GA-41Y			PD25W+QC3.0 with cable USB-C+USB-A (White)	C-C	¥ 17.00	100	54.0	31.5	41.5	0.0706	11.82	PD 25W fast charger Input:AC 100-240V,50-60Hz 0.7A Output:Type-C: 5V=3A 9V=2.77A (PPS)3.3-5.9V=3AAor3.3-11V=2.75V USB-A: 5V=3A 9V=2.77A Type-C+USB-A: 5V=3A (total)
					C-IP	¥ 19.00							
NEW	GA-42Y			PD67W with cable 2USB-C+1USB-A Green light (Black)	C-C	¥ 56.00	100	50.0	34.5	49.0	0.0845		PD 65W fast charger ,support Samsung AFC, Huawei FCP , PD3.0, QC3.0 INPUT:AC 100-240V 50/60HZ 1.8A OUTPUT:USB-C1:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W USB-C2:5V=3A 9V=3A 12V=3A 15V=3A 20V=3.35A 67W USB-A:4.5V=5A 5V=4.5A 9V=2A 12V=1.5A 10V=2.25A 22.5W USB-C1+USB-C2:45W+20W 65W USB-C1+USB-A:45W+20W 65W USB-C2+USB-A:20W MAX USB-C1+(USB-C2+USB-A):45W+20W 65W Line length: 1000MM
NEW	GA-44Y			PD45W with cable USB-C+USB-A Green light (Black)	C-C	¥ 20.90	100	50.0	34.5	49.0	0.0845	19.3	Input:AC 100V-240V,50Hz 1.0A Output:USB-C: 5V=3A 9V=3A 12V=3A 15V=3A 20V=2.25A PPS Output:USB-A: 5V=3A 9V=3A 12V=3A 15V=3A 20V=2.25A Output:USB-C+USB-A: 5V=3A Line length: 1M
HOT	GA-01YF			18W/QC3.0 with cable 1USB-A (White)	MICRO	¥ 9.90	100	54.0	31.5	41.5	0.0706	13.76	Input:100-240V,50/60Hz 0.5A Output:5V-3A/9V-2A/12V-1.5A Working temperature: -10°C-50°C QC 3.0 charger Line length: 1M
					TYPE-C	¥ 10.40							
					5G	¥ 10.60							
NEW	GA-19YF			18W/QC3.0 with cable 1USB-A (White)	MICRO	¥ 10.50	100	54.0	31.5	41.5	0.0706	13.2	Input:100-240V,50/60Hz 0.5A Output:5V-3A/9V-2A/12V-1.5A Working temperature: -10°C-50°C QC 3.0 charger Line length: 1M
					TYPE-C	¥ 11.00							
					5G	¥ 11.20							
HOT	GA-26Y			3.4A with cable 3USB-A (White)	MICRO	¥ 9.00	100	54.0	31.5	41.5	0.0706	13.9	Input:AC 100-240V,50-60Hz 0.35A Output:DC 5V=3.4A Working temperature: -10°C-50°C Line length: 1M
					TYPE-C	¥ 9.50							
					5G	¥ 9.70							
HOT	GA-01Y			2.4A with cable 2USB-A (White)	MICRO	¥ 9.50	100	54.0	31.5	41.5	0.0706	12.32	Input:100-240V,50/60Hz Output:5V-2.4A(MAX) Working temperature: -10°C-50°C Line length: 1M
					TYPE-C	¥ 9.90							
					5G	¥ 10.30							
NEW	GA-19Y			3A with cable 2USB-A Green light (White)	MICRO	¥ 8.50	100	54.0	31.5	41.5	0.0706	11.9	Input:AC100-240V,50/60Hz 0.35A Output:DC5V=3A length: 1M
					TYPE-C	¥ 9.00							
					5G	¥ 9.20							
HOT	GA-22Y			2.4A with cable 2USB-A (White)	MICRO	¥ 9.90	100	54.0	31.5	41.5	0.0706	11.7	Input:AC100-240V,50/60Hz Output:DC5V=2.4A Working temperature: -10°C-50°C Line length: 1M
					TYPE-C	¥ 10.30							
					5G	¥ 10.70							
NEW	GA-27Y			3A with cable 2USB-A Green light (White)	MICRO	¥ 9.50	100	54.0	31.5	41.5	0.0706	10.6	Input:AC 100-240V,50-60Hz 0.35A Output:DC 5V=2.4A Working temperature: -10°C-50°C Line length: 1M
					TYPE-C	¥ 9.90							
					5G	¥ 10.30							

 GA-33Y			3A with cable 2USB-A (White)	MICRO	¥ 8.00	100	54.0	31.5	41.5	0.0706	10.45	Input:AC 100-240V,50-60Hz 0.6A Output:Type-C 5V=3A 9V=2.22A 12V=1.67A USB-A: 5V=3A 9V=2A 12V=1.5A Type-C+USB-A: =3A (Total) Line length: 1M
				TYPE-C	¥ 8.50							
				5G	¥ 8.70							























GERLAX®

















DATA CABLE




































ADD:New Asia International Digital City No, 55 Xiti Erma Road, Guangzhou





































Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

型号	产品图	产品图	卖点	类型	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情	
Model	Product Picture	Product Picture	SELLING POINTS	Type	Price rmb	OUTER CTN/ INNER	Carton size (CM)			CBM/CTN (m³)	KG/CTN	SPECIFICATIONS	
D2V			3A 1M	MICRO	¥1.5	500	64.0	37.0	44.0	0.1042	17.5	1.Model: D2V 2.Output: 5V=7A 3.Material: Nylon 4.Line length: 1000MM 5.Support charging and sync 6. Selling point: good quality at low price 7.Product color: white	
D2T			3A 1M	TYPE-C	¥1.8	500	64.0	37.0	44.0	0.1042	17.5	1.Model: D2T 2.Output: 5V=7A 3.Material: Nylon 4.Line length: 1000MM 5.Support charging and sync 6. Selling point: good quality at low price 7.Product color: white	
D2L			3A 1M	5G	¥2.1	500	64.0	37.0	44.0	0.1042	17.5	1.Model: D2L 2.Output: 5V=7A 3.Material: Nylon 4.Line length: 1000MM 5.Support charging and sync 6. Selling point: good quality at low price 7.Product color: white	
D3V			2.4A 1M	MICRO	¥0.95	500	47.5	39.8	27.0	0.0510	13	1. Size: 3.3x1000mm Weight: 20g 2. Connector Surface: PVC, two end injection molding 3. Maximum current: 2.4A 4. Support charging and sync 5. Connector: Two end cooper pin with gold plated, 24 Hours Salt - Fog Test 6. Selling point: good quality at low price 7.Product color: white	
D3T				TYPE-C	¥1.7	500							
D3L				5G	¥1.9	500							
D4T			PD60W 3A 1M	TYPE-C	¥2.7	400	50.0	42.0	34.0	0.0714	10.55		1. Size: 2.9x1000mm Weight: 14g 2. Connector Surface: TPE, Shell injection molding 3. Core wire: 100 Pure cooper wires 4. Maximum current: 3A 5. Support charging and sync 6. Connector: Two end cooper pin with gold plated, 24 Hours Salt -Fog Test 7. Selling point: good quality at low price 8.Product color: white 9.100 Pure cooper wires
D4L			PD20W 3A 1M	IOS	¥4.5	400	50.0	42.0	34.0	0.0714	10.55		1. Size: 2.9x1000mm Weight: 13.6g 2. Connector Surface: TPE, Shell injection molding 3. Core wire: 100 Pure cooper wires 4. Maximum current: 3A 5. Support charging and sync 6. Connector: Two end cooper pin with gold plated, 24 Hours Salt -Fog Test 7. Selling point: good quality at low price 8.Product color: white 9.Pack color: yellow 10.100 Pure cooper wires
D5G			3A 1.25M	3IN1	¥3.3	500	64.0	37.0	44.0	0.1042	24.75		1. Size: 3x1250mm Weight: 33.8g 2. Connector: Surface: TPE, Shell injection molding 3. Core wire: 100 Pure cooper wires 4. Maximum current: 3A 5. Support charging and sync 6. Connector: Two end cooper pin with gold plated, 24 Hours Salt -Fog Test 7. Selling point: good quality at low price 8.Product color: white 9.Pack color: green 10.100 Pure cooper wires
D7V			5A 1M (Black, White, Yellow, Red)	MICRO	¥2.4	500/10	64.0	37.0	44.0	0.1042	18.6		1. Cable length: 1M 2. Wire diameter: outer diameter 4.0mm 3. Connector surface: Silicone data cable 4. Maximum current: 5A 5. Supportsfast charging and data transmission
D7T			5A 1M (Black, White, Yellow, Red)	TYPE-C	¥2.7	500/10	64.0	37.0	44.0	0.1042	18.6	1. Cable length: 1M 2. Wire diameter: outer diameter 4.0mm 3. Connector surface: Silicone data cable 4. Maximum current: 5A 5. Supportsfast charging and data transmission	
D7L			5A 1M (Black, White, Yellow, Red)	5G	¥2.9	500/10	64.0	37.0	44.0	0.1042	18.6	1. Cable length: 1M 2. Wire diameter: outer diameter 4.0mm 3. Connector surface: Silicone data cable 4. Maximum current: 5A 5. Supportsfast charging and data transmission	
D8T			PD60W 1M	C-C	¥3.1	400	44.5	36.5	36.5	0.0593	10.85	1. Size:2.9x1000mm Weight: 14g 2. Connector Surface: TPE, Shell injection molding 3. Core wire: 100 Pure cooper wires 4. Maximum current: 3A 5. Support charging and sync 6. Connector: Two end cooper pin with gold plated, 24 Hours Salt -Fog Test 7. Selling point: good quality at low price 8.Product color: white 9.Pack color: white 10.100 Pure cooper wires	



























D8L			PD20W 1M	C-IP	¥4.6	400	44.5	36.5	36.5	0.0593	10.85	<ol style="list-style-type: none"> Size:2.9x1000mm Weight: 14g Connector Surface: TPE, Shell injection molding Core wire: 100 Pure cooper wires Maximum current: 3A Support charging and sync Connector: Two end cooper pin with gold plated, 24 Hours Salt -Fog Test Selling point: good quality at low price Product color: white Pack color: white 100 Pure cooper wires
D22T			PD60W 1M	C-C	¥3.5	500/10	64.0	37.0	44.0	0.1042	10.85	<ol style="list-style-type: none"> Cable length :1M Wire diameter: Outer diameter 4.0mm Connector surface :16 braided wire Metal: Aluminum alloy Maximum current: :5A Support charging and data transmission, PD60W Product color: black Selling point: good quality at low price , braided data cable is flexible and durable
D22L			PD30W 1M	C-IP	¥4.5	500/10	64.0	37.0	44.0	0.1042	10.85	<ol style="list-style-type: none"> Cable length :1M Wire diameter: Outer diameter 4.0mm Connector surface :16 braided wire Metal: Aluminum alloy Maximum current: :5A Support charging and data transmission, PD30W Product color: black Selling point: good quality at low price , braided data cable is flexible and durable
D23T			PD60W 1M	C-C	¥3.8	500/10	64.0	37.0	44.0	0.1042	10.85	<ol style="list-style-type: none"> Cable length: 1M Wire diameter: Outer diameter 4.0mm Connector surface: silicone data cable Maximum current: 60W Support Xiaomi ultra-fast charging and data transmission Product color: white Selling point: good quality at low price, silicone data cable is soft and not knotted, durable and safe, fire and frost proof
D23L			PD60W 1M	C-IP	¥4.8	500/10	64.0	37.0	44.0	0.1042	10.85	<ol style="list-style-type: none"> Cable length: 1M Wire diameter: Outer diameter 4.0mm Connector surface: silicone data cable Maximum current: 30W Support charging and data transmission Product color: white Selling point: good quality at low price, silicone data cable is soft and not knotted, durable and safe, fire and frost proof
D13V			9A/QC3.0	MICRO	¥2.2	400/50	58.0	29.5	22.0	0.0376	11.7	The USB 2.0 data cable can transfer speeds up to 480Mbps, while USB 3.0 can transfer speeds up to 5Gbps. And with the emergence of USB 3.1 and USB 3.2, their transmission speeds are even higher, reaching up to 20Gbps. OD4.0 wire: Liquid silicone material with a length of 1M..Selling point: good quality at low price , silicone data cable is soft and not knotted, durable and safe, fire and frost proof
D13T			9A/QC3.0	TYPE-C	¥2.5	400/50						
D13L			9A/QC3.0	5G	¥2.7	400/50						
D13V			9A/QC3.0	MICRO	¥2.2	400/50	58.0	29.5	22.0	0.0376	11.7	The USB 2.0 data cable can transfer speeds up to 480Mbps, while USB 3.0 can transfer speeds up to 5Gbps. And with the emergence of USB 3.1 and USB 3.2, their transmission speeds are even higher, reaching up to 20Gbps. OD4.0 wire: Liquid silicone material with a length of 1M. Selling point: good quality at low price , silicone data cable is soft and not knotted, durable and safe, fire and frost proof
D13T			9A/QC3.0	TYPE-C	¥2.5	400/50						
D13L			9A/QC3.0	5G	¥2.7	400/50						
D14V			9A/QC3.0	MICRO	¥1.1	400/50	57.0	29.5	21.5	0.0362		OD3.8, Fast Charging & Transmit Data Performance - Ensure a maximum charging speed up to 9A, Support Xiaomi top speed charging , Great performance ensures your devices syncs and charge simultaneously with up to 480Mb/s transferring speed.It has excellent bending resistance.Data cable length 1m, white, black two colors to choose from.
D14T			9A/QC3.0	TYPE-C	¥1.4	400/50						
D14L			9A/QC3.0	5G	¥1.6	400/50						
D15T			60W	TYPE-C	¥4.0	400/20	44.5	36.5	36.0	0.0585		Material : braided wire Line length: 1M Wire diameter:OD3.3mm Maximum current: 60W Fast Charging & Transmit Data Performance
D16V			9A 1M	MICRO	¥2.2	500/20	46.0	36.0	22.5	0.0373	12.75	<ol style="list-style-type: none"> Cable length :1M Wire diameter: Outer diameter 4.8mm Connector surface: foamed silicone wire Maximum current: 9A Support charging and data transmission Selling point:Foam silicone data cable is soft and not knotted, feel better, durable and safe, fire and frost proof
D16T			9A 1M	TYPE-C	¥2.6	500/20						<ol style="list-style-type: none"> Cable length :1M Wire diameter: Outer diameter 4.8mm Connector surface: foamed silicone wire Maximum current: 9A Support charging and data transmission, support Xiaomi speed charging Product color: black Selling point:Foam silicone data cable is soft and not knotted, feel better, durable and safe, fire and frost proof
D16L			9A 1M	5G	¥2.8	500/20						<ol style="list-style-type: none"> Cable length :1M Wire diameter: Outer diameter 4.8mm Connector surface: foamed silicone wire Maximum current: 9A Support charging and data transmission Selling point:Foam silicone data cable is soft and not knotted, feel better, durable and safe, fire and frost proof
D18V			5A 1M	MICRO	¥3.0	500/10	64.0	37.0	44.0	0.1042		<ol style="list-style-type: none"> Cable length: 1M Wire diameter: outer diameter 4.8mm Connector surface: Silicone cable Metal: Aluminum alloy Maximum current: 5A Supports charging and data transfer, supports Xiaomi fast charging Product color: White Selling point: good quality at low price , silicone data cable is soft and not knotted, durable and safe, fire and frost proof



























D18T			5A 1M	TYPE-C	¥3.5	500/10	64.0	37.0	44.0	0.1042	<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 4.8mm 3. Connector surface: Silicone cable 4. Metal: Aluminum alloy 5. Maximum current: 5A 6. Supports charging and data transfer, supports Xiaomi's high-speed charging 7. Product color: White 8. Selling point: good quality at low price, silicone data cable is soft and not knotted, durable and safe, fire and frost proof
D18L			5A 1M	5G	¥3.7	500/10	64.0	37.0	44.0	0.1042	<ul style="list-style-type: none"> 1. Cable length :1M 2. Wire diameter: Outer diameter 4.8mm 3. Connector surface: silicone cable 4. Metal: Aluminum alloy 5. Maximum current: 5A 6. Support charging and data transmission 7. Product color: white 8. Selling point: good quality at low price, silicone data cable is soft and not knotted, durable and safe, fire and frost proof
D19V			9A 1M	MICRO	¥1.4	500/10	64.0	37.0	44.0	0.1042	<ul style="list-style-type: none"> 1. Cable length :1M 2. Wire diameter: Outer diameter 3.8mm 3. Connector surface :PVC 4. Maximum current :9A 5. Support charging and data transmission 6. Product color: Black 7. Selling point: good quality at low price
D19T			9A 1M	TYPE-C	¥1.7	500/10					
D19L			9A 1M	5G	¥1.9	500/10					
D19V			9A 1M	MICRO	¥1.4	500/10	64.0	37.0	44.0	0.1042	<ul style="list-style-type: none"> 1. Cable length :1M 2. Wire diameter: Outer diameter 3.8mm 3. Connector surface :PVC 4. Maximum current :9A 5. Support charging and data transmission 6. Product color: White 7. Selling point: good quality at low price
D19T			9A 1M	TYPE-C	¥1.7	500/10					
D19L			9A 1M	5G	¥1.9	500/10					
D20V			5A 1M	MICRO	¥2.05	500/20					<ul style="list-style-type: none"> 1. Cable length :1M 2. Wire diameter: Outer diameter 4.0mm 3. Connector surface :48 fishing net braided wire 4. Maximum current: 5A 4. Support charging and data transmission 5. Product color: black 6. Selling point: good quality at low price, braided data cable is flexible and durable
D20T			5A 1M	TYPE-C	¥2.35	500/20					
D20L			5A 1M	5G	¥2.55	500/20					
D21V				MICRO	¥1.55	500/20					<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 3.8MM 3. Connector surface: silicone data cable 4. Maximum current: 5A 5. Support QC3.0 quick charge and data transmission 6. Product color: black/white
D21T				TYPE-C	¥1.85	500/20					<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 3.8MM 3. Connector surface: silicone data cable 4. Maximum current: 5A 5. Support Xiaomi ultra-fast charging, QC3.0 quick charge and data transmission 6. Product color: black/white
D21L				5G	¥2.05	500/20					<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 3.8MM 3. Connector surface: silicone data cable 4. Maximum current: 5A 5. Support charging and data transmission 6. Product color: black/white
D25V			5A 1M	MICRO	¥1.5	500/20					<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 4mm 3. Connector surface: TPE 4. Maximum current: 5A 5. Support QC3.0 fast charge charging, QC3.0 fast charging, and data transmission 6. Product color: black 7. Selling point: good quality at low price
D25T			5A 1M	TYPE-C	¥1.7	500/20					
D25L			5A 1M	5G	¥2.0	500/20					
D25V			5A 1M	MICRO	¥1.5	500/20					<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 4mm 3. Connector surface: TPE 4. Maximum current: 5A 5. Support QC3.0 fast charge charging, QC3.0 fast charging, and data transmission 6. Product color: White 7. Selling point: good quality at low price
D25T			5A 1M	TYPE-C	¥1.7	500/20					
D25L			5A 1M	5G	¥2.0	500/20					
TYPE-C to Lightning Cable, PD Cable											
GD-60T			1000MM 100W	C-C	¥9.9	200	47.5	37.5	47.5	0.0846	<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 4.0mm 3. Connector surface: 24 braided cotton yarn 4. Metal: Aluminum alloy 5. Maximum current: 100W 6. Support Xiaomi top speed charging, QC3.0 quick charge and data transfer 7. Selling point: With intelligent digital display, the charging power can be displayed in real time 8. Product color: black

	GD-60L			1000MM 100W	C-IP	¥10.9	200	47.5	37.5	47.5	0.0846		<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 4.0mm 3. Connector surface: 24 braided cotton yarn 4. Metal: Aluminum alloy 5. Maximum current: 30W 6. Supports charging and data transfer 7. Selling point: With intelligent digital display, the charging power can be displayed in real time 8. Product color: black
	L2T			1000mm 3A	C-C	¥6.5	200	46.5	36.5	46.0	0.0781	11.35	<ul style="list-style-type: none"> Output:3A Material:Silicone Selling point: there are four colors to choose from,silicone data cable is soft and not knotted, durable and safe, fire and frost proof
	L2L			1000mm 3A	C-IP	¥9.0	200	46.5	36.5	46.0	0.0781	11.35	<ul style="list-style-type: none"> Output:3A Material:Silicone Selling point: there are four colors to choose from,silicone data cable is soft and not knotted, durable and safe, fire and frost proof
	L9T			1000MM 3A	C-C	¥6.6	200	46.5	36.5	46.0	0.0781	13.2	<ul style="list-style-type: none"> Output:60W Material:Aluminium alloy Selling point: braided data cable is flexible and durable
	L9L			1000MM 3A	C-IP	¥8.6	200	46.5	36.5	46.0	0.0781	13.2	<ul style="list-style-type: none"> Output:30W Material:Aluminium alloy Selling point: braided data cable is flexible and durable
	L18T			1000MM 10A	C-C	¥5.5	200	46.5	36.5	46.0	0.0781	11.3	<ul style="list-style-type: none"> 100W FAST CHARGING: Ideal for charging and powering USB Type-C enabled devices (100W/20V/10A) as well as syncing data, photos and music transmission (up to 5Gbps data transfer speed); supports fast charging when used with Power Delivery (PD) chargers UNIVERSAL CONNECTOR: Reversible design—easily insert the Type-C connector into any Type-C enabled device (does not matter which side is up)
	L19T			1000MM 10A	C-C	¥5.5	200	46.5	36.5	46.0	0.0781	11.95	<ul style="list-style-type: none"> 100W FAST CHARGING: Ideal for charging and powering USB Type-C enabled devices (100W/20V/10A) as well as syncing data, photos and music transmission (up to 5Gbps data transfer speed); supports fast charging when used with Power Delivery (PD) chargers UNIVERSAL CONNECTOR: Reversible design—easily insert the Type-C connector into any Type-C enabled device (does not matter which side is up)
	L20T			1000MM 10A	C-C	¥14.0	200	46.5	36.5	46.0	0.0781	12.4	<ul style="list-style-type: none"> 100W USB C Super Fast Charging Cable: The LED-Display USB C to USB C fast charging cable support charging speeds up to PD 100W/10A with a maximum charging power. Which can charge most types of C devices including phones, tablets, computers, and more. full charge for MacBook Pro 13 in about 2.5h. LED Power Digital Display: The 100W USB C Cable with LED power display, Real-time fast charging power is displayed, with visual design, it charging power and monitors your device status in real-time.
	L20T2			2000MM 10A	C-C	¥17.0	200	57.0	31.5	44.5	0.0799	17.9	<ul style="list-style-type: none"> 100W USB C Super Fast Charging Cable: The LED-Display USB C to USB C fast charging cable support charging speeds up to PD 100W/10A with a maximum charging power. Which can charge most types of C devices including phones, tablets, computers, and more. full charge for MacBook Pro 13 in about 2.5h. LED Power Digital Display: The 100W USB C Cable with LED power display, Real-time fast charging power is displayed, with visual design, it charging power and monitors your device status in real-time. The 6.6ft/2m long USB C charging cable is ideal for long-distance usage at home, in your office, car, on your travel, and more place
	L22T			1000MM 6A	C-C	¥5.0	200	46.5	36.5	46.0	0.0781	11.3	<ul style="list-style-type: none"> This type c to lightning cable cable can charge iPhone 14 Pro from 0% to 58% in just 30min, Supports PD Fast Charge 6A/30W(max) and 480 Mbps high data transmission which can greatly saving your time. (Note:You need to use 20W or above USB-C Power Adapter to achieve fast charge) Models that support pd fast charging include Full Series iPhone and other latest models.
	L22L			1000MM 6A	C-IP	¥6.5							
	L29T			1000MM 10A	C-C	¥17.5	200	46.5	36.5	46.0	0.0781	13.6	<ul style="list-style-type: none"> Transparent warehouse, interior technology sense: Mcdodo USB C to USB C Charger Cable interface transparent shell package, neat and orderly arrangement of components, real-time display of charging power, charging speed can be seen at a glance, real-time view your notebook/l pad/Phone Fast charging in progress. 100W high-speed charging: It has technology and good looks, say goodbye to low-speed charging.Compatible with all Type-C devices.Supports PD100W (Max.), suitable for fast charging of Type-C interface devices such as notebooks/tablets/Switches/mobile phones (please note whether your device supports 100W power) Equipped with high-end chips: Built-in E-marker chip, equipped with MSC technology independently developed by Macdodo, automatically identifies equipment matching current, and corresponds to different brands or reasonable control voltage for tablets, notebooks, mobile phones, etc. Intelligent power-off when fully charged, automatically detects battery power and replenishes the battery periodically, reducing battery loss and protecting the battery to extend its service life.
	L29L			1000MM 10A	C-IP	¥19.0	200	46.5	36.5	46.0	0.0781	13.6	<ul style="list-style-type: none"> Equipped with high-end chips: Built-in E-marker chip, equipped with MSC technology independently developed by Macdodo, automatically identifies equipment matching current, and corresponds to different brands or reasonable control voltage for tablets, notebooks, mobile phones, etc. Intelligent power-off when fully charged, automatically detects battery power and replenishes the battery periodically, reducing battery loss and protecting the battery to extend its service life.








































	L31			1000MM 60W	C-C	¥6.0	200	46.5	36.5	46.0	0.0781	9.75	Output:60W Material:Woven fabric Selling point: braided data cable is flexible and durable, compatible with Apple 15/16 charging
	L34T			300MM 3A	C-C	¥2.7	500	63.0	36.0	42.5	0.0964	12.3	Output:6A Material:TPE Selling point: 30cm data cable, easy to carry, no space
	L34L			300MM 3A	C-IP	¥5.2	500	63.0	36.0	42.5	0.0964	12.3	Output:6A Material:TPE Selling point: 30cm data cable, easy to carry, no space
	L35T			1000MM 60W	C-C	¥6.5	200	46.5	36.5	46.0	0.0781	12.35	Output:60W Material:Nylon Braided Line length: 1M Selling point: braided data cable is flexible and durable
	L35L			1000MM 30W	C-IP	¥8.0	200	46.5	36.5	46.0	0.0781	12.35	Output:30W Material:Nylon Braided Line length: 1M Selling point: braided data cable is flexible and durable
	L39T			1000MM 60W	C-C	¥7.0	200	46.5	36.5	46.0	0.0781	11.7	Output:60W Material:Nylon Braided Line length: 1M Selling point: With intelligent digital display, the charging power can be displayed in real time
	L39L			1000MM 30W	C-IP	¥10.0	200	46.5	36.5	46.0	0.0781	11.7	Output:30W Material:Nylon Braided Line length: 1M Selling point: With intelligent digital display, the charging power can be displayed in real time
	L37			1500MM 150W	2IN1	¥17.5	200	52.5	35.0	61.0	0.1121	25.20	Output:150W/15A Material:Nylon diameter: OD5.0mm Selling point:High power data cable, 2-in-1 data cable, there are two interfaces can be used for different mobile phones
	L40T			1500MM 60W	C-C	¥9.0	200	46.5	36.5	46.0	0.0781	14.35	A soft silicone data cable, safe material. Fire and frost proof. 60W high-speed charging: say goodbye to low-speed charging, which can support PD fast charging and fast data transmission performance. Data cable length 1.5m, white, blue, green three colors to choose from.
	L40L			1500MM 30W	C-IP	¥10.5	200	46.5	36.5	46.0	0.0781	14.35	
	L41T			1000MM 240W	C-C	¥9.0	200	46.5	36.5	46.0	0.0781		Output:240W Material: Aluminum alloy braided wire Line length: 1M
Aluminum alloy													
	GD-54V3			3000MM 6A	MICRO	¥9.9	200	53.6	36.0	62.5	0.1206	25.50	Output:6A Material:Nylon Selling point: Braided wire soft and durable, 3 meters long data cable

























		3000MM 6A	TYPE-C	¥10.5	200	53.6	36.0	62.5	0.1206	25.50	Output:6A Material:Nylon Selling point:Braided wire soft and durable, 3 meters long data cable
		3000MM 6A	5G	¥10.7	200	53.6	36.0	62.5	0.1206	25.50	Output:6A Material:Nylon Selling point:Braided wire soft and durable, 3 meters long data cable
		2000MM 6A	MICRO	¥6.9	200	47.5	37.5	57.5	0.1024	18.00	Output:6A Material:Nylon Selling point:Braided wire soft and durable, 2 meters long data cable
		2000MM 6A	TYPE-C	¥7.5	200	47.5	37.5	57.5	0.1024	18.00	Output:6A Material:Nylon Selling point:Braided wire soft and durable, 2 meters long data cable
		2000MM 6A	5G	¥7.7	200	47.5	37.5	57.5	0.1024	18.00	Output:6A Material:Nylon Selling point:Braided wire soft and durable, 2 meters long data cable
		1000mm 6A	MICRO	¥4.5	200	47.5	37.5	47.5	0.0846	12.6	Output:6A Material:Nylon Selling point:Braided wire is soft, tough and durable
		1000mm 6A	TYPE-C	¥5.1							Huawei Super Fast Charger Output:6A Material:Nylon Selling point:Braided wire is soft, tough and durable
		1000mm 6A	TYPE-C	¥5.1							MI Turbo Charger Output:6A Material:Nylon Selling point:Braided wire is soft, tough and durable
		1000mm 6A	5G	¥5.3							Output:6A Material:Nylon Selling point:Braided wire is soft, tough and durable
		5000mm 6A	TYPE-C	¥22.5	80	81.5	41.5	37.0	0.1251	22.3	Output:6A Material:Nylon Selling point:Braided wire soft and durable, 5 meters long data cable
		5000mm 6A	5G	¥22.8	80	81.5	41.5	37.0	0.1251	22.3	Output:6A Material:Nylon Selling point:Braided wire soft and durable, 5 meters long data cable
		1000mm 9A	MICRO	¥3.7	200	47.5	37.5	47.5	0.0846		1. Line length: 1M 2.Wire diameter:OD 4.0mm 2. Connector Surface: 48 Cich woven Wire 4. Maximum current: 9A 5. Support charging and data transmission 8.Product color: balck 9.Selling point:Braided wire soft and durable,high-end aluminum alloy oxidation process
		1000mm 9A	TYPE-C	¥4.1	200	47.5	37.5	47.5	0.0846		1. Line length: 1M 2.Wire diameter:OD 4.0mm 2. Connector Surface: 48 Cich woven Wire 4. Maximum current: 9A 5. Support charging and data transmission, Support Xiaomi's high-speed charging 8.Product color: blue 9.Selling point:Braided wire soft and durable,high-end aluminum alloy oxidation process

GD-56L			1000mm 9A	5G	¥4.3	200	47.5	37.5	47.5	0.0846		<ul style="list-style-type: none"> 1. Line length: 1M 2. Wire diameter: OD 4.0mm 3. Connector Surface: 48 C10th woven Wre 4. Maximum current: 9A 5. Support charging and data transmission 6. Product color: purple 7. Selling point: Braided wire soft and durable, high-end aluminum alloy oxidation process
GD-58V			1000mm 9A	MICRO	¥3.9	200	47.5	37.5	47.5	0.0846	12	<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 4.0mm 3. Connector surface: 48 braided wire, horizontal stripe braided 4. Metal: Aluminum alloy 5. Maximum current: 9A 6. Supports Xiaomi fast charging, QC3.0 fast charging, and data transmission 7. Product color: Grey 8. Selling point: Braided wire soft and durable, high-end aluminum alloy oxidation process
GD-58T			1000mm 9A	TYPE-C	¥4.3	200	47.5	37.5	47.5	0.0846	12.2	<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 4.0mm 3. Connector surface: 48 braided wire, horizontal stripe braided 4. Metal: Aluminum alloy 5. Maximum current: 9A 6. Supports Xiaomi's fast charging, QC3.0 fast charging, and data transmission 7. Product color: Grey 8. Selling point: Braided wire soft and durable, high-end aluminum alloy oxidation process
GD-58L			1000mm 9A	5G	¥4.5	200	47.5	37.5	47.5	0.0846	12	<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 4.0mm 3. Connector surface: 48 braided wire woven with horizontal stripes 4. Metal: Aluminum alloy 5. Maximum current: 9A 6. Supports charging and data transfer 7. Product color: Grey 8. Selling point: Braided wire soft and durable, high-end aluminum alloy oxidation process
GD-59T			1000MM 66W	TYPE-C	¥8.8	200	47.5	37.5	47.5	0.0846		<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 4.0mm 3. Connector surface: 24 braided cotton yarn 4. Metal: Aluminum alloy 5. Maximum current: 66W 6. Support Xiaomi top speed charging, QC3.0 quick charge and data transfer 7. Selling point: With intelligent digital display, the charging power can be displayed in real time 8. Product color: black
GD-59L			1000MM 66W	5G	¥9.3	200	47.5	37.5	47.5	0.0846		<ul style="list-style-type: none"> 1. Cable length: 1M 2. Wire diameter: outer diameter 4.0mm 3. Connector surface: 24 braided cotton yarn 4. Metal: Aluminum alloy 5. Maximum current: 30W 6. Supports charging and data transfer 7. Selling point: With intelligent digital display, the charging power can be displayed in real time 8. Product color: black
L1VY			1000mm 3A	MICRO	¥3.4	200/5	47.0	29.5	52.0	0.0721	8.9	<ul style="list-style-type: none"> Output: 3A (MAX) Material: Silicone Selling point: there are four colors to choose from, silicone data cable is soft and not knotted, durable and safe, fire and frost proof
L1VW												
L1VB												
L1VR												
L1TY			1000mm 3A	TYPE-C	¥3.9	200/5	47.0	29.5	52.0	0.0721	8.9	<ul style="list-style-type: none"> Output: 3A (MAX) Material: Silicone Selling point: there are four colors to choose from, silicone data cable is soft and not knotted, durable and safe, fire and frost proof
L1TW												
L1TB												
L1TR												
L1LY			1000mm 3A	5G	¥4.2	200/5	47.0	29.5	52.0	0.0721	8.9	<ul style="list-style-type: none"> Output: 3A (MAX) Material: Silicone Selling point: there are four colors to choose from, silicone data cable is soft and not knotted, durable and safe, fire and frost proof
L1LW												
L1LB												
L1LR												
L3			1000MM 6A	MICRO	¥5.0	200	63.0	36.0	47.5	0.1077	15.9	<ul style="list-style-type: none"> Output: 6A Material: TPE Selling point: OD6.0 thick data cable, strong and durable
				TYPE-C	¥5.6							
				5G	¥5.8							
L5V			1000MM 6A	MICRO	¥3.5	200	47.5	37.5	47.5	0.0846	11.8	<ul style="list-style-type: none"> Output: 6A Material: Aluminium alloy Braided wire is strong and durable, resistant to bending
L5T			1000MM 6A	TYPE-C	¥4.1	200	47.5	37.5	47.5	0.0846	11.8	<ul style="list-style-type: none"> Output: 6A Material: Aluminium alloy Braided wire is strong and durable, resistant to bending
L6V			1000MM 6A	MICRO	¥3.3	200	47.5	37.5	47.5	0.0846	11.8	<ul style="list-style-type: none"> Output: 6A Material: Aluminium alloy Braided wire is strong and durable, resistant to bending

L6T			1000MM 6A	TYPE-C	¥3.9	200	47.5	37.5	47.5	0.0846	11.8	Output:6A Material:Aluminium alloy Braided wire is strong and durable, resistant to bending
L6L			1000MM 6A	5G	¥4.1	200	47.5	37.5	47.5	0.0846	11.8	Output:6A Material:Aluminium alloy Braided wire is strong and durable, resistant to bending
L7V			1000MM 6A	MICRO	¥3.7	200	47.5	37.5	47.5	0.0846	11.8	Output:6A Material:Aluminium alloy Braided wire is strong and durable, resistant to bending
L7T			1000MM 6A	TYPE-C	¥4.3	200	47.5	37.5	47.5	0.0846	11.8	Output:6A Material:Aluminium alloy Braided wire is strong and durable, resistant to bending
L7L			1000MM 6A	5G	¥4.5	200	47.5	37.5	47.5	0.0846	11.8	Output:6A Material:Aluminium alloy Braided wire is strong and durable, resistant to bending
L10			1000MM 6A	MICRO	¥3.5	200	47.5	37.5	47.5	0.0846	11.9	Output:6A Material:Aluminium alloy + Nylon Braided Fast charging,Support QC3.0/Mi turbo Charge Charge your device with6A fast charge technology, built-in 56KΩ resistor incredible safety, protect your devices and charging adapters from damage.
				TYPE-C	¥4.1							
L12			1000MM 6A	MICRO	¥2.5	500/10	64.0	37.0	44.0	0.1042	19.6	Output: 6A Incredible Charging Speed: Wide-diameter wires and reduced cord resistance maximize charging speed. Secure Fit: Sturdy unibody connectors resist damage while ensuring a secure fit with every insertion
				TYPE-C	¥3.0							
				5G	¥3.3							
L13V			1000MM 6A	MICRO	¥3.3	200	47.5	37.5	47.5	0.0846	12.15	
L13T			1000MM 6A	TYPE-C	¥3.9	200	47.5	37.5	47.5	0.0846	12.15	Output:6A Material:Aluminium alloy + Nylon Braided Fast charging,Support QC3.0/Mi turbo Charge Long SR design to protect your wire will no break Strong military fiber can be use for long time. The most flexible, powerful and durable braided material, makes tensile force increased by 200%. Special Strain Relief design, can bear more bending test.
L13L			1000MM 6A	5G	¥4.1	200	47.5	37.5	47.5	0.0846	12.15	
L14V			1000MM 6A	MICRO	¥3.7	200	47.5	37.5	47.5	0.0846	12.2	
L14T			1000MM 6A	TYPE-C	¥4.3	200	47.5	37.5	47.5	0.0846	12.2	Output:6A Material:Aluminium alloy+Nylon braided Longer SR,DURABLE & Flexible: The nylon USB braided quick charge cable ensures excellent anti-twist and abrasion resistance properties Aluminum alloy shell by micro-arc oxidation process makes the shell surface harder and more wearable. Nylon braided with a tested more bend lifespan
L14L			1000MM 6A	5G	¥4.5	200	47.5	37.5	47.5	0.0846	12.2	

L15L			1000MM 6A	5G	¥6.0	200	47.5	37.5	47.5	0.0846	11.9	
L16			1000MM 6A	MICRO	¥3.9	200	47.5	37.5	47.5	0.0846	11.3	Output: 6A Smart LED indicator & Safe Charge, With a fashionable appearance and a nice green LED light, stays solid green while charging, helps fast finding your device in the dark. Built-in smart chips monitoring the charging power and adjusting current and voltage automatically, avoiding damage to the battery in case of unstable current.
				TYPE-C	¥4.4							
				5G	¥4.7							
L17			1000MM 6A	MICRO	¥2.9	500/10	64.0	37.0	44.0	0.1042	23.9	Output: 6A Durability design, Flexible iPhone charging cords have high-quality double Nylon braided jacket and core material, can withstand a variety of everyday connection needs and long-term use. Extreme Durability & Reliable, The cable contains three protective layers. The solid and durable two-shade braided nylon shield gives the cable stronger protection and flexible performance than others and no need to worry about tangling, no more cable breakage worries, and nylon cable will not be over-heat.
				TYPE-C	¥3.4							
				5G	¥3.7							
L23			1000MM 6A	MICRO	¥2.9	500/10	64.0	37.0	44.0	0.1042	20.6	Extra strength nylon double-braided jacket protects your cable and keeps it tangle-free. No more untangling your cables! Top quality molded joint plugs and metal alloy connectors are extremely durable and look great. These cables are produced to spec according to USB-C standards and are equipped with 56kΩ pull-up resistors to ensure a safe charging experience for your device
				TYPE-C	¥3.4							
				5G	¥3.7							
L24V			1000MM 6A	MICRO	¥2.3	500	64.0	37.0	44.0	0.1042	21	
L24T			1000MM 6A	TYPE-C	¥2.8	500	64.0	37.0	44.0	0.1042	21	Durable and Tangle-free Android Charger - Covered with braided-nylon fiber jacket which makes the cable durable and sturdier than normal micro usb charging cable but also flexible, tangle-free. Fast Charging & Transmit Data Performance - Ensure a maximum charging speed up to 6A, charge faster than most android phone charger cord and work better for tablets and quick charge devices. Great performance ensures your devices syncs and charge simultaneously with up to 480Mb/s transferring speed.
L24L			1000MM 6A	5G	¥3.1	500	64.0	37.0	44.0	0.1042	21	
L25			300MM 6A	MICRO	¥1.9	500	64.0	37.0	44.0	0.1042	13.3	Output: 6A Material: TPE Line length: 30CM Selling point: 30cm data cable, easy to carry, no space
				TYPE-C	¥2.2							
				5G	¥2.5							
L26T			1000MM 6A	TYPE-C	¥3.6	500	64.0	37.0	44.0	0.1042	18.85	Output: 6A Material: silica gel Silicone wire soft feel good, safe and anti-freeze fire. There are three colors to choose from
L26L			1000MM 6A	5G	¥3.9	500	64.0	37.0	44.0	0.1042	18.85	Output: 6A Material: silica gel Silicone wire soft feel good, safe and anti-freeze fire. There are three colors to choose from
L27			1000MM 6A	MICRO	¥2.5	500	64.0	37.0	44.0	0.1042	20	Output: 6A Material: TPE
				TYPE-C	¥3.0							
				5G	¥3.3							

	L28V			1000MM 7A	MICRO	¥3.3	500	64.0	37.0	44.0	0.1042	24	Support 7A Super Fast Charging And Data Transfer. Reversible Type-C Cable: Super Charging And Hi-speed Data Sync,faster,safer And Stronger. Comfortable&Durable:With A Comfortable Hand-feeling And The Cable Is Flexible And Durable. Fast Charging:7A Current Output,also Compatible With Other Pad/smart Phone/power Bank And Other With Type C Device.
	L28T			1000MM 7A	TYPE-C	¥3.8	500	64.0	37.0	44.0	0.1042	24	
	L28L			1000MM 7A	5G	¥4.1	500	64.0	37.0	44.0	0.1042	24	
	L30V			1000MM 7A	MICRO	¥3.5	200	47.5	37.5	47.5	0.0846	14.8	Output:7A Material:NYLON Selling point: Nylon braided wire is strong and durable.Aluminum casing makes the USB A to USB C Cable non-oxidizing, non-rusting, and has a long lifespan.
	L30T			1000MM 7A	TYPE-C	¥4.1	200	47.5	37.5	47.5	0.0846	14.8	Output:7A Material:NYLON Selling point: Nylon braided wire is strong and durable.Aluminum casing makes the USB A to USB C Cable non-oxidizing, non-rusting, and has a long lifespan.
	L30L			1000MM 7A	5G	¥4.3	200	47.5	37.5	47.5	0.0846	14.8	Output:7A Material:NYLON Selling point: Nylon braided wire is strong and durable.Aluminum casing makes the USB A to USB C Cable non-oxidizing, non-rusting, and has a long lifespan.
	L32V			1000MM 7A	MICRO	¥3.5	200	47.0	29.0	52.0	0.0709	13.6	7A Fast ChargeAbsolutely sturdy and durable USB Type C Cable can fully withstand daily wear and tear, and the phone cable will never break. Aluminum casing makes the USB A to USB C Cable non-oxidizing, non-rusting, and has a long lifespan.
	L32T			1000MM 7A	TYPE-C	¥4.0	200	47.0	29.0	52.0	0.0709	13.6	
	L32L			1000MM 7A	5G	¥4.3	200	47.0	29.0	52.0	0.0709	13.6	
	L33V			1000MM 6A	MICRO	¥4.5	200	47.5	37.5	47.5	0.0846	12.1	QC3.0 FAST CHARGING & DATA-SYNC: The USB A to USB C Cable Supports safe high-speed charging6A and data syncing speed up to (480Mb/s). 56kΩ resistor provide outstandingly reliable conductivity &stability and protect your devices and charging adapters from damage. DURABLE & HEAVY DUTY:Integral Seamless stretch process, high pressure resistance. Aluminum alloy shell by micro-arc oxidation process makes the shell surface harder and more wearable
	L33T			1000MM 6A	TYPE-C	¥5.0	200	47.5	37.5	47.5	0.0846	12.1	
	L33L			1000MM 6A	5G	¥5.3	200	47.5	37.5	47.5	0.0846	12.1	
	L36V			1000MM 120W 8A	MICRO	¥2.5	500	64.0	37.0	44.0	0.1042	20.55	Output:120W/8A Material:Nylon Aluminum alloy shell by micro-arc oxidation process makes the shell surface harder and more wearable










			1000MM 120W 8A	TYPE-C	¥2.9	500	64.0	37.0	44.0	0.1042	20.55	Output:120W/8A Material:Nylon Aluminum alloy shell by micro-arc oxidation process makes the shell surface harder and more wearable
			1000MM 120W 8A	5G	¥3.3	500	64.0	37.0	44.0	0.1042	20.55	Output:120W/8A Material:Nylon Aluminum alloy shell by micro-arc oxidation process makes the shell surface harder and more wearable
			2000MM 2.4A	5G	¥5.8	200	47.0	29.5	52.0	0.0721	15.45	Output:2.4A(MAX) Material:TPE
NEW			1000mm 2.4A	MICRO	¥2.5	400/10	50.0	42.0	34.0	0.0714	13.77	Output:2.1A(MAX) Material:PVC
GD-11T				TYPE-C	¥3.0							
GD-11L				5G	¥3.3							
			1000mm 2.4A	5G	¥2.5	500/10	56.0	32.0	49.0	0.0878	18	Output:2.4A(MAX) Material:PVC
NEW			1200MM 6A	3IN1	¥5.8	500	64.0	37.0	44.0	0.1042	24.40	【3 in 1 Super Fast Charging Cable】 One cable can satisfy multiple charging demands for you. Offers USB C, Micro USB, and Phone Port to replace a whole mess of cables. Used with wall charger, power bank, car charger, etc. which offers you total 6A charging speed,ideal for charging share of different devices with others when car driving, business trip, office working, travel.
NEW			1200MM 6A	3IN1	¥5.8	500	64.0	37.0	44.0	0.1042	24.40	
			1200MM 6A	3IN1	¥5.8	500	64.0	37.0	44.0	0.1042	24.40	
			1000mm 7A	2IN1	¥4.8	200	47.5	37.5	47.5	0.0846	10.60	
			1000mm 7A	2IN1	¥4.8	200	47.5	37.5	47.5	0.0846	10.60	Output:7A(MAX) Material:TPE Line Length: 1M
NEW			1200mm 120W	3IN1	¥5.5	200	47.5	37.5	47.5	0.0846		1. Line length: 1.2M 2. Wire diameter: outer diameter 3.8mm 3. Connector surface: TPE 4. Supports charging and data transmission, with three interfaces for convenient charging. TC supports Xiaomi's high-speed charging and also supports Apple 15 charging 5. Product color: White
NEW			1500mm 120W	3IN1	¥8.5	200	47.5	37.5	47.5	0.0846		1. Cable length: 1.5M 2. Wire diameter: Outer diameter 4.0mm 3. Connector surface: silicone data cable 4. Maximum current: 5A 5.Support QC3.0 fast charge & Xiaomi support ultra-fast charging&Support Huawei fast charging& data transfer 6. Product color: white 7.Selling point: silicone data cable is soft and not knotted, durable and safe, fire and frost proof.Can support multiple mobile phone charging at the same time

GERLAX®

AUDIO CABLE

ADD:New Asia International Digital City No, 55 Xiti Erma Rosd, Guangzhou

Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

型号	产品图	类型	价格 rmb	数量/箱	箱规	立方数	重量/箱	详情
Model	Product Picture	Type	Price rmb	OUTER CTN/ INNER BOX	Carton size (CM)	CBM/CTN (m³)	KG/CTN	SPECIFICATIONS
X5B		DC (3.5mm)	¥0.9	500	47.5 39.8 27.0	0.0564	13.75	1.Length: 1m; 3.5mm TO 3.5mm 2.Material:PVC 3. Wire core: three-core oxygen-free copper core wire core gauge OD3.5, 16/0.08*3 4.Product color: black 5.Pack color: yellow
X5W		DC (3.5mm)	¥0.9	500	47.5 39.8 27.0	0.0564	13.75	1.Length: 1m; 3.5mm TO 3.5mm 2.Material:PVC 3. Wire core: three-core oxygen-free copper core wire core gauge OD3.5, 16/0.08*3 4.Product color: white 5.Pack color: green
GX-01		DC (3.5mm)	¥3.5	200	47.5 37.5 47.0	0.0837	8.9	Material:Gold plated connectors High strength textile cable Nondestructive quality Length: 1M
		TYPE-C	¥6.5					
		5G	¥7.5					
GX-03		TYPE-C	¥5.5	200/20	64.0 37.0 44.0	0.1042	5.7	Material:NYLON Length: 1.2M
		5G	¥7.0					
GX-02		DC (3.5mm)	¥2.8	200/10	38.0 37.0 32.0	0.0450	6.6	Material:TPE Length: 1.5M
GX-04		DC (3.5mm)	¥2.5	200/10	37.5 37.0 32.0	0.0444	7.45	Connect speakers to portable audio equipment, guitars, speaker functions, etc. Connect iphone to amplifier or other audio-visual equipment This Lightning to 6.352 mm 1/4" TS mono Y-cable splitter is ideal for connecting laptops or PCs with jack speaker outputs to devices with 2 x 6.35 mm jack inputs-such as mixing Station.
		TYPE-C	¥4.5					
		5G	¥5.7					
GX-05		DC (3.5mm)	¥2.5	200/10	37.5 37.0 32.0	0.0444	6.4	Plug and play:Connect a mobile phone, speaker, laptop or PC with a Lightning jack speaker output to a device with a 2 x 6.35 mm jack input. The 24K gold-plated connectors are corrosion resistant and ensure the best sound quality. No need to install drivers, plug and play High-quality wire: nylon braid protects your cable. This Lightning to dual 6.35 mm mono plug audio cable is equipped with a nylon braid to prevent scratches and abrasion and prolong its service life.
TYPE-C	¥4.5							
GX-05L		5G	¥5.7					
GX-06		DC (3.5mm)	¥2.5	200/10	37.5 37.0 32.0	0.0444	7.4	Premium Sound Quality: We adopt the upgraded audio chips to ensures stable and no loss transmission of audio signal, provide flawlessly music transmission and sound quality. Double-Braided: Constructed with double-braided exterior provides maximum's durability. This Car AUX Cable can stand wear and tear. 3.28ft / 1m in length is enough to connecting up Audio devices both in car and home.
		TYPE-C	¥4.5					
		5G	¥5.7					





















			DC (3.5mm)	¥1.95	500/10	37.5	37.0	44.0	0.0611	12.4	Material:TPE Length: 1M
NEW			DC (3.5mm)	¥3.5	200	37.5	37.0	32.0	0.0444	24.7	Material:NYLON Length: 2M
NEW			TYPE-C	¥6.0	200	37.5	37.0	32.0	0.0444	24.7	Material:NYLON Length: 2M
NEW			5G	¥7.5	200	37.5	37.0	32.0	0.0444	24.7	Material:NYLON Length: 2M
NEW			5G	¥11.0	200	37.5	37.0	32.0	0.0444	6.1	The transfer speed of this USB Camera Adapter is 25MB/S-30MB/S which is 2 times faster than the speed of other products,the best way to copy photos and video to the iPhone or iPad in a short time; Plug and Play & easy to use,no need to download APP,share your photos and videos from your camera to your social network freely,No need to use PC anymore,Fast and easy !
NEW			TYPE-C	¥3.8	200	37.5	37.0	32.0	0.0444	5.9	By supporting USB 3.0 and OTG, this adapter allows USB-C equipped smartphones and tablets to read from removable media as the host, offering data transfer speeds of up to 5 Gbps between connected devices. It also supports up to 2.4 Amps of power output for charging your devices.
NEW			TYPE-C+5G	¥17.0	200	37.5	37.0	32.0	0.0444	6.5	PLUG AND PLAY – Easy to Use, No App needed and no need to take out the camera's memory card. (For iOS 9.2 to 12) Just wait for 3-5 seconds after connecting to your device, there's a pop-up for you to import photos/videos from digital camera to iPhone/iPad directly. (For iOS 13)There's no pop-up, please click 'Photos' APP on iOS 13 device and find 'Import'. you can also read photo or video directly on iOS 13 system.

GERLAX®

























CAR CHARGER

ADD:New Asia International Digital City No, 55 Xiti Erma Rosd, Guangzhou

Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

型号	产品图	产品图	卖点	类型	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Product Picture	SELLING POINTS	Type	Price rmb	OUTER CTN/ INNER	Carton size (CM)			CBM/CTN (m ³)	KG/CTN	SPECIFICATIONS
C8T			55W with cable 1USB-C+1USB-A (grey)	C-C	¥12.5	420/6	74.0	40.5	53.5	0.1603		1. Input:DC12-24V 50-60Hz 0.6A 2. TYPE-C output: DC5V/3A,9V/3A,12V/2.5A (30W) USB-A output: DC5V/3A,9V/2.77A,12V/2.25A (25W) 3. Material:aluminium alloy+ABS 4.Support Samsung Fast Charging&FCP/SCP Fast Charging&Xiaomi support ultra-fast charging&QC3.0 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 6.Selling point:Colorful ambient light 7.Line length: 1m
C8L			55W with cable 1USB-C+1USB-A (grey)	C-IP	¥13.5	420/6	74.0	40.5	53.5	0.1603		1. Input:DC12-24V 50-60Hz 0.6A 2. TYPE-C output: DC5V/3A,9V/3A,12V/2.5A (30W) USB-A output: DC5V/3A,9V/2.77A,12V/2.25A (25W) 3. Material:aluminium alloy+ABS 4. Support charging 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 6. Selling point:Colorful ambient light 7. Line length: 1m
C2V			2.4A with cable 2USB-A (White)	MICRO	¥4.5	300	54.0	47.0	37.0	0.1016	15.7	
C2T			2.4A with cable 2USB-A (White)	TYPE-C	¥5.2	300	54.0	47.0	37.0	0.1016	15.7	Charger: 1.Input: DC12-24V 2.Output: Dual USB 2.4A Data cable: 3.Adaptor: Micro USB 4.Support charging and sync Overcurrent and overvoltage protections for the circuit; Short circuit protection, Intelligent identification IC 5.Data line with D3
C2L			2.4A with cable 2USB-A (White)	5G	¥5.3	300	54.0	47.0	37.0	0.1016	15.7	
C3L			3A with cable 2USB-A (White)	5G	¥5.6	300	73.0	40.0	51.5	0.1608	19.55	Charger: 1.Input: DC12-24V 2.Output: Dual USB 3A Data cable: 3.Adaptor: Lightning USB 4.Support charging and sync Overcurrent and overvoltage protections for the circuit; Short circuit protection, Intelligent identification IC 5.Data line with D3
C4S			3A 2USB-A (tarnish)	Without Cable	¥4.8	200	67.0	33.0	32.5	0.0786	8.07	Dual USB 1.Input: DC12-24V 2.Output: Dual USB 3A
C4V			3A with cable 2USB-A (tarnish)	MICRO	¥5.8	300	73.0	40.0	51.5	0.1608	20.5	Charger: 1.Input: DC12-24V 2.Output: Dual USB 3A Data cable: 3.Adaptor: Micro USB 4.Support charging and sync Overcurrent and overvoltage protections for the circuit; Short circuit protection, Intelligent identification IC 5.Data line with D3
C4T			3A with cable 2USB-A (tarnish)	TYPE-C	¥6.5	300	73.0	40.0	51.5	0.1608	20.5	Charger: 1.Input: DC12-24V 2.Output: Dual USB 3A Data cable: 3.Adaptor: Micro USB 4.Support charging and sync Overcurrent and overvoltage protections for the circuit; Short circuit protection, Intelligent identification IC 5.Data line with D3
C4L			3A with cable 2USB-A (tarnish)	5G	¥6.6	300	73.0	40.0	51.5	0.1608	20.5	Charger: 1.Input: DC12-24V 2.Output: Dual USB 3A Data cable: 3.Adaptor: Micro USB 4.Support charging and sync Overcurrent and overvoltage protections for the circuit; Short circuit protection, Intelligent identification IC 5.Data line with D3

C5S			18W/QC3.0 1USB-A with LED light (tarnish)	Without Cable	¥6.0	200	67.0	33.0	32.5	0.0786	7.8	Single USB*1 1.Input: DC12-24V 2.Output: Dual USB 3A 3.Material: aluminum alloy 4.QC3.0&18W with LED light
C5V			18W/QC3.0 with cable 1USB-A with LED light (tarnish)	MICRO	¥6.4	300	54.0	47.0	37.0	0.1016	16.7	Charger: 1.Input: DC12-24V 2.Output: Dual USB 3A 3.Material: aluminum alloy 4.QC3.0&18W with LED light Data cable: 3.Adaptor: Micro USB 4.Support charging and sync Overcurrent and overvoltage protections for the circuit; Short circuit protection, Intelligent identification IC 5.Data line with D3
C5T			18W/QC3.0 with cable 1USB-A with LED light (tarnish)	TYPE-C	¥7.1	300	54.0	47.0	37.0	0.1016	16.7	1.Input: DC12-24V 2.Output: Dual USB 3A 3.Material: aluminum alloy 4.QC3.0&18W with LED light Data cable: 3.Adaptor: Micro USB 4.Support charging and sync Overcurrent and overvoltage protections for the circuit; Short circuit protection, Intelligent identification IC 5.Data line with D3
C5L			18W/QC3.0 with cable 1USB-A with LED light (tarnish)	5G	¥7.2	300	54.0	47.0	37.0	0.1016	16.7	
C800			55W/QC3.0 1USB-C+1USB-A (Black)	Without Cable	¥9.5	300/50	73.0	40.0	51.5	0.1016		1. Input:DC12-24V 50-60Hz 0.6A 2. TYPE-C output: DC5V/3A,9V/3A,12V/2.5A (30W) USB-A output: DC5V/3A,9V/2.77A,12V/2.25A (25W) 3. Material:aluminum alloy +ABS 4.Support Samsung Fast Charging&FCP/SCP Fast Charging&Xiaomi support ultra-fast charging&QC3.0 5. Overcurrent and overvoltage protections for the circuit; Short circuit protection, blast-proof, Intelligent identification IC 6.Product color: grey 7.Selling point:Seven Colored Lights
C900			QC3.0 1USB-C+1USB-A (Black)	Without Cable	¥7.6	420/70	74.0	40.5	53.5	0.1603		1. Input:DC12-24V 2. TYPE-C output: 5V/3A, 9V/3A,12V/2.5A USB-A output: 5V/3A, 9V/2.5A,12V1.875A 3. Material: Aluminum alloy +ABS 4.QC3.0&FCP, SCP, Samsung support fast charging, Xiaomi support ultra-fast charging
C11V			30W 1USB-A (tarnish)	MICRO	¥5.9	360/6	73.0	40.0	51.5	0.1504		1. Input :DC10-24V 50/60Hz 0.5A 2. USB-A output: 5V/3A, 9V/3A,12V/2.5A 3. Material: Aluminum alloy +ABS 4.Support QC3.0 fast charge &Support vivo, oppo fast charging 5.Line length: 1m
C11T			30W 1USB-A (tarnish)	TYPE-C	¥6.2	360/6	73.0	40.0	51.5	0.1504		1. Input :DC10-24V 50/60Hz 0.5A 2. USB-A output: 5V/3A, 9V/3A,12V/2.5A 3. Material: Aluminum alloy +ABS 4.Support QC3.0 fast charge &Support Huawei, vivo, oppo fast charging 5.Line length: 1m
C11L			30W 1USB-A (tarnish)	5G	¥6.4	360/6	73.0	40.0	51.5	0.1504		1. Input :DC10-24V 50/60Hz 0.5A 2. USB-A output: 5V/3A, 9V/3A,12V/2.5A 3. Material: Aluminum alloy +ABS 4.Support charging 5.Line length: 1m
C12V			30W 1USB-A (tarnish)	MICRO	¥7.5	360/6	73.0	40.0	51.5	0.1504		1. Input :DC10-24V 50/60Hz 0.5A 2. USB-A output: 5V/3A, 9V/3A,12V/2.5A 3. Material: Aluminum alloy 4.Support QC3.0 fast charge &Support vivo, oppo fast charging 5.Line length: 1m
C12T			30W 1USB-A (tarnish)	TYPE-C	¥7.8	360/6	73.0	40.0	51.5	0.1504		1. Input :DC10-24V 50/60Hz 0.5A 2. USB-A output: 5V/3A, 9V/3A,12V/2.5A 3. Material: Aluminum alloy 4.Support QC3.0 fast charge & Xiaomi support ultra-fast charging&Support Huawei, vivo, oppo fast charging 5.Line length: 1m
C12L			30W 1USB-A (tarnish)	5G	¥8.0	360/6	73.0	40.0	51.5	0.1504		1. Input :DC10-24V 50/60Hz 0.5A 2. USB-A output: 5V/3A, 9V/3A,12V/2.5A 3. Material: Aluminum alloy 4.Support charging 5.Line length: 1m

			PD20W/QC3.0 USB-C+USB-A (tarnish)	Without Cable	¥12.0	200/10	67.0	33.0	32.5	0.0719	9.9	Input:12V-24V Output PD: 5V/5A=3A/9V=2A/12=1.5A Output USB: 5V=3A/9V=2.2A/12=1.67A
NEW			PD38W/QC3.0 USB-C+USB-A (tarnish)	Without Cable	¥13.0	200/10	67.0	33.0	32.5	0.0719	9.6	
NEW			PD68W/QC3.0 2USB-C+1USB-A (Black)	Without Cable	¥28.0	100	37.0	34.5	46.5	0.0594	10.7	Input:12V-32V 50-60Hz TYPE-C1: 30W/5V=3.4A/9V=2.7A/12=2A TYPE-C2: 20W/5V=3A/9V=2A/12V=1.5A
			PD50W 2USB-C (White)	Without Cable	¥18.0	200	59.5	28.0	38.0	0.0633	13.2	Input:12V-32V 50-60Hz TYPE-C1: 25V/5A=3.4A/9V=2.7A/12=2A TYPE-C2: 25V/5A=3.4A/9V=2.7A/12=2A
			PD50W 2USB-C (Black)	Without Cable	¥18.0	200	59.5	28.0	38.0	0.0633	13.2	
NEW			PD20W+QC3.0 USB-C+USB-A (White)	Without Cable	¥13.5	200	59.5	28.0	38.0	0.0633	11.92	Input:DC12-24V Output1:QC3.0 5V=3A/9V=2A/12V1.67A Output2:PD/5V=3A
NEW			PD20W+QC3.0 USB-C+USB-A (White, Black)	Without Cable	¥11.5	200	59.5	28.0	38.0	0.0633	8.32	Input:DC12-24V Output1: (PD) 18W Output2:(AUTO-ID)5V=2.4A QC 3.0 Fast car charger
NEW			3.4A+QC3.0 USB-C+2USB-A (White)	Without Cable	¥9.0	100	54.0	31.5	41.5	0.0706	7.25	Input:12V-24V USB1 QC3.0: 5V/3A=3A/9V=2A/12=1.67A USB12+USB3: 5V=3.4A
NEW			PD20W+QC3.0 with cable USB-C+USB-A (White)	C-C C-IP	¥18.5 ¥21.5	100	35.5	32.5	40.0	0.0462	9.9	Input:DC12-24V Output1: QC3.0 5V=3A/9V=2A/12V1.67A Output2:PD/5V=3A Line length: 1M
NEW			PD20W+QC3.0 with cable USB-C+USB-A (tarnish)	MICRO TYPE-C 5G	¥15.5 ¥16.0 ¥16.8	100	37.5	35.0	42.5	0.0558	9.35	Material: metal 38W Car charger PD20W and USB 18W Two mobile phones are charged at the same time, can show fast charging
NEW			PD20W+QC3.0 with cable USB-C+USB-A (tarnish)	MICRO TYPE-C 5G	¥16.0 ¥16.5 ¥16.8	100	37.5	35.0	42.5	0.0558	9.17	Material: metal 38W Car charger PD20W and USB 18W Two mobile phones are charged at the same time, can show fast charging
NEW			PD18W+QC3.0 with cable USB-C+2USB-A (White)	MICRO TYPE-C 5G	¥10.6 ¥11.0 ¥12.4	100	54.0	31.5	41.5	0.0706	9.65	Input:12V-24V USB1 QC3.0: 5V/3A=3A/9V=2A/12=1.67A USB12+USB3: 5V=3.4A Line length: 1M

HOT C1			QC3.0 with cable 2USB-A (White)	MICRO	¥8.9	100	37.5	35.0	42.5	0.0558	8.45	Input:DC12-24V Output:QC3.0 5V=3A/9V=2A/12V1.67A Output2:DC5V=2.4A Line length: 1M
				TYPE-C	¥9.4							
				5G	¥9.7							
HOT GC-06			QC3.0 with cable 3USB-A (White)	MICRO	¥11.0	100	37.5	35.0	42.5	0.0558	9.42	Input:DC12-24V Output:18W+3A(MAX) Working temperature:-10°C-50°C QC 3.0 Fast car charger
				TYPE-C	¥11.6							
				5G	¥12.0							

























GERLAX®

POWER BANK

ADD:New Asia International Digital City No, 55 Xiti Erma Road, Guangzhou

Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费)

型号	产品图	产品图	卖点	价格 rmb	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Product Picture	SELLING POINTS	Price rmb	OUTER CTN/ INNER BOX (PCS)	Carton size (CM)			CBM/CTN (m³)	KG/CTN	SPECIFICATIONS
P102B			10000mAh 2.4A (Black)	¥17.90	50	47.5	21.5	18.0	0.0213	12.5	1. Size:139*67.5*16mm 2. Weight: 3. Input: Dual Input DC5V/2.4A 4. Output: Dual USB DC5V/2.4A/AUTO-ID 5. Battery: Lithium Polymer 6. Battery Capacity:10000mAh/5V/50Wh 7. Rated Capacity: 6500mAh 8. Material:ABS 9. Overcurrent and overvoltage protections for the circuit
P20			10000mAh with cable 2.4A (Black, White)	¥39.00	50	45.5	28.5	16.0	0.0207	13.4	Battery: Lithium Polymer Battery Capacity: 10000mAh/3.7V/37Wh Rated Capacity: 6800mAh(5V=2.4A) Micro Input:DC5V=2.4A(Max) Type-c Input:DC5V=2.4A(Max) USB1/2 Output:DC5V=2.4A(Max) Size:105*65*24mm Net Weight:230g
P3T			20000mAh with cable 2.4A (Black, White)	¥47.50	40	37.0	35.0	18.0	0.0233	18.8	Battery: Lithium Polymer Battery Capacity: 20000mAh/3.7V/74Wh Rated Capacity: 13600mAh(5V=2.4A) Micro Input:DC5V=2.4A(Max) Type-c Input:DC5V=2.4A(Max) USB1/2 Output:DC5V=2.4A(Max) Size:146*70*28mm Net Weight:411g
P10T			20000mAh PD20W & QC3.0 (Black)	¥49.00	40	37.5	35.0	18.0	0.0236	18.15	Battery: Lithium Polymer Battery Capacity: 20000mAh/3.7V/74Wh Rated Capacity: 13600mAh(5V=2.4A) Micro Input:DC5V=2.4A/9V=2A Type-c Input:12V=1.66A/9V=2.22A/5V=2.6A USB Output:12V=1.5A/9V=2A/5V=3A Type-c Output:12V=1.66A/9V=2.22A/5V=3A Size:147*67.5*28mm Net Weight:405g
P101			10000mAh 2.4A (Black, White)	¥21.00	50	47.5	21.5	18.0	0.0184	13.4	Battery: Lithium Polymer Battery Capacity: 10000mAh/3.7V/37Wh Rated Capacity: 5000mAh(5V=2.4A) Micro Input:DC5V=2.4A(Max) Type-c Input:DC5V=2.4A(Max) USB1/2 Output:DC5V=2.4A(Max) Size:142*68*15.6mm Net Weight:217g
P103			10000mAh 2.4A (Black)	¥29.00	40	37.5	35.0	18.0	0.0236	11.35	Battery: Lithium Polymer Battery Capacity: 10000mAh/3.7V/37Wh Rated Capacity: 5000mAh(5V=2.4A) Micro Input:DC5V=2.4A(Max) Type-c Input:DC5V=2.4A(Max) USB1/2 Output:DC5V=2.4A(Max) Size:146.8*69.5*19.5mm Net Weight:236g
P104			10000mAh 22.5W Full protocol fast charge (Black, White)	¥44.50	40	37.5	35.0	18.0	0.0236	11.6	Battery: Lithium Polymer Battery Capacity: 10000mAh/3.7V/37Wh Rated Capacity: 6000mAh(5V=2A) USB Input:DC5V=3A Type-c Input:5V=3A/9V=2A/12V=1.5A/PD18W USB output:4.5V=5A/5V=4.5A/9V=2A/12V=1.5A/PD=22.5W Type-c output:5V=3A/9V=2.23A/12V=1.67A/PD20W Lighting output:5V=3A Size:150*69.5*17.8mm Net Weight:180g
P105P			10000mAh PD20W Wireless-15W (Black)	¥83.50	40	37.5	35.0	18.0	0.0236	18.1	Battery: Lithium Polymer Battery Capacity: 10000mAh/3.7V/37Wh Rated Capacity: 5200mAh(5V=3A) Type-c Input:DC5V=2.5/9V=2A/12V=1.5A Type-c Output:5V=3A/9V=2.22A/12V=1.66A Wireless Output:5W/7.5W/10W/15W Size:106*67*19mm Net Weight:210g
P106P			10000mAh PD20W Wireless-15W (Black)	¥56.70	40	38.5	37.5	19.0	0.0274	19.45	Battery: Lithium Polymer Battery Capacity: 10000mAh/3.7V/37Wh Rated Capacity: 5200mAh(5V=3A) Type-c Input:5V=2.6A/9V=2A/12V=1.5A Type-c Output:5V=3A/9V=2.22A/12V=1.66A USB1/2 Output:5V=4.5/5V=3A/9V=2A/12V=1.5A Size:87*50*33mm Net Weight:193g
P107			10000mAh 22.5W Full protocol fast charge Wireless-15W (Black, White)	¥69.50	40	37.5	35.0	18.0	0.0236	18.15	Battery: Lithium Polymer Battery Capacity: 10000mAh/3.7V/37Wh Rated Capacity: 5200mAh(5V=3A) Type-c Input:5V=2.5A/9V=2A/12V=1.5A Type-c Output:5V=3A/9V=2.22A/12V=1.66A USB1/2 Output:5V=4.5A/4.5V=5A/12V=1.5A Size:112.5*69*21.5mm Net Weight:7g
P108			10000mAh 22.5W Full protocol fast charge Wireless-15W Watch wireless-20W (Black, White)	¥82.00	40	37.5	35.0	18.0	0.0236	12.4	Battery: Lithium Polymer Battery Capacity: 10000mAh/3.7V/37Wh Rated Capacity: 5200mAh(5V=3A) Type-c Input:5V=2.5A/9V=2A/12V=1.5A Type-c Output:5V=3A/9V=2.22A/12V=1.66A USB1/2 Output:5V=4.5A/4.5V=5A/12V=1.5A Size:112.5*69*21.5mm Net Weight:7g

NEW			10000mAh 2.4A (Black, White)	¥27.00	40	38.0	35.0	18.0	0.0239	17.05	Battery: Lithium Polymer Battery Capacity: 10000mAh/3.7V/37Wh Rated Capacity: 6500mAh(5V=2.4A) USB Input:5V=2.4A Micro Input:5V=2.4A Type-c Input:5V=2.4A Type-c output:5V=2.4A Micro output:5V=2.4A USB1/2 output:5V=2.4A Lightning output:5V=2.4A Size:147*68*21mm Net Weight:240g
NEW			10000mAh 2.4A (Black, White)	¥26.00	40	37.5	35.0	18.0	0.0236	10.8	Battery: Lithium Polymer Battery Capacity: 10000mAh/3.7V/37Wh Rated Capacity: 6500mAh(5V=2.4A) USB Input:5V=2.4A Micro Input:5V=2.4A Type-c Input:5V=2.4A Type-c output:5V=2.4A Micro output:5V=2.4A USB1/2 output:5V=2.4A Lightning output:5V=2.4A Size:150*70.5*19mm Net Weight:150.4g
			10000mAh 22.5W Full protocol fast charge (Black, White)	¥26.00	50	38.5	36.0	19.5	0.0270	13.15	1. Capacity:10000 mAh Rated Capacity: 5300mAh 2.TYPE-C Input:DC 5V=2.6A 9V=2A 12V=1.5A 3.TYPE-C Output:DC 5V=3A 9V=2.22A 12V=1.67A 4.USB 1/2 Output:DC 5V=3A 5V=4.5A 9V=2A 12V=1.5A 5.Display: LED digital display power 6.Material: ABS+PC flame retardant 7.Size:145*68*16mmmm 8.Weight:227g
NEW			20000mAh 2.4A (Black, White)	¥33.50	40	37.5	35.0	18.0	0.0236	10.29	Battery: Lithium Polymer Battery Capacity: 20000mAh/3.7V/74Wh Rated Capacity: 10600mAh(5V=2A) Micro Input:DC5V=2.4A(Max) Type-c Input:DC5V=2.4A(Max) USB1/2 Output:DC5V=2.4A(Max) Size:142*68*27.8mm Net Weight:404.5g
NEW			20000mAh 2.4A (Black)	¥43.50	40	38.5	37.5	19.0	0.0274	10.55	Battery: Lithium Polymer Battery Capacity: 20000mAh/3.7V/74Wh Rated Capacity: 10600mAh(5V=2A) Micro Input:DC5V=2.4A(Max) Type-c Input:DC5V=2.4A(Max) USB1/2 Output:DC5V=2.4A(Max) Size:150*69.5*31.4mm Net Weight:411.5g
NEW			20000mAh 22.5W Full protocol fast charge (Black, White)	¥58.50	40	37.5	35.0	18.0	0.0236	18.8	Battery: Lithium Polymer Battery Capacity: 20000mAh/3.7V/74Wh Rated Capacity: 10600mAh(5V=2A) USB Input:DC5V=3A Type-c Input:5V=3A/9V=2A/12V=1.5A/PD18W USB output:4.5V=5A/5V=4.5A/9V=2A/12V=1.5A/PD=22.5W Type-c output:5V=3A/9V=2.23A/12V=1.67A/PD20W Lightning output:5V=3A Size:150*69.5*29.5mm Net Weight:422g
NEW			20000mAh 2.4A (Black, White)	¥41.00	40	40.0	38.8	20.8	0.0323	18.14	Battery: Lithium Polymer Battery Capacity: 20000mAh/3.7V/74Wh Rated Capacity: 13000mAh(5V=2.4A) USB Input:5V=2.4A Micro Input:5V=2.4A Type-c Input:5V=2.4A Type-c output:5V=2.4A Micro output:5V=2.4A USB1/2 output:5V=2.4A Lightning output:5V=2.4A Size:147*68*32mm Net Weight:420g
NEW			20000mAh 2.4A (Black, White)	¥39.50	40	38.5	37.5	19.0	0.0274	17.8	Battery: Lithium Polymer Battery Capacity: 20000mAh/3.7V/74Wh Rated Capacity: 13000mAh(5V=2.4A) USB Input:5V=2.4A Micro Input:5V=2.4A Type-c Input:5V=2.4A Type-c output:5V=2.4A Micro output:5V=2.4A USB1/2 output:5V=2.4A Lightning output:5V=2.4A Size:150*70.5*27mm Net Weight:260g
			20000mAh 3A (Black, White)	¥36.00	40	38.5	37.5	19.0	0.0274	19.4	1.Capacity:20000 mAh Rated Capacity: 13000mAh 2.USB Input: 5V=3A 3.TYPE-C Input:5V=3A 4.Micro Input: 5V=2A 5.USB1/2 Output:5V=3A 6.Micro Output:5V=2A 7.TYPE-C Output:5V=3A 8.lightning Output: 5V=2A 9.Display: LED digital display power 10.Material: ABS+PC flame retardant
			20000mAh 3A (Black, White)	¥38.00	40	38.5	37.5	19.0	0.0274	18.4	1.Capacity:20000 mAh Rated Capacity: 13000mAh 2.USB Input: 5V=3A 3.TYPE-C Input:5V=3A 4.Micro Input: 5V=2A 5.USB Output:5V=3A 6.Micro Output:5V=2A 7.TYPE-C Output:5V=3A 8.lightning Output: 5V=2A 9.Display: LED digital display power 10.Material: ABS+PC
			20000mAh 3A (Black)	¥38.50	40	38.5	37.5	19.0	0.0274	19.25	1.Capacity:20000 mAh Rated Capacity: 13000mAh 2.USB Input: 5V=3A 3.TYPE-C Input:5V=3A 4.Micro Input: 5V=2A 5.USB1/2 Output:5V=3A 6.Micro Output:5V=2A 7.TYPE-C Output:5V=3A 8.lightning Output: 5V=2A 9.Display: LED digital display power 10.Material: ABS+PC
NEW			1.4in1 Comes With Cable Multi-output Mobile Power Supply 2.Removable charger cables (Black, White)	¥38.50	40	38.5	37.5	19.0	0.0274	18.9	1.Capacity:20000mAh 2.Rated Capacity: 13000mAh 3.USB Input: 5V=3A 4.TYPE-C Input:5V=3A 5.USB Output:5V=3A 6.Micro Output:5V=3A 7.TYPE-C Output:5V=3A 8.lightning Output: 5V=3A 9.Display: LED digital display power 10.Material: ABS+PC flame retardant 11.Size:150*69.5*31.2mm 12.Weight:423g

















P301			30000mAh 3A (Black, White)	¥50.80	30	27.0	38.5	31.5	0.0327	21.35	<ol style="list-style-type: none"> Capacity: 30000 mAh Rated Capacity: 19500mAh USB Input: 5V=3A TYPE-C Input: 5V=3A Micro Input: 5V=2A USB*4 Output: 5V=3A TYPE-C Output: 5V=3A Lightning Output: 5V=2A Display: LED digital display power Material: ABS+PC flame retardant
P302			30000mAh 3A LED lighting fixtures (Black)	¥58.30	30	27.0	38.5	31.5	0.0327	21.3	<ol style="list-style-type: none"> Capacity: 30000 mAh Rated Capacity: 19500mAh TYPE-C Input: 5V=3A Micro Input: 5V=2A Lightning Input: 5V=2A USB*4 Output: 5V=3A TYPE-C Output: 5V=3A Lightning Output: 5V=2A Display: LED digital display power Material: ABS+PC
P401			40000mAh 3A LED lighting fixtures (Black)	¥70.40	20	38.0	38.0	21.5	0.0310	18.3	<ol style="list-style-type: none"> Capacity: 40000 mAh Rated Capacity: 26000mAh TYPE-C Input: 5V=3A Micro Input: 5V=2A Lightning Input: 5V=2A USB*4 Output: 5V=3A TYPE-C Output: 5V=3A Lightning Output: 5V=2A Display: LED digital display power Material: ABS+PC
P501			50000mAh 3A LED lighting fixtures (Black)	¥83.30	20	38.0	38.0	21.5	0.0310	21.9	<ol style="list-style-type: none"> Capacity: 50000 mAh Rated Capacity: 32500mAh TYPE-C Input: 5V=3A Micro Input: 5V=2A Lightning Input: 5V=2A USB*4 Output: 5V=3A TYPE-C Output: 5V=3A Lightning Output: 5V=2A Display: LED digital display power Material: ABS+PC

GERLAX®

MEMORY CARD











ADD:New Asia International Digital City No, 55 Xiti Erma Rosd, Guangzhou

Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

型号	产品图	产品图	容量	详情	数量/箱	箱规			立方数	重量/箱
Model	Product Picture	Product Picture	Capacity	Standard	OUTER CTN/ INNER BOX (PCS)	Carton size (CM)			CBM/CTN (m ³)	KG/CTN
内存卡										
N2			2GB	1. 级别: Class 10 2. USB 协议: USB2.0 3. 存储方式: MLC 4. 读取速度: 60MB/s	1000/20	51.5	42.5	16.0	0.0350	
N4			4GB	1. 级别: Class 10 2. USB 协议: USB2.0 3. 存储方式: MLC 4. 读取速度: 60MB/s	1000/20	51.5	42.5	16.0	0.0350	
N8			8GB	1. 级别: Class 10 2. USB 协议: USB2.0 3. 存储方式: MLC 4. 读取速度: 75MB/s	1000/20	51.5	42.5	16.0	0.0350	
N16			16GB	1. 级别: Class 10 2. USB 协议: USB3.0 3. 存储方式: MLC 4. 读取速度: 90MB/s	1000/20	51.5	42.5	16.0	0.0350	
N32			32GB	1. 级别: Class 10 2. USB 协议: USB3.0 3. 存储方式: MLC 4. 读取速度: 90MB/s	1000/20	51.5	42.5	16.0	0.0350	
N64			64GB	1. 级别: Class10 U3 2. USB 协议: USB3.0 3. 存储方式: MLC 4. 读取速度: 95MB/s	1000/20	51.5	42.5	16.0	0.0350	
N128			128GB	1. 级别: Class10 U3 2. USB 协议: USB3.0 3. 存储方式: MLC 4. 读取速度: 100MB/s	1000/20	51.5	42.5	16.0	0.0350	
N256			256GB	1. 级别: Class10 U3 2. USB 协议: USB3.0 3. 存储方式: MLC 4. 读取速度: 100MB/s	1000/20	51.5	42.5	16.0	0.0350	

USB

U5-2 USB 3.0			2GB	Capacity: 1.85G~1.9GB Photos:8MP 9MP 12P video: 10Mbps HD 17Mbps FullHD		40.5	40.5	28.5	0.0467	10.9
U5-4 USB 3.0			4GB	Capacity: 3.65G~3.7GB Photos:8MP 9MP 12P video: 10Mbps HD 17Mbps FullHD		40.5	40.5	28.5	0.0467	10.9
U5-8 USB 3.0			8GB	Capacity: 7.4G~7.6GB Photos:8MP 9MP 12P video: 10Mbps HD 17Mbps FullHD		40.5	40.5	28.5	0.0467	10.9
U5-16 USB 3.0			16GB	Capacity: 14.9G~15.4GB Photos:8MP 9MP 12P video: 10Mbps HD 17Mbps FullHD		40.5	40.5	28.5	0.0467	10.9
U5-32 USB 3.0			32GB	Capacity: 29.8G~30.3GB Photos:8MP 9MP 12P video: 10Mbps HD 17Mbps FullHD		40.5	40.5	28.5	0.0467	10.9
U5-64 USB 3.0			64GB	Capacity: 59.6G~60.1GB Photos:8MP 9MP 12P video: 10Mbps HD 17Mbps FullHD		40.5	40.5	28.5	0.0467	10.9
U5-128 USB 3.0			128GB	Capacity: 111.2G~111.7GB Photos:8MP 9MP 12P video: 10Mbps HD 17Mbps FullHD		40.5	40.5	28.5	0.0467	10.9
U2			2GB	1. USB 协议: USB2.0 2. 接口: USB2.0 3. 材质: 锌合金+ABS+UDP 4. 颜色: 银色 5.尺寸: 25.6×12.2×4.6mm 6.重量: 9.4g 7.写入速度: 6-10MB/s; 读取速度: 15-25MB/s	1000/20	51.5	42.5	16.0	0.0350	10.90
U4			4GB							
U8			8GB							
U16			16GB							
U32			32GB							
U64			64GB							
U128			128GB							
U1-2			2GB	1. USB 协议: USB2.0 2. 接口: USB2.0 3. 材质: 锌合金+ABS+UDP 4. 颜色: 银色 5.尺寸: 25.6×12.2×4.6mm 6.重量: 7.写入速度: 6-10MB/s; 读取速度: 15-25MB/s	1000/20	42.5	40.5	30.0	0.0516	
U1-4			4GB							
U1-8			8GB							
U1-16			16GB							
U1-32			32GB							
U1-64			64GB							
U1-128			128GB							
UG3-16			16GB	1. USB 协议: USB3.0 2. 接口: USB3.0 3. 材质: 锌合金+BGA 4. 颜色: 银色 5.写入速度: 25MB/s; 读取速度: 80-130MB/s	500/20	51.5	45.5	31.0	0.0487	
UG3-32			32GB							
UG3-64			64GB							
UG3-128			128GB							
UG3-256			256GB							
UG2-16			16GB	1. USB 协议: USB3.0 2. 接口: USB3.0 3. 材质: 锌合金+BGA 4. 颜色: 银色 5.写入速度: 25MB/s; 读取速度: 80-130MB/s	500/20	48.0	40.5	29.0	0.0487	
UG2-32	32GB									
UG2-64	64GB									
UG2-128	128GB									


U4-2	 		2GB	1、USB协议: USB2.0 2、接口: USB2.0 3、材质: ABS+UDP 4、颜色: 黑+红 5、尺寸: 41.5*17.6*7.4mm 6、写入速度: 6-15MB/S 7、读取速度: 15-30MB/S	1000/20					
U4-4			4GB							
U4-8			8GB							
U4-16			16GB							
U4-32			32GB							
U4-64			64GB							
U4-128			128GB							
U4-256			256GB							

GERLAX[®]

VICE MATERIAL

ADD:New Asia International Digital City No, 55 Xiti Erma Rosd, Guangzhou

Shipping orders of 10,000 RMB or more, shipping to Guangzhou, Foshan, two regions do not charge postage.
(发货订单在1万元人民币以上, 发货到广州、佛山两个地区不收取邮费。)

型号	产品图	价格	数量/箱	箱规			立方数	重量/箱	详情
Model	Product Picture	Price rmb QTY	OUTER CTN/ INNER BOX (PCS)	Carton size (CM)			CBM/CTN (m ³)	KG/CTN	Standard
ZG2		¥450.0	1	125	40	57	0.2850	30	100*30*220CM 配60个挂钩 包装外面有木架材料加固
ZG3 Single		¥200.0	2	146	71	9	0.0933	10	60*25*160CM 配42个挂钩
ZG4 two-sided		¥260.0	2	146	71	9	0.0933	13	60*30*160CM 配66个挂钩
GERLAX-DZ1 BIG		¥0.8	400	57	41	16.5	0.0386	15.15	80*50+11 8C
DZ2		¥0.5	800	36	33	23.5	0.0279	12.9	51*30+11 8C
DZ3		¥0.8	800	51	21	35.5	0.0380	26.69	34*40+5

帽子1		¥25.0	200	60	51	51.5	0.1576	20.3	/
本子1		¥13.0	100	45	31	41.5	0.0579	30.4	/
笔2	 笔2	¥1.5	1000	49	32	21.5	0.0337	7.8	50一盒 1000一件
背包1	 背包1	¥28.0	40	61	41	54	0.1351	15.5	45*30*12CM
YF-L	 YF1-L 尺码表: 肩宽 45cm, 袖长 19cm, 衣长 70cm, 胸围 50cm	¥35.0	20/5	0	0	0	0.0000		Size: L Shoulder: 45CM Length: 70CM Bust: 50CM Material: Pure cotton
YF-XL	 YF1-XL 尺码表: 肩宽 47cm, 袖长 19cm, 衣长 72cm, 胸围 54cm	¥35.0	20/5	0	0	0	0.0000		Size: XL Shoulder: 47CM Length: 72CM Bust: 54CM Material: Pure cotton
YF-2XL	 YF1-2XL 尺码表: 肩宽 49cm, 袖长 19cm, 衣长 76cm, 胸围 57cm	¥35.0	20/5	0	0	0	0.0000		Size: 2XL Shoulder: 49CM Length: 76CM Bust: 57CM Material: Pure cotton
YF-3XL	 YF1-3XL 尺码表: 肩宽 52cm, 袖长 19cm, 衣长 78cm, 胸围 61cm	¥35.0	20/5	0	0	0	0.0000		Size: 3XL Shoulder: 52CM Length: 78CM Bust: 61CM Material: Pure cotton

<p>HB1</p>		<p>¥20.0</p>	<p>50</p>	<p>88</p>	<p>17</p>	<p>17.5</p>	<p>0.0262</p>	<p>13.3</p>	<p>80*100CM</p>
<p>HB2</p>		<p>¥0.8</p>	<p>900</p>	<p>46</p>	<p>33</p>	<p>25.5</p>	<p>0.0387</p>	<p>26.25</p>	<p>75*26CM</p>
<p>HB3</p>		<p>¥260.0</p>	<p>6</p>	<p>48.5</p>	<p>56</p>	<p>53</p>	<p>0.1439</p>	<p>11.2</p>	<p>Size: 47*15*20CM Line Length: 1.5M</p>
<p>品牌胶纸</p>		<p>¥8.0</p>	<p>60</p>	<p>63</p>	<p>43</p>	<p>30.5</p>	<p>0.0826</p>	<p>33.5</p>	